



Hybrid Marine Propulsion

Case History

VARD

Where:

Søvik, Norway

Specified:

2 x AvK[®] DSG 144 alternators and 3 x AvK[®] DSG 114 alternators

Purpose:

Hybrid power for the newly constructed Skandi Iceman offshore vessel.

AvK[®] alternators provide power in VARD's hybrid system

When the hybrid power system for a customer's new oil & gas offshore support vessel required alternators, it was a natural decision for VARD to specify **AvK**[®]. Over many years, VARD has come to rely on the **NEWAGE[®] | STAMFORD[®] | AvK**[®] sales, order handling and application engineering teams for their high level of technical knowledge and quick response to requirements. On this project, VARD were impressed with a particularly swift response in support of final contract negotiations with VARD's end customer, DOF Subsea.

VARD won the contract, which was to supply the onboard hybrid power system for the Skandi Iceman. DOF Subsea's new Anchor Handling Tug Supply (AHTS) vessel is designed for offshore operation in the oil & gas sector.

NEWAGE[°] **STAMFORD**[°] **AvK**[°] Powering the world with confidence since 1904



VARD supplied a rugged hybrid power system to ensure constant operation across the globe

In addition to the features of conventional platform supply vessels, AHTS vessels have winches for towing and anchor handling, and an open stern that allows anchors to be brought on deck.

The Skandi Iceman is designed to be deployable worldwide, and able to operate continuously in order to pay back its investment. The vessel's specification called for high speed, low fuel consumption, excellent manoeuvrability and stability. VARD ensured the overall power system achieved the internationally recognised DNV certification, while DNV Green Passport accreditation was provided by

NEWAGE[®] | STAMFORD[®] | AvK[®]

DOF Subsea called for a number of modifications, which VARD and

NEWAGE® | **STAMFORD®** | **AvK®** collaborated on and successfully delivered. The automatic voltage regulator had to be in a

separate box from the alternator, while a custom redesign of the alternator's external dimensions was required to fit into limited space in the machining room. Other bespoke work included oil supply and oil cooling of sleeve bearings, plus the locations of water connections and of power cable entry. The system benefits from IP44 enclosure protection with an air/water heat exchanger.

Because of the vessel's deck machinery and its Diesel Electric Propulsion (DEP) capability, including tunnel thrusters and acipod thruster, the power system had to be able to handle high load steps.





Five **AvK**[®] alternators provide reliable power to the vessel's hybrid marine power system

The DOF Subsea design called for a number of modifications, which VARD and **NEWAGE[®] | STAMFORD[®] | AvK[®]** successfully delivered.

And because the vessel would have to operate in heavy seas, its power system had to be rugged enough to cope with the demands of a harsh marine environment.

The Skandi Iceman has now entered service in the North Sea with all its design requirements met by a power solution built around five alternators. Two AvK® DSG144n/10W alternators function as shaft alternators for nonpropulsive power - "hotel power" in marine terminology - and also for propulsive hybrid power. Three auxiliary generator sets fitted with AvK[®] DSG 114M1/8W alternators deliver power for the DEP system while manoeuvring, as well as power for deck machinery and the vessel's FiFi I+II specification fire fighting pumps. Between them, the two 5,500 kVA DSG 144 alternators and the three 3,000 kVA DSG 114 alternators meet the vessel's 20,000 kVA total power requirement.

For more information on the full range of **NEWAGE® | STAMFORD® | AvK**®

products and services visit: www.stamford-avk.com



©Copyright 2021, Cummins Generator Technologies Ltd. All Rights Reserved Cummins and the Cummins logo are registered marks of Cummins Inc. NEWAGE, STAMFORD and AvK are registered trade marks of Cummins Generator Technologies Ltd.

Part No: CS_MAR_VARD_P_EN_GS_02