

**STAMFORD®**

**STAMFORD® Alternator**  
**Industrial**  
**Ratings**

**Edition 3.1**

**NEWAGE® | STAMFORD® | AvK®**

Powering the world with confidence since 1904



## Introduction



### Rating Definitions

All ratings are based on Rise by Resistance measurement method. Ratings based on Embedded Temperature Device (ETD) measurement may be provided under application to Cummins Generator Technologies.

#### Thermal Insulation Class

Insulation class governs the maximum permissible temperature an alternator can operate without damaging the insulation system. Cummins Generator Technologies use Class H & Class F.

Insulation Class	Maximum Permissible Temperature
Class F	155 °C
Class H	180 °C

#### Temperature Rise

Temperature rise is the increase in temperature above ambient temperature 40 °C.

Temperature Rise	Temperature °C
Class B	80 °C
Class F	105 °C
Class H	125 °C

Standby application allows windings to run hotter than the Class H temperature rise limit, therefore for an ambient of 40 °C temperature rise 150 °C  
27 °C temperature rise 163 °C

### Generator Set Ratings

The tables below summarises the definitions according to ISO8528-1 for the generator set and a combination of ISO8528-3 and IEC60034-1 for the alternator.

Genset Rating (ISO8528-1)	Emergency Standby Power (ESP)	Limited Time Prime (LTP)	Prime Rated Power (PRP)	Continuous Operating Power (COP)
<b>Load type</b>	Variable	Constant	Variable	Constant
<b>Annual operating hours</b>	200	500	Unlimited	Unlimited
<b>Average load</b>	70%	100%	70%	100%
<b>Overload</b>	No	No	10% (1 hour in every 12 Hrs)	No
<b>Alternator Rating (NEMA MG1-32)</b>	Standby	Standby	Continuous	Continuous
<b>Duty Cycle (IEC 60034-1)</b>	S10	S10	S1	S1
<b>Alternator Ratings</b>	Standby 150/40 Standby 163/27	Standby 150/40 Standby 163/27	Class H 125/40 Class F 105/40 Class B 80/40	Class H 125/40 Class F 105/40 Class B 80/40



## Introduction



### Derates

#### Ambient Temperature

If the ambient (alternator air inlet temperature) exceeds 40 °C then the alternator output rating must be reduced using the following tables.

#### STAMFORD S0 to S7 (P7)

Temperature °C	Multiplying Factor
45	0.97
50	0.94
55	0.91
60	0.88

#### STAMFORD P80 & S9

Utilisation	Class H	Class F	Class B
Temperature °C	Multiplying Factor	Multiplying Factor	Multiplying Factor
45	0.970	0.965	0.955
50	0.940	0.930	0.910
55	0.910	0.895	0.865
60	0.880	0.860	0.820

For ambient temperatures above 60 °C please consult applications engineering.

#### Altitude (Low Voltage ≤ 690V)

All ratings are based on altitude up to 1000 metres above sea level. If the altitude exceeds 1000m then the alternator output ratings must be derated using the following table.

Altitude above sea level in metres	Multiplying Factor
1500	0.97
2000	0.94
2500	0.91
3000	0.88
3500	0.85
4000	0.82

Please consult applications engineering department for

1. High Voltages (>690V)
2. Altitudes above 4000m



# Introduction



## Winding Configurations and Winding Numbers


**NOTICE**

Additional parts may be required to achieve reconnections

**CAUTION**

Misconnections can result in permanent machine damage. Refer to machine wiring diagram for specific details

Windings for STAMFORD alternators may be selected to give voltages at different connections as this table.



	WINDING NUMBER (3-PHASE)	EXIT LEADS	SERIES STAR (3-PHASE)	PARALLEL STAR (3-PHASE)	SERIES DELTA (3-PHASE)	STAR (3-PHASE)	DELTA (3-PHASE)	DOUBLE DELTA (1-PHASE)	PARALLEL DELTA (1-PHASE)	SERIES (1-PHASE)	PARALLEL (1-PHASE)
50Hz	5	4								220-240	110-120
	25	12	660-690	330-345	380-400						
	26	6				660-690	380-400				
	311	12	380-440	190-220	220-254			220-240	110-120		
	312	6				380-440	220-254				
	51	6				3300					
	61	6				6300-6600					
	71	6				6000					
	81	6				10000					
	83	6				10500 - 11000					
60Hz	6	4								220-240	110-120
	7	6				600	346				
	13	6				380-416	220-240				
	14	12	380-416	190-208	220-240						
	17	12	600	300	346						
	27	12	660-690	330-345	380-400						
	28	6				660-690	380-400				
	311	12	416-480	208-240	240-277			220-240	110-120		
	312	6				416-480	240-277				
	51	6				4160					
	71	6				7200					
	81	6				11400					
	87	6				12470					
	91	6				12470 - 13800					



## Introduction



## Useful Formulas

TO OBTAIN	Single Phase AC power	Three Phase AC power
kilowatts electrical (kW)	$\frac{\text{Volts} \times \text{Amps} \times \text{PF}}{1000}$	$\frac{\text{Volts} \times \text{Amps} \times \text{PF} \times \sqrt{3}}{1000}$
kilowatts electrical (kW)	$kVA \times \text{PF}$	$kVA \times \text{PF}$
kilowatts mechanical (kWm)	$\frac{kVA \times \text{PF}}{\text{Alternator Efficiency}}$	$\frac{kVA \times \text{PF}}{\text{Alternator Efficiency}}$
kVA	$\frac{\text{Volts} \times \text{Amps}}{1000}$	$\frac{\text{Volts} \times \text{Amps} \times \sqrt{3}}{1000}$
Amps	$\frac{kVA \times 1000}{\text{Volts}}$	$\frac{kVA \times 1000}{\text{Volts} \times \sqrt{3}}$
Speed (rpm)	$\frac{120 \times \text{Frequency}}{\# \text{ Poles}}$	$\frac{120 \times \text{Frequency}}{\# \text{ Poles}}$
% Voltage regulation (for Steady- Loads, from No- Load to Full-Load)	$\frac{V_{NL} - V_{FL}}{V_{FL}} \times 100$	$\frac{V_{NL} - V_{FL}}{V_{FL}} \times 100$
Horsepower required to drive alternator	$\frac{kW}{0.746 \times \text{Alternator Efficiency}}$	$\frac{kW}{0.746 \times \text{Alternator Efficiency}}$
First cycle RMS short circuit current ( $\pm 10\%$ )	$\frac{\text{Rated Amperes}}{puX''d}$	$\frac{\text{Rated Amperes}}{puX''d}$

- “PF” refers to power factor, which is expressed as a decimal fraction. For example, 80% power factor = 0.8 for the purposes of calculations.
- # Poles refers to number of Poles
- “Volts” refers to line-to-line voltage.
- “Amps” refers to line current in amperes.
- “pu” refers to per unit



# Table of Contents



## 2 POLE Single Phase

Page

### 50Hz 3000rpm

220V-240V Dedicated 0.8 pf	Page 9
220V-240V Dedicated 1.0 pf	Page 9
220V-240V Reconnectable 0.8 pf	Page 10
220V-240V Reconnectable 1.0 pf	Page 10

### 60Hz 3600rpm

220V-240V Dedicated 0.8 pf	Page 11
220V-240V Dedicated 1.0 pf	Page 11
220V Reconnectable 0.8 pf	Page 12
220V Reconnectable 1.0 pf	Page 12
230V Reconnectable 0.8 pf	Page 13
230V Reconnectable 1.0 pf	Page 13
240V Reconnectable 0.8 pf	Page 14
240V Reconnectable 1.0 pf	Page 14



## 2 POLE Three Phase

Pages

### 50Hz 3000rpm

380V-415V	Page 15
440V	Page 15

### 60Hz 3600rpm

380V	Page 16
416V	Page 16
440V- 480V	Page 17



## 4 POLE Single Phase

Pages

### 50Hz 1500rpm

220V Dedicated 0.8 pf	Page 18
220V Dedicated 1.0 pf	Page 19
230V Dedicated 0.8 pf	Page 20
230V Dedicated 1.0 pf	Page 21
240V Dedicated 0.8 pf	Page 22
240V Dedicated 1.0 pf	Page 23
220V-240V Reconnectable 0.8 pf	Page 24-29



# Table of Contents



## 4 POLE Single Phase (Continued)

### Pages

### 60Hz 1800rpm

220V Dedicated 0.8 pf	Page 30
220V Dedicated 1.0 pf	Page 31
230V Dedicated 0.8 pf	Page 32
230V Dedicated 1.0 pf	Page 33
240V Dedicated 0.8 pf	Page 34
240V Dedicated 1.0 pf	Page 35
220V Reconnectable 0.8 pf	Page 36-37
220V Reconnectable 1.0 pf	Page 38-39
230V Reconnectable 0.8 pf	Page 40-41
230V Reconnectable 1.0 pf	Page 42-43
240V Reconnectable 0.8 pf	Page 44-45
240V Reconnectable 1.0 pf	Page 46-47



## 4 POLE Three Phase

### 50Hz 1500rpm

380V	Page 48-50
400V	Page 51-53
415V	Page 54-56
440V	Page 57-59
660V-690V	Page 60-61

### 60Hz 1800rpm

380V	Page 62-67
416V	Page 68-70
440V	Page 71-73
460V	Page 74-76
480V	Page 77-79
600V	Page 80-82
660V-690V	Page 83



## 6 POLE Three Phase

### Pages

### 50Hz 1000rpm

380V-415V	Page 84
-----------	---------

### 60Hz 1200rpm

380V	Page 84
416V	Page 85
440V-480V	Page 85-86
600V	Page 86



# Table of Contents

## Medium Voltage

## Pages

### 50Hz 1500rpm

3300V

Page 87

### 60Hz 1800rpm

4160V

Page 87

## High Voltage

## Pages

### 50Hz 1500rpm

5500V

Page 88

6000V

Page 88

6300V

Page 89

6600V-6900V

Page 90

10000V

Page 91

10500V

Page 92

11000V

Page 92

### 60Hz 1800rpm

4160V

Page 93

6600V

Page 94

7200V

Page 94

11400V

Page 95

12470V

Page 95-96

13200V

Page 96-97

13800V

Page 98





# 2 POLE Single Phase

**Dedicated**

**Series** 220V - 240V **50Hz/3000rpm**  
**Parallel** 110V - 120V **0.8 Power Factor**

Winding 05	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	10.0	8.0	9.1	7.3	8.4	6.7	7.5	6.0	6.7	5.4
PI042E	12.0	9.6	10.9	8.7	10.1	8.1	9.0	7.2	8.1	6.5
PI042F	13.9	11.1	12.6	10.1	11.7	9.4	10.6	8.5	9.4	7.5
PI042G	15.9	12.7	14.5	11.6	13.4	10.7	12.0	9.6	10.7	8.6
PI142D	20.0	16.0	18.1	14.5	16.8	13.4	15.0	12.0	13.4	10.7
PI142E	21.9	17.5	19.9	15.9	18.4	14.7	16.6	13.3	14.7	11.8
PI142F	25.4	20.3	23.1	18.5	21.4	17.1	19.3	15.4	17.1	13.7
PI142G	29.8	23.8	27.1	21.7	25.1	20.1	22.5	18.0	20.1	16.1
PI142H	31.8	25.4	28.9	23.1	26.8	21.4	24.0	19.2	21.4	17.1
PI142J	35.9	28.7	32.6	26.1	30.2	24.2	27.2	21.8	24.2	19.4

**Dedicated**

**Series** 220V - 240V **50Hz/3000rpm**  
**Parallel** 110V - 120V **1.0 Power Factor**

Winding 05	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	10.0	10.0	9.1	9.1	8.4	8.4	7.5	7.5	6.7	6.7
PI042E	12.0	12.0	10.9	10.9	10.1	10.1	9.0	9.0	8.1	8.1
PI042F	13.9	13.9	12.6	12.6	11.7	11.7	10.6	10.6	9.4	9.4
PI042G	15.9	15.9	14.5	14.5	13.4	13.4	12.0	12.0	10.7	10.7
PI142D	20.0	20.0	18.1	18.1	16.8	16.8	15.0	15.0	13.4	13.4
PI142E	21.9	21.9	19.9	19.9	18.4	18.4	16.6	16.6	14.7	14.7
PI142F	25.4	25.4	23.1	23.1	21.4	21.4	19.3	19.3	17.1	17.1
PI142G	29.8	29.8	27.1	27.1	25.1	25.1	22.5	22.5	20.1	20.1
PI142H	31.8	31.8	28.9	28.9	26.8	26.8	24.0	24.0	21.4	21.4
PI142J	35.9	35.9	32.6	32.6	30.2	30.2	27.2	27.2	24.2	24.2



# 2 POLE Single Phase



**Reconnectable** Double Delta 220V - 240V **50Hz/3000rpm**  
**0.8 Power Factor**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	8.3	6.6	8.1	6.5	7.5	6.0	7.0	5.6	6.0	4.8
PI042E	9.9	7.9	9.7	7.8	9.0	7.2	8.3	6.6	7.2	5.8
PI042F	11.6	9.3	11.3	9.0	10.5	8.4	9.6	7.7	8.4	6.7
PI042G	13.2	10.6	13.0	10.4	12.0	9.6	10.8	8.6	9.6	7.7
PI142D	16.5	13.2	16.2	13.0	15.0	12.0	13.8	11.0	12.0	9.6
PI142E	18.2	14.6	17.8	14.2	16.5	13.2	15.0	12.0	13.2	10.6
PI142F	21.1	16.9	20.7	16.6	19.2	15.4	17.6	14.1	15.4	12.3
PI142G	24.8	19.8	24.3	19.4	22.5	18.0	20.7	16.6	18.0	14.4
PI142H	26.4	21.1	25.9	20.7	24.0	19.2	21.6	17.3	19.2	15.4
PI142J	29.7	23.8	29.2	23.4	27.0	21.6	24.3	19.4	21.6	17.3

**Reconnectable** Double Delta 220V - 240V **50Hz/3000rpm**  
**1.0 Power Factor**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	8.3	8.3	8.1	8.1	7.5	7.5	7.0	7.0	6.0	6.0
PI042E	9.9	9.9	9.7	9.7	9.0	9.0	8.3	8.3	7.2	7.2
PI042F	11.6	11.6	11.3	11.3	10.5	10.5	9.6	9.6	8.4	8.4
PI042G	13.2	13.2	13.0	13.0	12.0	12.0	10.8	10.8	9.6	9.6
PI142D	16.5	16.5	16.2	16.2	15.0	15.0	13.8	13.8	12.0	12.0
PI142E	18.2	18.2	17.8	17.8	16.5	16.5	15.0	15.0	13.2	13.2
PI142F	21.1	21.1	20.7	20.7	19.2	19.2	17.6	17.6	15.4	15.4
PI142G	24.8	24.8	24.3	24.3	22.5	22.5	20.7	20.7	18.0	18.0
PI142H	26.4	26.4	25.9	25.9	24.0	24.0	21.6	21.6	19.2	19.2
PI142J	29.7	29.7	29.2	29.2	27.0	27.0	24.3	24.3	21.6	21.6



# 2 POLE Single Phase

**Dedicated**

**Series** 220V - 240V **60Hz/3600rpm**  
**Parallel** 110V - 120V **0.8 Power Factor**

Winding 06	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	10.3	8.2	10.1	8.1	9.4	7.5	8.4	6.7	7.5	6.0
PI042E	12.4	9.9	12.2	9.8	11.3	9.0	10.2	8.2	9.0	7.2
PI042F	14.2	11.4	14.0	11.2	12.9	10.3	11.6	9.3	10.3	8.2
PI042G	16.5	13.2	16.2	13.0	15.0	12.0	13.5	10.8	12.0	9.6
PI142D	18.7	15.0	18.4	14.7	17.0	13.6	15.3	12.2	13.6	10.9
PI142E	23.2	18.6	22.8	18.2	21.1	16.9	19.0	15.2	16.9	13.5
PI142F	26.2	21.0	25.7	20.6	23.8	19.0	21.4	17.1	19.0	15.2
PI142G	29.9	23.9	29.4	23.5	27.2	21.8	24.5	19.6	21.8	17.4
PI142H	35.2	28.2	34.5	27.6	32.0	25.6	28.8	23.0	25.6	20.5
PI142J	37.4	29.9	36.7	29.4	34.0	27.2	30.6	24.5	27.2	21.8

**Dedicated**

**Series** 220V - 240V **60Hz/3600rpm**  
**Parallel** 110V - 120V **1.0 Power Factor**

Winding 06	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	10.3	10.3	10.1	10.1	9.4	9.4	8.4	8.4	7.5	7.5
PI042E	12.4	12.4	12.2	12.2	11.3	11.3	10.2	10.2	9.0	9.0
PI042F	14.2	14.2	14.0	14.0	12.9	12.9	11.6	11.6	10.3	10.3
PI042G	16.5	16.5	16.2	16.2	15.0	15.0	13.5	13.5	12.0	12.0
PI142D	18.7	18.7	18.4	18.4	17.0	17.0	15.3	15.3	13.6	13.6
PI142E	23.2	23.2	22.8	22.8	21.1	21.1	19.0	19.0	16.9	16.9
PI142F	26.2	26.2	25.7	25.7	23.8	23.8	21.4	21.4	19.0	19.0
PI142G	29.9	29.9	29.4	29.4	27.2	27.2	24.5	24.5	21.8	21.8
PI142H	35.2	35.2	34.5	34.5	32.0	32.0	28.8	28.8	25.6	25.6
PI142J	37.4	37.4	36.7	36.7	34.0	34.0	30.6	30.6	27.2	27.2



# 2 POLE Single Phase



**Reconnectable Double Delta 220V 60Hz/3600rpm  
0.8 Power Factor**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	8.2	6.6	8.0	6.4	7.5	6.0	6.7	5.4	6.0	4.8
PI042E	9.9	7.9	9.7	7.8	9.0	7.2	8.1	6.5	7.2	5.8
PI042F	11.3	9.0	11.1	8.9	10.3	8.2	9.2	7.4	8.2	6.6
PI042G	13.1	10.5	12.8	10.2	11.9	9.5	10.7	8.6	9.5	7.6
PI142D	14.9	11.9	14.6	11.7	13.5	10.8	12.2	9.8	10.8	8.6
PI142E	18.4	14.7	18.1	14.5	16.7	13.4	15.1	12.1	13.4	10.7
PI142F	20.8	16.6	20.4	16.3	18.9	15.1	17.0	13.6	15.1	12.1
PI142G	23.8	19.0	23.3	18.6	21.6	17.3	19.4	15.5	17.3	13.8
PI142H	27.9	22.3	27.4	21.9	25.4	20.3	22.8	18.2	20.3	16.2
PI142J	29.7	23.8	29.2	23.4	27.0	21.6	24.3	19.4	21.6	17.3

**Reconnectable Double Delta 220V 60Hz/3600rpm  
1.0 Power Factor**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	8.2	8.2	8.0	8.0	7.5	7.5	6.7	6.7	6.0	6.0
PI042E	9.9	9.9	9.7	9.7	9.0	9.0	8.1	8.1	7.2	7.2
PI042F	11.3	11.3	11.1	11.1	10.3	10.3	9.2	9.2	8.2	8.2
PI042G	13.1	13.1	12.8	12.8	11.9	11.9	10.7	10.7	9.5	9.5
PI142D	14.9	14.9	14.6	14.6	13.5	13.5	12.2	12.2	10.8	10.8
PI142E	18.4	18.4	18.1	18.1	16.7	16.7	15.1	15.1	13.4	13.4
PI142F	20.8	20.8	20.4	20.4	18.9	18.9	17.0	17.0	15.1	15.1
PI142G	23.8	23.8	23.3	23.3	21.6	21.6	19.4	19.4	17.3	17.3
PI142H	27.9	27.9	27.4	27.4	25.4	25.4	22.8	22.8	20.3	20.3
PI142J	29.7	29.7	29.2	29.2	27.0	27.0	24.3	24.3	21.6	21.6



# 2 POLE Single Phase



**Reconnectable** Double Delta 230V 60Hz/3600rpm  
0.8 Power Factor

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	8.7	7.0	8.5	6.8	7.9	6.3	7.1	5.7	6.3	5.0
PI042E	10.5	8.4	10.3	8.2	9.5	7.6	8.6	6.9	7.6	6.1
PI042F	12.0	9.6	11.7	9.4	10.9	8.7	9.8	7.8	8.7	7.0
PI042G	13.9	11.1	13.6	10.9	12.6	10.1	11.3	9.0	10.1	8.1
PI142D	15.7	12.6	15.5	12.4	14.3	11.4	12.9	10.3	11.4	9.1
PI142E	19.5	15.6	19.2	15.4	17.7	14.2	16.0	12.8	14.2	11.4
PI142F	22.0	17.6	21.6	17.3	20.0	16.0	18.0	14.4	16.0	12.8
PI142G	25.2	20.2	24.7	19.8	22.9	18.3	20.6	16.5	18.3	14.6
PI142H	29.6	23.7	29.1	23.3	26.9	21.5	24.2	19.4	21.5	17.2
PI142J	31.5	25.2	30.9	24.7	28.6	22.9	25.8	20.6	22.9	18.3

**Reconnectable** Double Delta 230V 60Hz/3600rpm  
1.0 Power Factor

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	8.7	8.7	8.5	8.5	7.9	7.9	7.1	7.1	6.3	6.3
PI042E	10.5	10.5	10.3	10.3	9.5	9.5	8.6	8.6	7.6	7.6
PI042F	12.0	12.0	11.7	11.7	10.9	10.9	9.8	9.8	8.7	8.7
PI042G	13.9	13.9	13.6	13.6	12.6	12.6	11.3	11.3	10.1	10.1
PI142D	15.7	15.7	15.5	15.5	14.3	14.3	12.9	12.9	11.4	11.4
PI142E	19.5	19.5	19.2	19.2	17.7	17.7	16.0	16.0	14.2	14.2
PI142F	22.0	22.0	21.6	21.6	20.0	20.0	18.0	18.0	16.0	16.0
PI142G	25.2	25.2	24.7	24.7	22.9	22.9	20.6	20.6	18.3	18.3
PI142H	29.6	29.6	29.1	29.1	26.9	26.9	24.2	24.2	21.5	21.5
PI142J	31.5	31.5	30.9	30.9	28.6	28.6	25.8	25.8	22.9	22.9



# 2 POLE Single Phase



**Reconnectable** Double Delta 240V 60Hz/3600rpm  
0.8 Power Factor

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	9.0	7.2	8.8	7.0	8.2	6.6	7.4	5.9	6.6	5.3
PI042E	10.8	8.6	10.6	8.5	9.9	7.9	8.9	7.1	7.9	6.3
PI042F	12.4	9.9	12.2	9.8	11.3	9.0	10.2	8.2	9.0	7.2
PI042G	14.4	11.5	14.1	11.3	13.1	10.5	11.8	9.4	10.5	8.4
PI142D	16.3	13.0	16.0	12.8	14.8	11.8	13.4	10.7	11.8	9.4
PI142E	20.2	16.2	19.9	15.9	18.4	14.7	16.6	13.3	14.7	11.8
PI142F	22.9	18.3	22.4	17.9	20.8	16.6	18.7	15.0	16.6	13.3
PI142G	26.1	20.9	25.6	20.5	23.7	19.0	21.4	17.1	19.0	15.2
PI142H	30.7	24.6	30.1	24.1	27.9	22.3	25.1	20.1	22.3	17.8
PI142J	32.6	26.1	32.1	25.7	29.7	23.8	26.7	21.4	23.8	19.0

**Reconnectable** Double Delta 240V 60Hz/3600rpm  
1.0 Power Factor

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	9.0	9.0	8.8	8.8	8.2	8.2	7.4	7.4	6.6	6.6
PI042E	10.8	10.8	10.6	10.6	9.9	9.9	8.9	8.9	7.9	7.9
PI042F	12.4	12.4	12.2	12.2	11.3	11.3	10.2	10.2	9.0	9.0
PI042G	14.4	14.4	14.1	14.1	13.1	13.1	11.8	11.8	10.5	10.5
PI142D	16.3	16.3	16.0	16.0	14.8	14.8	13.4	13.4	11.8	11.8
PI142E	20.2	20.2	19.9	19.9	18.4	18.4	16.6	16.6	14.7	14.7
PI142F	22.9	22.9	22.4	22.4	20.8	20.8	18.7	18.7	16.6	16.6
PI142G	26.1	26.1	25.6	25.6	23.7	23.7	21.4	21.4	19.0	19.0
PI142H	30.7	30.7	30.1	30.1	27.9	27.9	25.1	25.1	22.3	22.3
PI142J	32.6	32.6	32.1	32.1	29.7	29.7	26.7	26.7	23.8	23.8



# 2 POLE 3 Phase



**Star** 380V - 415V  
**Parallel Star** 190V - 208V  
**Delta** 220V - 240V

**50Hz/3000rpm**  
**0.8 Power Factor**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	13.8	11.0	13.5	10.8	12.5	10.0	11.5	9.2	10.0	8.0
PI042E	16.5	13.2	16.2	13.0	15.0	12.0	13.5	10.8	12.0	9.6
PI042F	19.3	15.4	18.9	15.1	17.5	14.0	16.0	12.8	14.0	11.2
PI042G	22.0	17.6	21.6	17.3	20.0	16.0	18.0	14.4	16.0	12.8
PI142D	27.5	22.0	27.0	21.6	25.0	20.0	22.5	18.0	20.0	16.0
PI142E	30.3	24.2	29.7	23.8	27.5	22.0	25.0	20.0	22.0	17.6
PI142F	35.2	28.2	34.6	27.7	32.0	25.6	29.3	23.4	25.6	20.5
PI142G	41.3	33.0	40.5	32.4	37.5	30.0	34.5	27.6	30.0	24.0
PI142H	44.0	35.2	43.2	34.6	40.0	32.0	36.0	28.8	32.0	25.6
PI142J	49.5	39.6	48.6	38.9	45.0	36.0	40.5	32.4	36.0	28.8

**Star** 440V  
**Parallel Star** 220V  
**Delta** 254V

**50Hz/3000rpm**  
**0.8 Power Factor**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	13.3	10.6	13.1	10.5	12.1	9.7	11.0	8.8	9.7	7.8
PI042E	16.1	12.9	15.8	12.6	14.6	11.7	13.3	10.6	11.7	9.4
PI042F	18.7	15.0	18.4	14.7	17.0	13.6	15.1	12.1	13.6	10.9
PI042G	21.3	17.0	21.0	16.8	19.4	15.5	17.5	14.0	15.5	12.4
PI142D	26.7	21.4	26.2	21.0	24.3	19.4	22.0	17.6	19.4	15.5
PI142E	29.4	23.5	28.8	23.0	26.7	21.4	24.0	19.2	21.4	17.1
PI142F	34.1	27.3	33.5	26.8	31.0	24.8	28.3	22.6	24.8	19.8
PI142G	40.0	32.0	39.3	31.4	36.4	29.1	33.0	26.4	29.1	23.3
PI142H	42.7	34.2	41.9	33.5	38.8	31.0	35.0	28.0	31.0	24.8
PI142J	48.1	38.5	47.2	37.8	43.7	35.0	39.3	31.4	35.0	28.0



# 2 POLE 3 Phase



Star 380V  
Parallel Star 190V  
Delta 220V

60Hz/3600rpm  
0.8 Power Factor

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	13.9	11.1	13.6	10.9	12.6	10.1	11.3	9.0	10.1	8.1
PI042E	16.7	13.4	16.4	13.1	15.2	12.2	13.6	10.9	12.2	9.8
PI042F	19.1	15.3	18.7	15.0	17.4	13.9	15.6	12.5	13.9	11.1
PI042G	22.1	17.7	21.7	17.4	20.1	16.1	18.1	14.5	16.1	12.9
PI142D	25.1	20.1	24.7	19.8	22.8	18.2	20.6	16.5	18.2	14.6
PI142E	31.1	24.9	30.6	24.5	28.3	22.6	25.5	20.4	22.6	18.1
PI142F	35.2	28.2	34.5	27.6	32.0	25.6	28.8	23.0	25.6	20.5
PI142G	40.2	32.2	39.5	31.6	36.5	29.2	32.9	26.3	29.2	23.4
PI142H	47.2	37.8	46.4	37.1	42.9	34.3	38.6	30.9	34.3	27.4
PI142J	50.2	40.2	49.3	39.4	45.7	36.6	41.1	32.9	36.6	29.3

Star 416V  
Parallel Star 208V  
Delta 240V

60Hz/3600rpm  
0.8 Power Factor

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	15.2	12.2	14.9	11.9	13.8	11.0	12.4	9.9	11.0	8.8
PI042E	18.3	14.6	17.9	14.3	16.6	13.3	14.9	11.9	13.3	10.6
PI042F	20.9	16.7	20.5	16.4	19.0	15.2	17.1	13.7	15.2	12.2
PI042G	24.2	19.4	23.8	19.0	22.0	17.6	19.8	15.8	17.6	14.1
PI142D	27.5	22.0	27.0	21.6	25.0	20.0	22.5	18.0	20.0	16.0
PI142E	34.1	27.3	33.5	26.8	31.0	24.8	27.9	22.3	24.8	19.8
PI142F	38.5	30.8	37.8	30.2	35.0	28.0	31.5	25.2	28.0	22.4
PI142G	44.0	35.2	43.2	34.6	40.0	32.0	36.0	28.8	32.0	25.6
PI142H	51.7	41.4	50.8	40.6	47.0	37.6	42.3	33.8	37.6	30.1
PI142J	55.0	44.0	54.0	43.2	50.0	40.0	45.0	36.0	40.0	32.0





# 2 POLE 3 Phase



**Star** 440V - 480V  
**Parallel Star** 220V - 240V  
**Delta** 254V - 277V

**60Hz/3600rpm**  
**0.8 Power Factor**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI042D	16.1	12.9	15.8	12.6	14.6	11.7	13.2	10.6	11.7	9.4
PI042E	19.4	15.5	19.0	15.2	17.6	14.1	15.8	12.6	14.1	11.3
PI042F	22.2	17.8	21.8	17.4	20.1	16.1	18.1	14.5	16.1	12.9
PI042G	25.7	20.6	25.2	20.2	23.3	18.6	21.0	16.8	18.6	14.9
PI142D	29.2	23.4	28.6	22.9	26.5	21.2	23.9	19.1	21.2	17.0
PI142E	36.1	28.9	35.5	28.4	32.9	26.3	29.6	23.7	26.3	21.0
PI142F	40.8	32.6	40.1	32.1	37.1	29.7	33.4	26.7	29.7	23.8
PI142G	46.6	37.3	45.8	36.6	42.4	33.9	38.2	30.6	33.9	27.1
PI142H	54.8	43.8	53.8	43.0	49.8	39.8	44.8	35.8	39.8	31.8
PI142J	58.3	46.6	57.2	45.8	53.0	42.4	47.7	38.2	42.4	33.9



# 4 POLE Single Phase



**Dedicated**    **Series** 220V    **50Hz/1500rpm**  
**Parallel** 110V    **0.8 Power Factor**

Winding 05	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	5.5	4.4	5.4	4.3	5.0	4.0	4.6	3.7	4.0	3.2
PI044E	7.4	5.9	7.2	5.8	6.7	5.4	6.1	4.9	5.4	4.3
PI044F	9.2	7.4	9.0	7.2	8.4	6.7	7.6	6.1	6.7	5.4
PI044G	11.1	8.9	10.9	8.7	10.1	8.1	9.2	7.4	8.0	6.4
PI044H	12.9	10.3	12.7	10.2	11.7	9.4	10.7	8.6	9.4	7.5
PI144D	15.0	12.0	14.6	11.7	13.6	10.9	12.4	9.9	10.9	8.7
PI144E	18.7	15.0	18.3	14.6	17.0	13.6	15.5	12.4	13.6	10.9
PI144F	20.6	16.5	20.2	16.2	18.7	15.0	17.0	13.6	15.0	12.0
PI144G	22.5	18.0	22.0	17.6	20.4	16.3	18.7	15.0	16.3	13.0
PI144H	26.2	21.0	25.5	20.4	23.8	19.0	21.8	17.4	19.1	15.3
PI144J	30.6	24.5	30.0	24.0	27.2	21.8	24.9	19.9	21.8	17.4
UCI224C	N/A	N/A	N/A	N/A	28.0	22.4	25.0	20.0	22.0	17.6
PI144K	31.9	25.5	30.6	24.5	28.5	22.8	25.0	20.0	22.4	17.9
UCI224D	N/A	N/A	N/A	N/A	35.0	28.0	31.5	25.2	27.5	22.0
UCI224E	N/A	N/A	N/A	N/A	40.0	32.0	36.0	28.8	31.6	25.3
UCI224F	N/A	N/A	N/A	N/A	50.0	40.0	45.0	36.0	40.0	32.0
UCI224G	N/A	N/A	N/A	N/A	60.0	48.0	54.0	43.2	47.5	38.0
UCI274C	N/A	N/A	N/A	N/A	66.0	52.8	60.0	48.0	52.5	42.0
UCI274D	N/A	N/A	N/A	N/A	74.0	59.2	66.3	53.0	58.0	46.4
UCI274E	N/A	N/A	N/A	N/A	94.0	75.2	84.0	67.2	75.0	60.0
UCI274F	N/A	N/A	N/A	N/A	110.0	88.0	100.0	80.0	87.5	70.0
UCI274G	N/A	N/A	N/A	N/A	120.0	96.0	108.0	86.4	95.0	76.0
UCI274H	N/A	N/A	N/A	N/A	140.0	112.0	125.0	100.0	110.0	88.0



# 4 POLE Single Phase


**Dedicated**
**Series** 220V 50Hz/1500rpm  
**Parallel** 110V 1.0 Power Factor

Winding 05	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	6.6	6.6	6.5	6.5	6.0	6.0	5.5	5.5	4.8	4.8
PI044E	8.9	8.9	8.6	8.6	8.0	8.0	7.3	7.3	6.5	6.5
PI044F	11.0	11.0	10.8	10.8	10.1	10.1	9.1	9.1	8.0	8.0
PI044G	13.3	13.3	13.1	13.1	12.1	12.1	11.0	11.0	9.6	9.6
PI044H	15.5	15.5	15.2	15.2	14.0	14.0	12.8	12.8	11.3	11.3
PI144D	16.2	16.2	15.8	15.8	14.7	14.7	13.4	13.4	11.8	11.8
PI144E	20.2	20.2	19.8	19.8	18.4	18.4	16.7	16.7	14.7	14.7
PI144F	22.2	22.2	21.8	21.8	20.2	20.2	18.4	18.4	16.2	16.2
PI144G	24.3	24.3	23.8	23.8	22.0	22.0	20.2	20.2	17.6	17.6
PI144H	28.3	28.3	27.5	27.5	25.7	25.7	23.5	23.5	20.6	20.6
UCI224C	N/A	N/A	N/A	N/A	28.0	28.0	25.0	25.0	22.0	22.0
PI144J	33.0	33.0	32.4	32.4	29.4	29.4	26.9	26.9	23.5	23.5
PI144K	34.5	34.5	33.0	33.0	30.8	30.8	27.0	27.0	24.2	24.2
UCI224D	N/A	N/A	N/A	N/A	35.0	35.0	31.5	31.5	27.5	27.5
UCI224E	N/A	N/A	N/A	N/A	40.0	40.0	36.0	36.0	31.6	31.6
UCI224F	N/A	N/A	N/A	N/A	50.0	50.0	45.0	45.0	40.0	40.0
UCI224G	N/A	N/A	N/A	N/A	60.0	60.0	54.0	54.0	47.5	47.5
UCI274C	N/A	N/A	N/A	N/A	66.0	66.0	60.0	60.0	N/A	N/A
UCI274D	N/A	N/A	N/A	N/A	74.0	74.0	66.3	66.3	N/A	N/A
UCI274E	N/A	N/A	N/A	N/A	94.0	94.0	84.0	84.0	N/A	N/A
UCI274F	N/A	N/A	N/A	N/A	110.0	110.0	100.0	100.0	N/A	N/A
UCI274G	N/A	N/A	N/A	N/A	120.0	120.0	108.0	108.0	N/A	N/A
UCI274H	N/A	N/A	N/A	N/A	140.0	140.0	125.0	125.0	N/A	N/A



# 4 POLE Single Phase


**Dedicated**
**Series** 230V  
**Parallel** 115V  
**50Hz/1500rpm**  
**0.8 Power Factor**

Winding 05	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	5.5	4.4	5.4	4.3	5.0	4.0	4.6	3.7	4.0	3.2
PI044E	7.4	5.9	7.2	5.8	6.7	5.4	6.1	4.9	5.4	4.3
S0L1-J 1	8.3	6.6	8.0	6.4	7.5	6.0	6.8	5.4	N/A	N/A
PI044F	9.2	7.4	9.0	7.2	8.4	6.7	7.6	6.1	6.7	5.4
S0L1-S 1	11.0	8.8	10.7	8.6	10.0	8.0	9.1	7.3	N/A	N/A
PI044G	11.1	8.9	10.9	8.7	10.1	8.1	9.2	7.4	8.0	6.4
PI044H	13.0	10.4	12.7	10.2	11.7	9.4	10.7	8.6	9.4	7.5
PI144D	15.0	12.0	14.6	11.7	13.6	10.9	12.4	9.9	10.9	8.7
S0L2-K 1, 2	16.5	13.2	16.0	12.8	15.0	12.0	13.7	11.0	N/A	N/A
PI144E	18.7	15.0	18.3	14.6	17.0	13.6	15.5	12.4	13.6	10.9
PI144F	20.6	16.5	20.2	16.2	18.7	15.0	17.0	13.6	15.0	12.0
S0L2-U 1, 2	22.0	17.6	21.3	17.0	20.0	16.0	18.2	14.6	N/A	N/A
PI144G	22.5	18.0	22.0	17.6	20.4	16.3	18.7	15.0	16.3	13.0
PI144H	26.2	21.0	25.5	20.4	23.8	19.0	21.8	17.4	19.1	15.3
S1L2-K 1, 2	27.5	22.0	26.7	21.4	25.0	20.0	22.8	18.2	N/A	N/A
PI144J	30.6	24.5	30.0	24.0	27.2	21.8	24.9	19.9	21.8	17.4
UCI224C	N/A	N/A	N/A	N/A	28.0	22.4	25.0	20.0	22.0	17.6
PI144K	31.9	25.5	30.6	24.5	28.5	22.8	25.0	20.0	22.4	17.9
S1L2-R 1, 2	33.0	26.4	32.0	25.6	30.0	24.0	27.3	21.8	N/A	N/A
UCI224D	N/A	N/A	N/A	N/A	35.0	28.0	31.5	25.2	27.5	22.0
UCI224E	N/A	N/A	N/A	N/A	40.0	32.0	36.0	28.8	31.6	25.3
UCI224F	N/A	N/A	N/A	N/A	50.0	40.0	45.0	36.0	40.0	32.0
UCI224G	N/A	N/A	N/A	N/A	60.0	48.0	54.0	43.2	47.5	38.0
UCI274C	N/A	N/A	N/A	N/A	66.0	52.8	60.0	48.0	52.5	42.0
UCI274D	N/A	N/A	N/A	N/A	74.0	59.2	66.3	53.0	58.0	46.4
UCI274E	N/A	N/A	N/A	N/A	94.0	75.2	84.0	67.2	75.0	60.0
UCI274F	N/A	N/A	N/A	N/A	110.0	88.0	100.0	80.0	87.5	70.0
UCI274G	N/A	N/A	N/A	N/A	120.0	96.0	108.0	86.4	95.0	76.0
UCI274H	N/A	N/A	N/A	N/A	140.0	112.0	125.0	100.0	110.0	88.0

1. Available with single bearing only

2. Auxiliary winding option available (winding 705)



# 4 POLE Single Phase


**Dedicated**
**Series** 230V 50Hz/1500rpm  
**Parallel** 115V 1.0 Power Factor

Winding 05	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	6.6	6.6	6.5	6.5	6.0	6.0	5.5	5.5	4.8	4.8
PI044E	8.9	8.9	8.6	8.6	8.0	8.0	7.3	7.3	6.5	6.5
S0L1-J 1	8.9	8.9	8.6	8.6	8.1	8.1	7.4	7.4	N/A	N/A
PI044F	11.0	11.0	10.8	10.8	10.1	10.1	9.1	9.1	8.0	8.0
S0L1-S 1	11.9	11.9	11.6	11.6	10.8	10.8	9.8	9.8	N/A	N/A
PI044G	13.3	13.3	13.1	13.1	12.1	12.1	11.0	11.0	9.6	9.6
PI044H	15.5	15.5	15.2	15.2	14.0	14.0	12.8	12.8	11.3	11.3
PI144D	16.2	16.2	15.8	15.8	14.7	14.7	13.4	13.4	11.8	11.8
S0L2-K 1, 2	17.8	17.8	17.3	17.3	16.2	16.2	14.7	14.7	N/A	N/A
PI144E	20.2	20.2	19.8	19.8	18.4	18.4	16.7	16.7	14.7	14.7
PI144F	22.2	22.2	21.8	21.8	20.2	20.2	18.4	18.4	16.2	16.2
S0L2-U 1, 2	23.8	23.8	23.0	23.0	21.6	21.6	19.7	19.7	N/A	N/A
PI144G	24.3	24.3	23.8	23.8	22.0	22.0	20.2	20.2	17.6	17.6
PI144H	28.3	28.3	27.5	27.5	25.7	25.7	23.5	23.5	20.6	20.6
S1L2-K 1, 2	29.7	29.7	28.8	28.8	27.0	27.0	24.6	24.6	N/A	N/A
UCI224C	N/A	N/A	N/A	N/A	28.0	28.0	25.0	25.0	22.0	22.0
PI144J	33.0	33.0	32.4	32.4	29.4	29.4	26.9	26.9	23.5	23.5
PI144K	34.5	34.5	33.0	33.0	30.8	30.8	27.0	27.0	24.2	24.2
S1L2-R 1, 2	35.6	35.6	34.6	34.6	32.4	32.4	29.5	29.5	N/A	N/A
UCI224D	N/A	N/A	N/A	N/A	35.0	35.0	31.5	31.5	27.5	27.5
UCI224E	N/A	N/A	N/A	N/A	40.0	40.0	36.0	36.0	31.6	31.6
UCI224F	N/A	N/A	N/A	N/A	50.0	50.0	45.0	45.0	40.0	40.0
UCI224G	N/A	N/A	N/A	N/A	60.0	60.0	54.0	54.0	47.5	47.5
UCI274C	N/A	N/A	N/A	N/A	66.0	66.0	60.0	60.0	N/A	N/A
UCI274D	N/A	N/A	N/A	N/A	74.0	74.0	66.3	66.3	N/A	N/A
UCI274E	N/A	N/A	N/A	N/A	94.0	94.0	84.0	84.0	N/A	N/A
UCI274F	N/A	N/A	N/A	N/A	110.0	110.0	100.0	100.0	N/A	N/A
UCI274G	N/A	N/A	N/A	N/A	120.0	120.0	108.0	108.0	N/A	N/A
UCI274H	N/A	N/A	N/A	N/A	140.0	140.0	125.0	125.0	N/A	N/A

1. Available with single bearing only

2. Auxiliary winding option available (winding 705)



# 4 POLE Single Phase


**Dedicated**
**Series** 240V **50Hz/1500rpm**  
**Parallel** 120V **0.8 Power Factor**

Winding 05	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	5.5	4.4	5.4	4.3	5.0	4.0	4.6	3.7	4.0	3.2
PI044E	7.4	5.9	7.2	5.8	6.7	5.4	6.1	4.9	5.4	4.3
PI044F	9.2	7.4	9.0	7.2	8.4	6.7	7.6	6.1	6.7	5.4
PI044G	11.1	8.9	10.9	8.7	10.1	8.1	9.2	7.4	8.0	6.4
PI044H	12.9	10.3	12.7	10.2	11.7	9.4	10.7	8.6	9.4	7.5
PI144D	15.0	12.0	14.6	11.7	13.6	10.9	12.4	9.9	10.9	8.7
PI144E	18.7	15.0	18.3	14.6	17.0	13.6	15.5	12.4	13.6	10.9
PI144F	20.6	16.5	20.2	16.2	18.7	15.0	17.0	13.6	15.0	12.0
PI144G	22.5	18.0	22.0	17.6	20.4	16.3	18.7	15.0	16.3	13.0
PI144H	26.2	21.0	25.5	20.4	23.8	19.0	21.8	17.4	19.1	15.3
PI144J	30.6	24.5	30.0	24.0	27.2	21.8	24.9	19.9	21.8	17.4
UCI224C	N/A	N/A	N/A	N/A	28.0	22.4	25.0	20.0	22.0	17.6
PI144K	31.9	25.5	30.6	24.5	28.5	22.8	25.0	20.0	22.4	17.9
UCI224D	N/A	N/A	N/A	N/A	35.0	28.0	31.5	25.2	27.5	22.0
UCI224E	N/A	N/A	N/A	N/A	40.0	32.0	36.0	28.8	31.6	25.3
UCI224F	N/A	N/A	N/A	N/A	50.0	40.0	45.0	36.0	40.0	32.0
UCI224G	N/A	N/A	N/A	N/A	60.0	48.0	54.0	43.2	47.5	38.0
UCI274C	N/A	N/A	N/A	N/A	66.0	52.8	60.0	48.0	52.5	42.0
UCI274D	N/A	N/A	N/A	N/A	74.0	59.2	66.3	53.0	58.0	46.4
UCI274E	N/A	N/A	N/A	N/A	94.0	75.2	84.0	67.2	75.0	60.0
UCI274F	N/A	N/A	N/A	N/A	110.0	88.0	100.0	80.0	87.5	70.0
UCI274G	N/A	N/A	N/A	N/A	120.0	96.0	108.0	86.4	95.0	76.0
UCI274H	N/A	N/A	N/A	N/A	140.0	112.0	125.0	100.0	110.0	88.0



# 4 POLE Single Phase


**Dedicated**
**Series** 240V 50Hz/1500rpm  
**Parallel** 120V 1.0 Power Factor

Winding 05	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	6.6	6.6	6.5	6.5	6.0	6.0	5.5	5.5	4.8	4.8
PI044E	8.9	8.9	8.6	8.6	8.0	8.0	7.3	7.3	6.5	6.5
PI044F	11.0	11.0	10.8	10.8	10.1	10.1	9.1	9.1	8.0	8.0
PI044G	13.3	13.3	13.1	13.1	12.1	12.1	11.0	11.0	9.6	9.6
PI044H	15.5	15.5	15.2	15.2	14.0	14.0	12.8	12.8	11.3	11.3
PI144D	16.2	16.2	15.8	15.8	14.7	14.7	13.4	13.4	11.8	11.8
PI144E	20.2	20.2	19.8	19.8	18.4	18.4	16.7	16.7	14.7	14.7
PI144F	22.2	22.2	21.8	21.8	20.2	20.2	18.4	18.4	16.2	16.2
PI144G	24.3	24.3	23.8	23.8	22.0	22.0	20.2	20.2	17.6	17.6
PI144H	28.3	28.3	27.5	27.5	25.7	25.7	23.5	23.5	20.6	20.6
UCI224C	N/A	N/A	N/A	N/A	28.0	28.0	25.0	25.0	22.0	22.0
PI144J	33.0	33.0	32.4	32.4	29.4	29.4	26.9	26.9	23.5	23.5
PI144K	34.5	34.5	33.0	33.0	30.8	30.8	27.0	27.0	24.2	24.2
UCI224D	N/A	N/A	N/A	N/A	35.0	35.0	31.5	31.5	27.5	27.5
UCI224E	N/A	N/A	N/A	N/A	40.0	40.0	36.0	36.0	31.6	31.6
UCI224F	N/A	N/A	N/A	N/A	50.0	50.0	45.0	45.0	40.0	40.0
UCI224G	N/A	N/A	N/A	N/A	60.0	60.0	54.0	54.0	47.5	47.5
UCI274C	N/A	N/A	N/A	N/A	66.0	66.0	60.0	60.0	N/A	N/A
UCI274D	N/A	N/A	N/A	N/A	74.0	74.0	66.3	66.3	N/A	N/A
UCI274E	N/A	N/A	N/A	N/A	94.0	94.0	84.0	84.0	N/A	N/A
UCI274F	N/A	N/A	N/A	N/A	110.0	110.0	100.0	100.0	N/A	N/A
UCI274G	N/A	N/A	N/A	N/A	120.0	120.0	108.0	108.0	N/A	N/A
UCI274H	N/A	N/A	N/A	N/A	140.0	140.0	125.0	125.0	N/A	N/A



# 4 POLE Single Phase


**Reconnectable Double Delta 220V**
**50Hz/1500rpm  
0.8 Power Factor**
**1 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S0L1-D 1	4.9	3.9	4.8	3.8	4.5	3.6	4.1	3.3	N/A	N/A
PI044D	5.0	4.0	4.9	3.9	4.5	3.6	4.1	3.3	3.6	2.9
PI044E	6.6	5.3	6.5	5.2	6.0	4.8	5.5	4.4	4.8	3.8
S0L1-H 1	6.6	5.3	6.5	5.2	6.0	4.8	5.4	4.3	N/A	N/A
S0L1-L 1	8.2	6.6	8.0	6.4	7.4	5.9	6.7	5.4	N/A	N/A
PI044F	8.3	6.6	8.1	6.5	7.5	6.0	6.8	5.4	6.0	4.8
S0L1-P 1	9.8	7.8	9.6	7.7	8.9	7.1	8.1	6.5	N/A	N/A
PI044G	9.9	7.9	9.7	7.8	9.0	7.2	8.2	6.6	7.2	5.8
S0L2-F 1, 2	11.1	8.9	10.9	8.7	10.1	8.1	9.2	7.4	N/A	N/A
PI044H	11.6	9.3	11.3	9.0	10.5	8.4	9.6	7.7	8.4	6.7
S0L2-G 1, 2	12.7	10.2	12.5	10.0	11.5	9.2	10.5	8.4	N/A	N/A
PI144D	13.2	10.6	12.9	10.3	12.0	9.6	10.9	8.7	9.6	7.7
S0L2-M 1, 2	15.9	12.7	15.6	12.5	14.4	11.5	13.1	10.5	N/A	N/A
PI144E	16.5	13.2	16.1	12.9	15.0	12.0	13.7	11.0	12.0	9.6
PI144F	18.2	14.6	17.8	14.2	16.5	13.2	15.0	12.0	13.2	10.6
S0L2-P 1, 2	19.1	15.3	18.7	15.0	17.3	13.8	15.8	12.6	N/A	N/A
PI144G	19.8	15.8	19.4	15.5	18.0	14.4	16.5	13.2	14.4	11.5
S1L2-J 1, 2	21.5	17.2	21.1	16.9	19.5	15.6	17.8	14.2	N/A	N/A
PI144H	23.1	18.5	22.5	18.0	21.0	16.8	19.2	15.4	16.8	13.4
S1L2-K 1, 2	24.6	19.7	24.1	19.3	22.3	17.8	20.3	16.2	N/A	N/A
PI144J	27.0	21.6	26.4	21.1	24.0	19.2	21.9	17.5	19.2	15.4
S1L2-N 1, 2	27.6	22.1	27.1	21.7	25.1	20.1	22.9	18.3	N/A	N/A
PI144K	28.1	22.5	27.0	21.6	25.5	20.4	23.0	18.4	19.7	15.8
S1L2-R 1, 2	30.7	24.6	30.2	24.2	27.9	22.3	25.4	20.3	N/A	N/A
UCI224C	N/A	N/A	N/A	N/A	28.5	22.8	25.0	20.0	22.0	17.6
UCI224D	N/A	N/A	N/A	N/A	33.5	26.8	30.0	24.0	26.5	21.2
S1L2-Y 1, 2	38.4	30.7	37.7	30.2	34.9	27.9	31.8	25.4	N/A	N/A
UCI224E	N/A	N/A	N/A	N/A	40.0	32.0	35.5	28.4	31.5	25.2
UCI224F	N/A	N/A	N/A	N/A	48.5	38.8	43.5	34.8	37.5	30.0
UCI224G	N/A	N/A	N/A	N/A	56.5	45.2	50.0	40.0	45.5	36.4
UCI274C	N/A	N/A	N/A	N/A	60.0	48.0	50.0	40.0	45.0	36.0

1. Available with single bearing only

2. Auxiliary winding option available (winding 711)





# 4 POLE Single Phase


**Reconnectable Double Delta 220V**
**50Hz/1500rpm  
0.8 Power Factor**
**2 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274D	N/A	N/A	N/A	N/A	68.0	54.4	60.0	48.0	54.0	43.2
UCI274E	N/A	N/A	N/A	N/A	85.0	68.0	75.0	60.0	67.5	54.0
UCI274F	N/A	N/A	N/A	N/A	96.0	76.8	87.0	69.6	75.0	60.0
UCI274G	N/A	N/A	N/A	N/A	108.0	86.4	98.7	79.0	85.4	68.3
UCI274H	N/A	N/A	N/A	N/A	125.0	100.0	110.0	88.0	93.8	75.0
S4L1S-C	N/A	N/A	N/A	N/A	125.0	100.0	115.0	92.0	100.0	80.0
HCI444C	N/A	N/A	N/A	N/A	125.0	100.0	115.0	92.0	100.0	80.0
UCDI274J	N/A	N/A	N/A	N/A	138.0	110.4	126.0	100.8	108.0	86.4
UCDI274K	N/A	N/A	N/A	N/A	150.0	120.0	137.0	109.6	120.0	96.0
HCI444D	N/A	N/A	N/A	N/A	150.0	120.0	140.0	112.0	120.0	96.0
S4L1S-D	N/A	N/A	N/A	N/A	150.0	120.0	140.0	112.0	120.0	96.0
S4L1S-E	N/A	N/A	N/A	N/A	175.0	140.0	160.0	128.0	140.0	112.0
HCI444E	N/A	N/A	N/A	N/A	175.0	140.0	160.0	128.0	140.0	112.0
HCI544C	N/A	N/A	N/A	N/A	180.0	144.0	160.0	128.0	140.0	112.0
HCI544D	N/A	N/A	N/A	N/A	200.0	160.0	180.0	144.0	155.0	124.0
S4L1S-F	N/A	N/A	N/A	N/A	200.0	160.0	185.0	148.0	160.0	128.0
HCI444F	N/A	N/A	N/A	N/A	200.0	160.0	185.0	148.0	160.0	128.0
HCI544E	N/A	N/A	N/A	N/A	240.0	192.0	220.0	176.0	190.0	152.0
HCI544F	N/A	N/A	N/A	N/A	265.0	212.0	245.0	196.0	215.0	172.0



# 4 POLE Single Phase


**Reconnectable Double Delta 230V**
**50Hz/1500rpm  
0.8 Power Factor**
**1 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S0L1-D 1	4.8	3.8	4.7	3.8	4.4	3.5	4.0	3.2	N/A	N/A
PI044D	5.0	4.0	4.9	3.9	4.5	3.6	4.1	3.3	3.6	2.9
S0L1-H 1	6.4	5.1	6.3	5.0	5.8	4.6	5.3	4.2	N/A	N/A
PI044E	6.6	5.3	6.5	5.2	6.0	4.8	5.5	4.4	4.8	3.8
S0L1-L 1	8.0	6.4	7.8	6.2	7.3	5.8	6.6	5.3	N/A	N/A
PI044F	8.3	6.6	8.1	6.5	7.5	6.0	6.8	5.4	6.0	4.8
S0L1-P 1	9.6	7.7	9.4	7.5	8.7	7.0	7.9	6.3	N/A	N/A
PI044G	9.9	7.9	9.7	7.8	9.0	7.2	8.2	6.6	7.2	5.8
S0L2-F 1, 2	11.0	8.8	10.8	8.6	10.0	8.0	9.1	7.3	N/A	N/A
PI044H	11.6	9.3	11.3	9.0	10.5	8.4	9.6	7.7	8.4	6.7
S0L2-G 1, 2	12.5	10.0	12.3	9.8	11.4	9.1	10.4	8.3	N/A	N/A
PI144D	13.2	10.6	12.9	10.3	12.0	9.6	10.9	8.7	9.6	7.7
S0L2-M 1, 2	15.7	12.6	15.4	12.3	14.3	11.4	13.0	10.4	N/A	N/A
PI144E	16.5	13.2	16.1	12.9	15.0	12.0	13.7	11.0	12.0	9.6
PI144F	18.2	14.6	17.8	14.2	16.5	13.2	15.0	12.0	13.2	10.6
S0L2-P 1, 2	18.8	15.0	18.5	14.8	17.1	13.7	15.6	12.5	N/A	N/A
PI144G	19.8	15.8	19.4	15.5	18.0	14.4	16.5	13.2	14.4	11.5
S1L2-J 1, 2	21.6	17.3	21.2	17.0	19.6	15.7	17.8	14.2	N/A	N/A
PI144H	23.1	18.5	22.5	18.0	21.0	16.8	19.2	15.4	16.8	13.4
S1L2-K 1, 2	24.6	19.7	24.2	19.4	22.4	17.9	20.4	16.3	N/A	N/A
PI144J	27.0	21.6	26.4	21.1	24.0	19.2	21.9	17.5	19.2	15.4
S1L2-N 1, 2	27.7	22.2	27.2	21.8	25.2	20.2	22.9	18.3	N/A	N/A
PI144K	28.1	22.5	27.0	21.6	25.5	20.4	23.0	18.4	19.7	15.8
S1L2-R 1, 2	30.8	24.6	30.2	24.2	28.0	22.4	25.5	20.4	N/A	N/A
UCI224C	N/A	N/A	N/A	N/A	28.5	22.8	25.0	20.0	22.0	17.6
UCI224D	N/A	N/A	N/A	N/A	33.5	26.8	30.0	24.0	26.5	21.2
S1L2-Y 1, 2	38.5	30.8	37.8	30.2	35.0	28.0	31.9	25.5	N/A	N/A
UCI224E	N/A	N/A	N/A	N/A	40.0	32.0	35.5	28.4	31.5	25.2
UCI224F	N/A	N/A	N/A	N/A	48.5	38.8	43.5	34.8	37.5	30.0
UCI224G	N/A	N/A	N/A	N/A	56.5	45.2	50.0	40.0	45.5	36.4
UCI274C	N/A	N/A	N/A	N/A	60.0	48.0	50.0	40.0	45.0	36.0

1. Available with single bearing only

2. Auxiliary winding option available (winding 711)



# 4 POLE Single Phase


**Reconnectable Double Delta 230V**
**50Hz/1500rpm  
0.8 Power Factor**
**2 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274D	N/A	N/A	N/A	N/A	68.0	54.4	60.0	48.0	54.0	43.2
UCI274E	N/A	N/A	N/A	N/A	85.0	68.0	75.0	60.0	67.5	54.0
UCI274F	N/A	N/A	N/A	N/A	100.0	80.0	87.0	69.6	75.0	60.0
UCI274G	N/A	N/A	N/A	N/A	108.0	86.4	98.7	79.0	85.4	68.3
UCI274H	N/A	N/A	N/A	N/A	125.0	100.0	115.0	92.0	100.0	80.0
S4L1S-C	N/A	N/A	N/A	N/A	125.0	100.0	115.0	92.0	100.0	80.0
HCI444C	N/A	N/A	N/A	N/A	125.0	100.0	110.0	88.0	93.8	75.0
UCDI274J	N/A	N/A	N/A	N/A	138.0	110.4	126.0	100.8	108.0	86.4
UCDI274K	N/A	N/A	N/A	N/A	150.0	120.0	137.0	109.6	120.0	96.0
HCI444D	N/A	N/A	N/A	N/A	150.0	120.0	140.0	112.0	120.0	96.0
S4L1S-D	N/A	N/A	N/A	N/A	150.0	120.0	140.0	112.0	120.0	96.0
S4L1S-E	N/A	N/A	N/A	N/A	175.0	140.0	160.0	128.0	140.0	112.0
HCI444E	N/A	N/A	N/A	N/A	175.0	140.0	160.0	128.0	140.0	112.0
HCI544C	N/A	N/A	N/A	N/A	180.0	144.0	160.0	128.0	140.0	112.0
HCI544D	N/A	N/A	N/A	N/A	200.0	160.0	180.0	144.0	155.0	124.0
S4L1S-F	N/A	N/A	N/A	N/A	200.0	160.0	185.0	148.0	160.0	128.0
HCI444F	N/A	N/A	N/A	N/A	200.0	160.0	185.0	148.0	160.0	128.0
HCI544E	N/A	N/A	N/A	N/A	240.0	192.0	220.0	176.0	190.0	152.0
HCI544F	N/A	N/A	N/A	N/A	265.0	212.0	245.0	196.0	215.0	172.0



# 4 POLE Single Phase


**Reconnectable Double Delta 240V**
**50Hz/1500rpm  
0.8 Power Factor**
**1 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S0L1-D 1	4.7	3.8	4.6	3.7	4.3	3.4	3.9	3.1	N/A	N/A
PI044D	5.0	4.0	4.9	3.9	4.5	3.6	4.1	3.3	3.6	2.9
S0L1-H 1	6.3	5.0	6.2	5.0	5.7	4.6	5.2	4.2	N/A	N/A
PI044E	6.6	5.3	6.5	5.2	6.0	4.8	5.5	4.4	4.8	3.8
S0L1-L 1	7.8	6.2	7.7	6.2	7.1	5.7	6.5	5.2	N/A	N/A
PI044F	8.3	6.6	8.1	6.5	7.5	6.0	6.8	5.4	6.0	4.8
S0L1-P 1	9.4	7.5	9.2	7.4	8.6	6.9	7.8	6.2	N/A	N/A
PI044G	9.9	7.9	9.7	7.8	9.0	7.2	8.2	6.6	7.2	5.8
S0L2-F 1, 2	10.8	8.6	10.6	8.5	9.8	7.8	8.9	7.1	N/A	N/A
PI044H	11.6	9.3	11.3	9.0	10.5	8.4	9.6	7.7	8.4	6.7
S0L2-G 1, 2	12.3	9.8	12.1	9.7	11.2	9.0	10.2	8.2	N/A	N/A
PI144D	13.2	10.6	12.9	10.3	12.0	9.6	10.9	8.7	9.6	7.7
S0L2-M 1, 2	15.4	12.3	15.1	12.1	14.0	11.2	12.7	10.2	N/A	N/A
PI144E	16.5	13.2	16.1	12.9	15.0	12.0	13.7	11.0	12.0	9.6
PI144F	18.2	14.6	17.8	14.2	16.5	13.2	15.0	12.0	13.2	10.6
PI144G	19.8	15.8	19.4	15.5	18.0	14.4	16.5	13.2	14.4	11.5
S1L2-J 1, 2	21.6	17.3	21.2	17.0	19.6	15.7	17.8	14.2	N/A	N/A
PI144H	23.1	18.5	22.5	18.0	21.0	16.8	19.2	15.4	16.8	13.4
S1L2-K 1, 2	24.6	19.7	24.2	19.4	22.4	17.9	20.4	16.3	N/A	N/A
PI144J	27.0	21.6	26.4	21.1	24.0	19.2	21.9	17.5	19.2	15.4
S1L2-N 1, 2	27.7	22.2	27.2	21.8	25.2	20.2	22.9	18.3	N/A	N/A
PI144K	28.1	22.5	27.0	21.6	25.5	20.4	23.0	18.4	19.7	15.8
S1L2-R 1, 2	30.8	24.6	30.2	24.2	28.0	22.4	25.5	20.4	N/A	N/A
UCI224C	N/A	N/A	N/A	N/A	28.5	22.8	25.0	20.0	22.0	17.6
S0L2-P 1, 2	18.5	14.8	18.1	14.5	30.0	24.0	N/A	N/A	N/A	N/A
UCI224D	N/A	N/A	N/A	N/A	33.5	26.8	30.0	24.0	26.5	21.2
S1L2-Y 1, 2	38.5	30.8	37.8	30.2	35.0	28.0	31.9	25.5	N/A	N/A
UCI224E	N/A	N/A	N/A	N/A	40.0	32.0	35.5	28.4	31.5	25.2
UCI224F	N/A	N/A	N/A	N/A	48.5	38.8	43.5	34.8	37.5	30.0
UCI224G	N/A	N/A	N/A	N/A	56.5	45.2	50.0	40.0	45.5	36.4
UCI274C	N/A	N/A	N/A	N/A	60.0	48.0	50.0	40.0	45.0	36.0

1. Available with single bearing only

2. Auxiliary winding option available (winding 711)



# 4 POLE Single Phase


**Reconnectable Double Delta 240V**
**50Hz/1500rpm  
0.8 Power Factor**
**2 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274D	N/A	N/A	N/A	N/A	68.0	54.4	60.0	48.0	54.0	43.2
UCI274E	N/A	N/A	N/A	N/A	85.0	68.0	75.0	60.0	67.5	54.0
UCI274F	N/A	N/A	N/A	N/A	100.0	80.0	87.0	69.6	75.0	60.0
UCI274G	N/A	N/A	N/A	N/A	108.0	86.4	98.7	79.0	85.4	68.3
UCI274H	N/A	N/A	N/A	N/A	125.0	100.0	110.0	88.0	93.8	75.0
HCI444C	N/A	N/A	N/A	N/A	125.0	100.0	115.0	92.0	100.0	80.0
S4L1S-C	N/A	N/A	N/A	N/A	125.0	100.0	115.0	92.0	100.0	80.0
UCDI274J	N/A	N/A	N/A	N/A	138.0	110.4	126.0	100.8	108.0	86.4
UCDI274K	N/A	N/A	N/A	N/A	150.0	120.0	137.0	109.6	120.0	96.0
HCI444D	N/A	N/A	N/A	N/A	150.0	120.0	140.0	112.0	120.0	96.0
S4L1S-D	N/A	N/A	N/A	N/A	150.0	120.0	140.0	112.0	120.0	96.0
HCI444E	N/A	N/A	N/A	N/A	175.0	140.0	160.0	128.0	140.0	112.0
S4L1S-E	N/A	N/A	N/A	N/A	175.0	140.0	160.0	128.0	140.0	112.0
HCI544C	N/A	N/A	N/A	N/A	180.0	144.0	160.0	128.0	140.0	112.0
HCI544D	N/A	N/A	N/A	N/A	200.0	160.0	180.0	144.0	155.0	124.0
S4L1S-F	N/A	N/A	N/A	N/A	200.0	160.0	185.0	148.0	160.0	128.0
HCI444F	N/A	N/A	N/A	N/A	200.0	160.0	185.0	148.0	160.0	128.0
HCI544E	N/A	N/A	N/A	N/A	240.0	192.0	220.0	176.0	190.0	152.0
HCI544F	N/A	N/A	N/A	N/A	265.0	212.0	245.0	196.0	215.0	172.0



# 4 POLE Single Phase


**Dedicated**
**Series** 220V  
**Parallel** 110V  
**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 06	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	6.4	5.1	6.2	5.0	5.8	4.6	5.2	4.2	4.6	3.7
PI044E	8.5	6.8	8.3	6.6	7.7	6.2	7.0	5.6	6.2	5.0
PI044F	10.6	8.5	10.4	8.3	9.6	7.7	8.8	7.0	7.7	6.2
PI044G	12.7	10.2	12.5	10.0	11.6	9.3	10.6	8.5	9.2	7.4
PI044H	14.8	11.8	14.6	11.7	13.5	10.8	12.3	9.8	10.8	8.6
PI144D	17.2	13.8	16.8	13.4	15.7	12.6	14.3	11.4	12.5	10.0
PI144E	21.5	17.2	21.1	16.9	19.6	15.7	17.8	14.2	15.7	12.6
PI144F	23.7	19.0	23.2	18.6	21.5	17.2	19.6	15.7	17.2	13.8
PI144G	25.8	20.6	25.3	20.2	23.5	18.8	21.5	17.2	18.8	15.0
PI144H	30.2	24.2	29.4	23.5	27.4	21.9	25.1	20.1	21.9	17.5
PI144J	35.2	28.2	34.5	27.6	31.3	25.0	28.6	22.9	25.1	20.1
PI144K	36.7	29.4	35.2	28.2	33.0	26.4	31.0	24.8	25.7	20.6
UCI224C	N/A	N/A	N/A	N/A	37.5	30.0	33.8	27.0	29.5	23.6
UCI224D	N/A	N/A	N/A	N/A	44.0	35.2	40.0	32.0	35.2	28.2
UCI224E	N/A	N/A	N/A	N/A	50.0	40.0	47.3	37.8	39.5	31.6
UCI224F	N/A	N/A	N/A	N/A	60.0	48.0	56.9	45.5	47.5	38.0
UCI224G	N/A	N/A	N/A	N/A	70.0	56.0	65.6	52.5	55.0	44.0
UCI274C	N/A	N/A	N/A	N/A	84.0	67.2	75.0	60.0	63.8	51.0
UCI274D	N/A	N/A	N/A	N/A	96.0	76.8	87.5	70.0	71.3	57.0
UCI274E	N/A	N/A	N/A	N/A	112.0	89.6	100.0	80.0	82.5	66.0
UCI274F	N/A	N/A	N/A	N/A	135.0	108.0	125.0	100.0	100.0	80.0
UCI274G	N/A	N/A	N/A	N/A	150.0	120.0	137.5	110.0	118.8	95.0
UCI274H	N/A	N/A	N/A	N/A	156.3	125.0	143.8	115.0	125.0	100.0
HCI444E	N/A	N/A	N/A	N/A	200.0	160.0	183.0	146.4	160.0	128.0
S4L1S-E	N/A	N/A	N/A	N/A	200.0	160.0	183.0	146.4	160.0	128.0
S4L1S-F	N/A	N/A	N/A	N/A	250.0	200.0	N/A	N/A	N/A	N/A



# 4 POLE Single Phase


**Dedicated**
**Series** 220V  
**Parallel** 110V  
**60Hz/1800rpm**  
**1.0 Power Factor**

Winding 06	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	8.3	8.3	8.1	8.1	7.5	7.5	6.8	6.8	6.0	6.0
PI044E	11.0	11.0	10.8	10.8	10.0	10.0	9.1	9.1	8.0	8.0
PI044F	13.8	13.8	13.5	13.5	12.5	12.5	11.3	11.3	10.0	10.0
PI044G	16.5	16.5	16.2	16.2	15.0	15.0	13.6	13.6	12.0	12.0
PI044H	19.3	19.3	18.9	18.9	17.5	17.5	15.9	15.9	14.0	14.0
PI144D	23.1	23.1	22.6	22.6	21.0	21.0	19.1	19.1	16.8	16.8
PI144E	27.5	27.5	26.9	26.9	25.0	25.0	22.8	22.8	20.0	20.0
PI144F	30.3	30.3	29.6	29.6	27.5	27.5	25.0	25.0	22.0	22.0
PI144G	33.0	33.0	32.3	32.3	30.0	30.0	27.3	27.3	24.0	24.0
PI144H	38.5	38.5	37.6	37.6	35.0	35.0	31.9	31.9	28.0	28.0
UCI224C	N/A	N/A	N/A	N/A	37.5	37.5	33.8	33.8	29.5	29.5
PI144J	44.0	44.0	43.0	43.0	40.0	40.0	36.4	36.4	32.0	32.0
PI144K	46.2	46.2	45.2	45.2	42.0	42.0	38.2	38.2	33.6	33.6
UCI224D	N/A	N/A	N/A	N/A	44.0	44.0	40.0	40.0	35.2	35.2
UCI224E	N/A	N/A	N/A	N/A	50.0	50.0	47.3	47.3	39.5	39.5
UCI224F	N/A	N/A	N/A	N/A	60.0	60.0	56.9	56.9	47.5	47.5
UCI224G	N/A	N/A	N/A	N/A	75.0	75.0	65.6	65.6	55.0	55.0
UCI274C	N/A	N/A	N/A	N/A	90.0	90.0	75.0	75.0	N/A	N/A
UCI274D	N/A	N/A	N/A	N/A	100.0	100.0	87.5	87.5	N/A	N/A
UCI274E	N/A	N/A	N/A	N/A	115.0	115.0	100.0	100.0	N/A	N/A
UCI274F	N/A	N/A	N/A	N/A	135.0	135.0	125.0	125.0	N/A	N/A
UCI274G	N/A	N/A	N/A	N/A	150.0	150.0	137.5	137.5	N/A	N/A
UCI274H	N/A	N/A	N/A	N/A	156.3	156.3	143.8	143.8	N/A	N/A
HCI444E	N/A	N/A	N/A	N/A	200.0	200.0	183.0	183.0	160.0	160.0
S4L1S-E	N/A	N/A	N/A	N/A	200.0	200.0	183.0	183.0	160.0	160.0
S4L1S-F	N/A	N/A	N/A	N/A	250.0	250.0	N/A	N/A	N/A	N/A



# 4 POLE Single Phase


**Dedicated**
**Series** 230V  
**Parallel** 115V  
**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 06	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	6.6	5.3	6.5	5.2	6.0	4.8	5.5	4.4	4.8	3.8
PI044E	8.8	7.0	8.7	7.0	8.0	6.4	7.3	5.8	6.4	5.1
PI044F	11.1	8.9	10.9	8.7	10.1	8.1	9.2	7.4	8.0	6.4
PI044G	13.3	10.6	13.0	10.4	12.1	9.7	11.0	8.8	9.6	7.7
PI044H	15.5	12.4	15.2	12.2	14.1	11.3	12.9	10.3	11.3	9.0
PI144D	18.0	14.4	17.6	14.1	16.3	13.0	14.9	11.9	13.1	10.5
PI144E	22.5	18.0	22.0	17.6	20.4	16.3	18.6	14.9	16.3	13.0
PI144F	24.7	19.8	24.2	19.4	22.5	18.0	20.4	16.3	18.0	14.4
PI144G	27.0	21.6	26.4	21.1	24.5	19.6	22.5	18.0	19.6	15.7
PI144H	31.5	25.2	30.6	24.5	28.6	22.9	26.2	21.0	22.9	18.3
PI144J	36.8	29.4	36.0	28.8	32.7	26.2	29.8	23.8	26.2	21.0
PI144K	38.2	30.6	36.8	29.4	34.0	27.2	32.3	25.8	26.9	21.5
UCI224C	N/A	N/A	N/A	N/A	37.5	30.0	33.8	27.0	29.5	23.6
UCI224D	N/A	N/A	N/A	N/A	44.0	35.2	40.0	32.0	35.2	28.2
UCI224E	N/A	N/A	N/A	N/A	50.0	40.0	47.3	37.8	39.5	31.6
UCI224F	N/A	N/A	N/A	N/A	60.0	48.0	56.9	45.5	47.5	38.0
UCI224G	N/A	N/A	N/A	N/A	70.0	56.0	65.6	52.5	55.0	44.0
UCI274C	N/A	N/A	N/A	N/A	84.0	67.2	75.0	60.0	63.8	51.0
UCI274D	N/A	N/A	N/A	N/A	96.0	76.8	87.5	70.0	71.3	57.0
UCI274E	N/A	N/A	N/A	N/A	112.0	89.6	100.0	80.0	82.5	66.0
UCI274F	N/A	N/A	N/A	N/A	135.0	108.0	125.0	100.0	100.0	80.0
UCI274G	N/A	N/A	N/A	N/A	150.0	120.0	137.5	110.0	118.8	95.0
UCI274H	N/A	N/A	N/A	N/A	156.3	125.0	143.8	115.0	125.0	100.0
HCI444E	N/A	N/A	N/A	N/A	200.0	160.0	183.0	146.4	160.0	128.0
S4L1S-E	N/A	N/A	N/A	N/A	200.0	160.0	183.0	146.4	160.0	128.0
S4L1S-F	N/A	N/A	N/A	N/A	250.0	200.0	N/A	N/A	N/A	N/A





# 4 POLE Single Phase


**Dedicated**
**Series** 230V  
**Parallel** 115V  
**60Hz/1800rpm**  
**1.0 Power Factor**

Winding 06	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	8.3	8.3	8.1	8.1	7.5	7.5	6.8	6.8	6.0	6.0
PI044E	11.0	11.0	10.8	10.8	10.0	10.0	9.1	9.1	8.0	8.0
PI044F	13.8	13.8	13.5	13.5	12.5	12.5	11.3	11.3	10.0	10.0
PI044G	16.5	16.5	16.2	16.2	15.0	15.0	13.6	13.6	12.0	12.0
PI044H	19.3	19.3	18.9	18.9	17.5	17.5	15.9	15.9	14.0	14.0
PI144D	23.1	23.1	22.6	22.6	21.0	21.0	19.1	19.1	16.8	16.8
PI144E	27.5	27.5	26.9	26.9	25.0	25.0	22.8	22.8	20.0	20.0
PI144F	30.3	30.3	29.6	29.6	27.5	27.5	25.0	25.0	22.0	22.0
PI144G	33.0	33.0	32.3	32.3	30.0	30.0	27.3	27.3	24.0	24.0
PI144H	38.5	38.5	37.6	37.6	35.0	35.0	31.9	31.9	28.0	28.0
UCI224C	N/A	N/A	N/A	N/A	37.5	37.5	33.8	33.8	29.5	29.5
PI144J	44.0	44.0	43.0	43.0	40.0	40.0	36.4	36.4	32.0	32.0
PI144K	46.2	46.2	45.2	45.2	42.0	42.0	38.2	38.2	33.6	33.6
UCI224D	N/A	N/A	N/A	N/A	44.0	44.0	40.0	40.0	35.2	35.2
UCI224E	N/A	N/A	N/A	N/A	50.0	50.0	47.3	47.3	39.5	39.5
UCI224F	N/A	N/A	N/A	N/A	60.0	60.0	56.9	56.9	47.5	47.5
UCI224G	N/A	N/A	N/A	N/A	75.0	75.0	65.6	65.6	55.0	55.0
UCI274C	N/A	N/A	N/A	N/A	90.0	90.0	75.0	75.0	N/A	N/A
UCI274D	N/A	N/A	N/A	N/A	100.0	100.0	87.5	87.5	N/A	N/A
UCI274E	N/A	N/A	N/A	N/A	115.0	115.0	100.0	100.0	N/A	N/A
UCI274F	N/A	N/A	N/A	N/A	135.0	135.0	125.0	125.0	N/A	N/A
UCI274G	N/A	N/A	N/A	N/A	150.0	150.0	137.5	137.5	N/A	N/A
UCI274H	N/A	N/A	N/A	N/A	156.3	156.3	143.8	143.8	N/A	N/A
HCI444E	N/A	N/A	N/A	N/A	200.0	200.0	183.0	183.0	160.0	160.0
S4L1S-E	N/A	N/A	N/A	N/A	200.0	200.0	183.0	183.0	160.0	160.0
S4L1S-F	N/A	N/A	N/A	N/A	250.0	250.0	N/A	N/A	N/A	N/A



# 4 POLE Single Phase


**Dedicated**
**Series** 240V  
**Parallel** 120V  
**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 06	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	6.9	5.5	6.8	5.4	6.3	5.0	5.7	4.6	5.0	4.0
PI044E	9.2	7.4	9.0	7.2	8.4	6.7	7.6	6.1	6.7	5.4
S0L1-J 1	9.8	7.8	9.5	7.6	9.0	7.2	8.1	6.5	7.2	5.8
PI044F	11.5	9.2	11.3	9.0	10.5	8.4	9.5	7.6	8.4	6.7
S0L1-S 1	13.1	10.5	12.7	10.2	12.0	9.6	10.8	8.6	9.6	7.7
PI044G	13.8	11.0	13.6	10.9	12.6	10.1	11.5	9.2	10.1	8.1
S0L2-G 1, 2	15.8	12.6	15.4	12.3	14.5	11.6	13.1	10.5	11.6	9.3
PI044H	16.1	12.9	15.8	12.6	14.7	11.8	13.4	10.7	11.7	9.4
PI144D	18.7	15.0	18.3	14.6	17.0	13.6	15.5	12.4	13.6	10.9
S0L2-M 1, 2	21.2	17.0	20.5	16.4	19.3	15.4	17.4	13.9	15.4	12.3
PI144E	23.4	18.7	22.9	18.3	21.3	17.0	19.4	15.5	17.0	13.6
PI144F	25.8	20.6	25.2	20.2	23.4	18.7	21.3	17.0	18.7	15.0
S0L2-U 1, 2	26.4	21.1	25.6	20.5	24.0	19.2	21.7	17.4	19.2	15.4
PI144G	28.1	22.5	27.5	22.0	25.5	20.4	23.4	18.7	20.4	16.3
S1L2-G 1, 2	30.0	24.0	28.6	22.9	27.0	21.6	24.4	19.5	21.6	17.3
S1L2-H 1, 2	31.9	25.5	30.7	24.6	29.0	23.2	26.2	21.0	23.2	18.6
PI144H	32.8	26.2	31.9	25.5	29.8	23.8	27.2	21.8	23.8	19.0
PI144J	38.3	30.6	37.5	30.0	34.1	27.3	31.1	24.9	27.2	21.8
S1L2-K 1, 2	38.2	30.6	36.8	29.4	34.7	27.8	31.4	25.1	27.8	22.2
PI144K	39.8	31.8	38.3	30.6	35.0	28.0	33.8	27.0	28.0	22.4
S1L2-N 1, 2	42.8	34.2	40.8	32.6	38.5	30.8	34.9	27.9	30.8	24.6
UCI224C	N/A	N/A	42.5	34.0	37.5	30.0	33.8	27.0	29.5	23.6
UCI224D	N/A	N/A	50.0	40.0	44.0	35.2	40.0	32.0	35.2	28.2
UCI224E	N/A	N/A	57.5	46.0	50.0	40.0	47.3	37.8	39.5	31.6
UCI224F	N/A	N/A	68.8	55.0	60.0	48.0	56.9	45.5	47.5	38.0
UCI224G	N/A	N/A	81.3	65.0	70.0	56.0	65.6	52.5	55.0	44.0
UCI274C	N/A	N/A	93.8	75.0	84.0	67.2	75.0	60.0	63.8	51.0
UCI274D	N/A	N/A	110.0	88.0	96.0	76.8	87.5	70.0	71.3	57.0
UCI274E	N/A	N/A	128.8	103.0	112.0	89.6	100.0	80.0	82.5	66.0
UCI274F	N/A	N/A	155.0	124.0	135.0	108.0	125.0	100.0	100.0	80.0
UCI274G	N/A	N/A	172.5	138.0	150.0	120.0	137.5	110.0	118.8	95.0
UCI274H	N/A	N/A	180.0	144.0	156.3	125.0	143.8	115.0	125.0	100.0
UCDI274J	N/A	N/A	N/A	N/A	175.0	140.0	160.0	128.0	N/A	N/A
UCDI274K	N/A	N/A	N/A	N/A	200.0	160.0	165.0	132.0	N/A	N/A
HCI444E	N/A	N/A	N/A	N/A	200.0	160.0	183.0	146.4	160.0	128.0
S4L1S-E	N/A	N/A	N/A	N/A	200.0	160.0	183.0	146.4	160.0	128.0
S4L1S-F	N/A	N/A	N/A	N/A	250.0	200.0	N/A	N/A	N/A	N/A

1. Available with single bearing only

2. Auxiliary winding option available (winding 706)



# 4 POLE Single Phase


**Dedicated**
**Series** 240V  
**Parallel** 120V  
**60Hz/1800rpm**  
**1.0 Power Factor**

Winding 06	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	8.3	8.3	8.1	8.1	7.5	7.5	6.8	6.8	6.0	6.0
S0L1-J 1	10.6	10.6	10.3	10.3	9.7	9.7	8.7	8.7	7.8	7.8
PI044E	11.0	11.0	10.8	10.8	10.0	10.0	9.1	9.1	8.0	8.0
PI044F	13.8	13.8	13.5	13.5	12.5	12.5	11.3	11.3	10.0	10.0
S0L1-S 1	14.1	14.1	13.7	13.7	13.0	13.0	11.7	11.7	10.4	10.4
PI044G	16.5	16.5	16.2	16.2	15.0	15.0	13.6	13.6	12.0	12.0
S0L2-G 1, 2	17.1	17.1	16.6	16.6	15.6	15.6	14.1	14.1	12.5	12.5
PI044H	19.3	19.3	18.9	18.9	17.5	17.5	15.9	15.9	14.0	14.0
S0L2-M 1, 2	22.9	22.9	22.2	22.2	20.8	20.8	18.8	18.8	16.6	16.6
PI144D	23.1	23.1	22.6	22.6	21.0	21.0	19.1	19.1	16.8	16.8
PI144E	27.5	27.5	26.9	26.9	25.0	25.0	22.8	22.8	20.0	20.0
S0L2-U 1, 2	28.5	28.5	27.6	27.6	25.9	25.9	23.5	23.5	20.7	20.7
PI144F	30.3	30.3	29.6	29.6	27.5	27.5	25.0	25.0	22.0	22.0
S1L2-G 1, 2	32.4	32.4	30.9	30.9	29.2	29.2	26.4	26.4	23.3	23.3
PI144G	33.0	33.0	32.3	32.3	30.0	30.0	27.3	27.3	24.0	24.0
S1L2-H 1, 2	34.4	34.4	33.2	33.2	31.3	31.3	28.3	28.3	25.0	25.0
PI144H	38.5	38.5	37.6	37.6	35.0	35.0	31.9	31.9	28.0	28.0
UCI224C	N/A	N/A	43.0	43.0	37.5	37.5	33.8	33.8	29.5	29.5
S1L2-K 1, 2	41.3	41.3	39.8	39.8	37.5	37.5	34.0	34.0	30.0	30.0
PI144J	44.0	44.0	43.0	43.0	40.0	40.0	36.4	36.4	32.0	32.0
S1L2-N 1, 2	46.2	46.2	44.0	44.0	41.6	41.6	37.6	37.6	33.3	33.3
PI144K	46.2	46.2	45.2	45.2	42.0	42.0	38.2	38.2	33.6	33.6
UCI224D	N/A	N/A	50.0	50.0	44.0	44.0	40.0	40.0	35.2	35.2
UCI224E	N/A	N/A	57.5	57.5	50.0	50.0	47.3	47.3	39.5	39.5
UCI224F	N/A	N/A	69.0	69.0	60.0	60.0	56.9	56.9	47.5	47.5
UCI224G	N/A	N/A	86.0	86.0	75.0	75.0	67.0	67.0	55.0	55.0
UCI274C	N/A	N/A	100.0	100.0	90.0	90.0	75.0	75.0	N/A	N/A
UCI274D	N/A	N/A	117.0	117.0	107.0	107.0	92.0	92.0	N/A	N/A
UCI274E	N/A	N/A	132.0	132.0	115.0	115.0	100.0	100.0	N/A	N/A
UCI274F	N/A	N/A	155.0	155.0	139.0	139.0	130.0	130.0	N/A	N/A
UCI274G	N/A	N/A	173.0	173.0	150.0	150.0	140.0	140.0	N/A	N/A
UCI274H	N/A	N/A	180.0	180.0	160.0	160.0	147.0	147.0	N/A	N/A
UCDI274J	N/A	N/A	N/A	N/A	175.0	175.0	160.0	160.0	N/A	N/A
UCDI274K	N/A	N/A	N/A	N/A	200.0	200.0	165.0	165.0	N/A	N/A
HCI444E	N/A	N/A	N/A	N/A	200.0	200.0	183.0	183.0	160.0	160.0
S4L1S-E	N/A	N/A	N/A	N/A	200.0	200.0	183.0	183.0	160.0	160.0
S4L1S-F	N/A	N/A	N/A	N/A	250.0	250.0	N/A	N/A	N/A	N/A

1. Available with single bearing only

2. Auxiliary winding option available (winding 706)



# 4 POLE Single Phase



**Reconnectable Double Delta 220V 60Hz/1800rpm  
0.8 Power Factor**

**1 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	5.0	4.0	4.9	3.9	4.6	3.7	4.1	3.3	3.6	2.9
S0L1-D 1	5.0	4.0	5.0	4.0	4.6	3.7	4.2	3.4	N/A	N/A
PI044E	6.7	5.4	6.6	5.3	6.1	4.9	5.5	4.4	4.9	3.9
S0L1-H 1	6.7	5.4	6.6	5.3	6.1	4.9	5.6	4.5	N/A	N/A
PI044F	8.3	6.6	8.2	6.6	7.6	6.1	6.9	5.5	6.1	4.9
S0L1-L 1	8.4	6.7	8.3	6.6	7.7	6.2	7.0	5.6	N/A	N/A
PI044G	10.0	8.0	9.8	7.8	9.1	7.3	8.3	6.6	7.3	5.8
S0L1-P 1	10.1	8.1	9.9	7.9	9.2	7.4	8.4	6.7	N/A	N/A
PI044H	11.7	9.4	11.5	9.2	10.6	8.5	9.7	7.8	8.5	6.8
S0L2-F 1, 2	11.8	9.4	11.6	9.3	10.7	8.6	9.9	7.9	N/A	N/A
PI144D	13.4	10.7	13.1	10.5	12.1	9.7	11.1	8.9	9.7	7.8
S0L2-G 1, 2	13.5	10.8	13.2	10.6	12.2	9.8	11.3	9.0	N/A	N/A
PI144E	16.7	13.4	16.3	13.0	15.2	12.2	13.8	11.0	12.1	9.7
S0L2-M 1, 2	16.8	13.4	16.5	13.2	15.3	12.2	14.1	11.3	N/A	N/A
PI144F	18.4	14.7	18.0	14.4	16.7	13.4	15.2	12.2	13.4	10.7
PI144G	20.0	16.0	19.6	15.7	18.2	14.6	16.7	13.4	14.6	11.7
S0L2-P 1, 2	20.2	16.2	19.8	15.8	18.4	14.7	16.9	13.5	N/A	N/A
PI144H	23.4	18.7	22.8	18.2	21.3	17.0	19.4	15.5	17.0	13.6
S1L2-J 1, 2	23.6	18.9	23.1	18.5	21.4	17.1	19.7	15.8	N/A	N/A
PI144J	27.3	21.8	26.7	21.4	24.3	19.4	22.2	17.8	19.4	15.5
S1L2-K 1, 2	26.9	21.5	26.4	21.1	24.5	19.6	22.5	18.0	N/A	N/A
PI144K	30.4	24.3	29.3	23.4	27.0	21.6	25.0	20.0	21.8	17.4
S1L2-N 1, 2	30.3	24.2	29.7	23.8	27.5	22.0	25.3	20.2	N/A	N/A
UCI224C	N/A	N/A	N/A	N/A	30.5	24.4	27.5	22.0	23.5	18.8
S1L2-R 1, 2	33.7	27.0	33.0	26.4	30.6	24.5	28.2	22.6	N/A	N/A
UCI224D	N/A	N/A	N/A	N/A	36.5	29.2	32.1	25.7	27.8	22.2
S1L2-Y 1, 2	42.1	33.7	41.3	33.0	38.3	30.6	35.2	28.2	N/A	N/A
UCI224E	N/A	N/A	N/A	N/A	41.3	33.0	38.1	30.5	32.3	25.8
UCI224F	N/A	N/A	N/A	N/A	50.0	40.0	45.6	36.5	39.4	31.5
UCI224G	N/A	N/A	N/A	N/A	56.9	45.5	53.1	42.5	45.6	36.5
UCI274C	N/A	N/A	N/A	N/A	61.3	49.0	53.1	42.5	45.6	36.5
UCI274D	N/A	N/A	N/A	N/A	72.0	57.6	66.0	52.8	54.0	43.2
UCI274E	N/A	N/A	N/A	N/A	84.0	67.2	76.5	61.2	65.6	52.5

1. Available with single bearing only

2. Auxiliary winding option available (winding 711)



# 4 POLE Single Phase



**Reconnectable Double Delta 220V 60Hz/1800rpm  
0.8 Power Factor**

**2 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274F	N/A	N/A	N/A	N/A	97.5	78.0	87.5	70.0	75.0	60.0
UCI274G	N/A	N/A	N/A	N/A	110.5	88.4	102.8	82.2	87.4	69.9
UCI274H	N/A	N/A	N/A	N/A	127.5	102.0	120.0	96.0	100.0	80.0
HCI444C	N/A	N/A	N/A	N/A	130.0	104.0	120.0	96.0	105.0	84.0
S4L1S-C	N/A	N/A	N/A	N/A	130.0	104.0	120.0	96.0	105.0	84.0
UCDI274J	N/A	N/A	N/A	N/A	150.0	120.0	135.0	108.0	116.0	92.8
UCDI274K	N/A	N/A	N/A	N/A	155.0	124.0	142.0	113.6	124.0	99.2
HCI444D	N/A	N/A	N/A	N/A	155.0	124.0	145.0	116.0	125.0	100.0
S4L1S-D	N/A	N/A	N/A	N/A	155.0	124.0	145.0	116.0	125.0	100.0
HCI444E	N/A	N/A	N/A	N/A	185.0	148.0	165.0	132.0	145.0	116.0
S4L1S-E	N/A	N/A	N/A	N/A	185.0	148.0	165.0	132.0	145.0	116.0
HCI544C	N/A	N/A	N/A	N/A	192.0	153.6	175.0	140.0	153.0	122.4
HCI544D	N/A	N/A	N/A	N/A	210.0	168.0	188.0	150.4	163.0	130.4
HCI444F	N/A	N/A	N/A	N/A	210.0	168.0	195.0	156.0	170.0	136.0
S4L1S-F	N/A	N/A	N/A	N/A	210.0	168.0	195.0	156.0	170.0	136.0
HCI544E	N/A	N/A	N/A	N/A	250.0	200.0	228.0	182.4	200.0	160.0
HCI544F	N/A	N/A	N/A	N/A	269.0	215.2	250.0	200.0	220.0	176.0



# 4 POLE Single Phase



**Reconnectable Double Delta 220V 60Hz/1800rpm  
1.0 Power Factor**

**1 of 2**

Winding 311	Model	TEMPERATURE RISE									
		Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
		kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
	S0L1-D 1	5.7	5.7	5.6	5.6	5.2	5.2	4.8	4.8	N/A	N/A
	PI044D	6.0	6.0	5.9	5.9	5.5	5.5	4.9	4.9	4.3	4.3
	S0L1-H 1	7.6	7.6	7.5	7.5	6.9	6.9	6.4	6.4	N/A	N/A
	PI044E	8.0	8.0	7.9	7.9	7.3	7.3	6.6	6.6	5.9	5.9
	S0L1-L 1	9.5	9.5	9.3	9.3	8.6	8.6	8.0	8.0	N/A	N/A
	PI044F	10.0	10.0	9.8	9.8	9.1	9.1	8.3	8.3	7.3	7.3
	S0L1-P 1	11.4	11.4	11.2	11.2	10.4	10.4	9.5	9.5	N/A	N/A
	PI044G	12.0	12.0	11.8	11.8	10.9	10.9	10.0	10.0	8.8	8.8
	S0L2-F 1, 2	13.3	13.3	13.1	13.1	12.1	12.1	11.1	11.1	N/A	N/A
	PI044H	14.0	14.0	13.8	13.8	12.7	12.7	11.6	11.6	10.2	10.2
	PI144D	14.5	14.5	14.1	14.1	13.1	13.1	12.0	12.0	10.5	10.5
	S0L2-G 1, 2	15.2	15.2	14.9	14.9	13.8	13.8	12.7	12.7	N/A	N/A
	PI144E	18.0	18.0	17.6	17.6	16.4	16.4	14.9	14.9	13.1	13.1
	S0L2-M 1, 2	19.0	19.0	18.7	18.7	17.3	17.3	15.9	15.9	N/A	N/A
	PI144F	19.9	19.9	19.4	19.4	18.0	18.0	16.4	16.4	14.5	14.5
	PI144G	21.6	21.6	21.2	21.2	19.7	19.7	18.0	18.0	15.8	15.8
	S0L2-P 1, 2	22.8	22.8	22.4	22.4	20.7	20.7	19.1	19.1	N/A	N/A
	PI144H	25.3	25.3	24.6	24.6	23.0	23.0	21.0	21.0	18.4	18.4
	S1L2-J 1, 2	26.6	26.6	26.1	26.1	24.2	24.2	22.3	22.3	N/A	N/A
	PI144J	29.5	29.5	28.8	28.8	26.2	26.2	24.0	24.0	21.0	21.0
	S1L2-K 1, 2	30.4	30.4	29.9	29.9	27.7	27.7	25.4	25.4	N/A	N/A
	PI144K	32.8	32.8	31.6	31.6	29.0	29.0	27.0	27.0	23.5	23.5
	UCI224C	N/A	N/A	N/A	N/A	30.5	30.5	27.5	27.5	23.5	23.5
	S1L2-N 1, 2	34.2	34.2	33.6	33.6	31.1	31.1	28.6	28.6	N/A	N/A
	S1L2-R 1, 2	38.0	38.0	37.3	37.3	34.6	34.6	31.8	31.8	N/A	N/A
	UCI224D	N/A	N/A	N/A	N/A	36.5	36.5	32.1	32.1	27.8	27.8
	UCI224E	N/A	N/A	N/A	N/A	41.3	41.3	38.1	38.1	32.3	32.3
	S1L2-Y 1, 2	47.5	47.5	46.7	46.7	43.2	43.2	39.8	39.8	N/A	N/A
	UCI224F	N/A	N/A	N/A	N/A	50.0	50.0	45.6	45.6	39.4	39.4
	UCI224G	N/A	N/A	N/A	N/A	56.9	56.9	53.1	53.1	45.6	45.6
	UCI274C	N/A	N/A	N/A	N/A	61.3	61.3	53.1	53.1	45.6	45.6
	UCI274D	N/A	N/A	N/A	N/A	72.0	72.0	66.0	66.0	54.0	54.0
	UCI274E	N/A	N/A	N/A	N/A	84.0	84.0	76.5	76.5	65.6	65.6

1. Available with single bearing only

2. Auxiliary winding option available (winding 711)



# 4 POLE Single Phase



**Reconnectable Double Delta 220V 60Hz/1800rpm  
1.0 Power Factor**

**2 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274F	N/A	N/A	N/A	N/A	97.5	97.5	87.5	87.5	75.0	75.0
UCI274G	N/A	N/A	N/A	N/A	110.5	110.5	102.8	102.8	87.4	87.4
UCI274H	N/A	N/A	N/A	N/A	127.5	127.5	120.0	120.0	100.0	100.0
HCI444C	N/A	N/A	N/A	N/A	130.0	130.0	120.0	120.0	105.0	105.0
S4L1S-C	N/A	N/A	N/A	N/A	130.0	130.0	120.0	120.0	105.0	105.0
UCDI274J	N/A	N/A	N/A	N/A	150.0	150.0	135.0	135.0	116.0	116.0
UCDI274K	N/A	N/A	N/A	N/A	155.0	155.0	142.0	142.0	124.0	124.0
HCI444D	N/A	N/A	N/A	N/A	155.0	155.0	145.0	145.0	125.0	125.0
HCI444E	N/A	N/A	N/A	N/A	185.0	185.0	165.0	165.0	145.0	145.0
S4L1S-E	N/A	N/A	N/A	N/A	185.0	185.0	165.0	165.0	145.0	145.0
HCI544C	N/A	N/A	N/A	N/A	192.0	192.0	175.0	175.0	153.0	153.0
HCI544D	N/A	N/A	N/A	N/A	210.0	210.0	188.0	188.0	163.0	163.0
HCI444F	N/A	N/A	N/A	N/A	210.0	210.0	195.0	195.0	170.0	170.0
S4L1S-F	N/A	N/A	N/A	N/A	210.0	210.0	195.0	195.0	170.0	170.0
HCI544E	N/A	N/A	N/A	N/A	250.0	250.0	228.0	228.0	200.0	200.0
HCI544F	N/A	N/A	N/A	N/A	269.0	269.0	250.0	250.0	220.0	220.0



# 4 POLE Single Phase



**Reconnectable Double Delta 230V 60Hz/1800rpm  
0.8 Power Factor**

**1 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	5.2	4.2	5.1	4.1	4.8	3.8	4.3	3.4	3.8	3.0
S0L1-D 1	5.2	4.2	5.2	4.2	4.8	3.8	4.4	3.5	N/A	N/A
PI044E	7.0	5.6	6.8	5.4	6.3	5.0	5.8	4.6	5.1	4.1
S0L1-H 1	7.0	5.6	6.9	5.5	6.4	5.1	5.9	4.7	N/A	N/A
PI044F	8.7	7.0	8.6	6.9	7.9	6.3	7.2	5.8	6.3	5.0
S0L1-L 1	8.7	7.0	8.6	6.9	8.0	6.4	7.3	5.8	N/A	N/A
PI044G	10.5	8.4	10.3	8.2	9.5	7.6	8.7	7.0	7.6	6.1
S0L1-P 1	10.5	8.4	10.3	8.2	9.5	7.6	8.8	7.0	N/A	N/A
PI044H	12.2	9.8	12.0	9.6	11.1	8.9	10.1	8.1	8.9	7.1
S0L2-F 1, 2	12.2	9.8	12.0	9.6	11.1	8.9	10.2	8.2	N/A	N/A
PI144D	13.9	11.1	13.6	10.9	12.7	10.2	11.5	9.2	10.1	8.1
S0L2-G 1, 2	14.0	11.2	13.7	11.0	12.7	10.2	11.7	9.4	N/A	N/A
PI144E	17.4	13.9	17.0	13.6	15.8	12.6	14.4	11.5	12.7	10.2
S0L2-M 1, 2	17.5	14.0	17.2	13.8	15.9	12.7	14.6	11.7	N/A	N/A
PI144F	19.2	15.4	18.8	15.0	17.4	13.9	15.8	12.6	13.9	11.1
PI144G	20.9	16.7	20.4	16.3	19.0	15.2	17.4	13.9	15.2	12.2
S0L2-P 1, 2	21.0	16.8	20.6	16.5	19.1	15.3	17.6	14.1	N/A	N/A
S1L2-J 1, 2	24.0	19.2	23.6	18.9	21.8	17.4	20.1	16.1	N/A	N/A
PI144H	24.4	19.5	23.8	19.0	22.2	17.8	20.3	16.2	17.7	14.2
S1L2-K 1, 2	27.5	22.0	27.0	21.6	25.0	20.0	23.0	18.4	N/A	N/A
PI144J	28.5	22.8	27.9	22.3	25.3	20.2	23.1	18.5	20.3	16.2
S1L2-N 1, 2	30.9	24.7	30.3	24.2	28.1	22.5	25.8	20.6	N/A	N/A
PI144K	31.7	25.4	30.6	24.5	28.5	22.8	26.0	20.8	22.7	18.2
S1L2-R 1, 2	34.3	27.4	33.7	27.0	31.2	25.0	28.7	23.0	N/A	N/A
UCI224C	N/A	N/A	N/A	N/A	32.0	25.6	28.8	23.0	24.8	19.8
UCI224D	N/A	N/A	N/A	N/A	38.3	30.6	33.5	26.8	29.0	23.2
S1L2-Y 1, 2	42.9	34.3	42.1	33.7	39.0	31.2	35.9	28.7	N/A	N/A
UCI224E	N/A	N/A	N/A	N/A	43.1	34.5	40.0	32.0	34.0	27.2
UCI224F	N/A	N/A	N/A	N/A	52.5	42.0	47.5	38.0	41.3	33.0
UCI224G	N/A	N/A	N/A	N/A	59.4	47.5	55.6	44.5	47.5	38.0
UCI274C	N/A	N/A	N/A	N/A	64.4	51.5	55.6	44.5	48.1	38.5
UCI274D	N/A	N/A	N/A	N/A	75.0	60.0	68.8	55.0	57.0	45.6
UCI274E	N/A	N/A	N/A	N/A	90.0	72.0	80.0	64.0	68.8	55.0

1. Available with single bearing only  
2. Auxiliary winding option available (winding 711)





# 4 POLE Single Phase



**Reconnectable Double Delta 230V 60Hz/1800rpm  
0.8 Power Factor**

**2 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274F	N/A	N/A	N/A	N/A	103.1	82.5	92.5	74.0	80.0	64.0
UCI274G	N/A	N/A	N/A	N/A	115.7	92.6	109.0	87.2	93.9	75.1
UCI274H	N/A	N/A	N/A	N/A	135.0	108.0	125.0	100.0	106.3	85.0
HCI444C	N/A	N/A	N/A	N/A	135.0	108.0	125.0	100.0	110.0	88.0
UCDI274J	N/A	N/A	N/A	N/A	157.0	125.6	145.0	116.0	122.0	97.6
HCI444D	N/A	N/A	N/A	N/A	165.0	132.0	155.0	124.0	135.0	108.0
S4L1S-D	N/A	N/A	N/A	N/A	165.0	132.0	155.0	124.0	135.0	108.0
UCDI274K	N/A	N/A	N/A	N/A	166.0	132.8	151.0	120.8	131.0	104.8
HCI444E	N/A	N/A	N/A	N/A	195.0	156.0	180.0	144.0	155.0	124.0
S4L1S-E	N/A	N/A	N/A	N/A	195.0	156.0	180.0	144.0	155.0	124.0
HCI544C	N/A	N/A	N/A	N/A	200.0	160.0	183.0	146.4	160.0	128.0
HCI444F	N/A	N/A	N/A	N/A	220.0	176.0	200.0	160.0	180.0	144.0
S4L1S-F	N/A	N/A	N/A	N/A	220.0	176.0	200.0	160.0	180.0	144.0
HCI544D	N/A	N/A	N/A	N/A	220.0	176.0	198.0	158.4	174.0	139.2
HCI544E	N/A	N/A	N/A	N/A	261.0	208.8	238.0	190.4	210.0	168.0
HCI544F	N/A	N/A	N/A	N/A	281.0	224.8	263.0	210.4	231.0	184.8



# 4 POLE Single Phase



**Reconnectable Double Delta 230V 60Hz/1800rpm  
1.0 Power Factor**

**1 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S0L1-D 1	5.9	5.9	5.8	5.8	5.4	5.4	5.0	5.0	N/A	N/A
PI044D	6.2	6.2	6.1	6.1	5.8	5.8	5.2	5.2	4.6	5.6
S0L1-H 1	7.9	7.9	7.8	7.8	7.2	7.2	6.6	6.6	N/A	N/A
PI044E	8.4	8.4	8.2	8.2	7.6	7.6	7.0	7.0	6.1	7.1
S0L1-L 1	9.9	9.9	9.7	9.7	9.0	9.0	8.3	8.3	N/A	N/A
PI044F	10.4	10.4	10.3	10.3	9.5	9.5	8.6	8.6	7.6	8.6
S0L1-P 1	11.9	11.9	11.6	11.6	10.8	10.8	9.9	9.9	N/A	N/A
PI044G	12.6	12.6	12.4	12.4	11.4	11.4	10.4	10.4	9.1	10.1
S0L2-F 1, 2	13.8	13.8	13.6	13.6	12.6	12.6	11.6	11.6	N/A	N/A
PI044H	14.6	14.6	14.4	14.4	13.3	13.3	12.1	12.1	10.7	11.7
PI144D	15.0	15.0	14.7	14.7	13.7	13.7	12.4	12.4	10.9	11.9
S0L2-G 1, 2	15.8	15.8	15.5	15.5	14.4	14.4	13.2	13.2	N/A	N/A
PI144E	18.8	18.8	18.4	18.4	17.1	17.1	15.6	15.6	13.7	14.7
S0L2-M 1, 2	19.8	19.8	19.4	19.4	18.0	18.0	16.5	16.5	N/A	N/A
PI144F	20.7	20.7	20.3	20.3	18.8	18.8	17.1	17.1	15.0	15.0
PI144G	22.6	22.6	22.0	22.0	20.5	20.5	18.8	18.8	16.4	16.4
S0L2-P 1, 2	23.7	23.7	23.3	23.3	21.6	21.6	19.8	19.8	N/A	N/A
S1L2-J	27.1	27.1	26.7	26.7	24.7	24.7	22.7	22.7	N/A	N/A
PI144H	26.4	26.4	25.7	25.7	24.0	24.0	21.9	21.9	19.1	20.1
PI144J	30.8	30.8	30.1	30.1	27.3	27.3	24.9	24.9	21.9	22.9
S1L2-K 1, 2	31.0	31.0	30.5	30.5	28.2	28.2	25.9	25.9	N/A	N/A
PI144K	34.1	34.1	33.0	33.0	31.0	31.0	28.0	28.0	24.5	25.5
S1L2-N 1, 2	34.9	34.9	34.3	34.3	31.7	31.7	29.2	29.2	N/A	N/A
S1L2-R 1, 2	38.8	38.8	38.1	38.1	35.3	35.3	32.4	32.4	N/A	N/A
UCI224C	N/A	N/A	N/A	N/A	32.0	32.0	28.8	28.8	24.8	24.8
UCI224D	N/A	N/A	N/A	N/A	38.3	38.3	33.5	33.5	29.0	29.0
UCI224E	N/A	N/A	N/A	N/A	43.1	43.1	40.0	40.0	34.0	34.0
S1L2-Y 1, 2	48.5	48.5	47.6	47.6	44.1	44.1	40.5	40.5	N/A	N/A
UCI224F	N/A	N/A	N/A	N/A	52.5	52.5	47.5	47.5	41.3	41.3
UCI224G	N/A	N/A	N/A	N/A	59.4	59.4	55.6	55.6	47.5	47.5
UCI274C	N/A	N/A	N/A	N/A	64.4	64.4	55.6	55.6	48.1	48.1
UCI274D	N/A	N/A	N/A	N/A	75.0	75.0	68.8	68.8	57.0	57.0
UCI274E	N/A	N/A	N/A	N/A	90.0	90.0	80.0	80.0	68.8	68.8

1. Available with single bearing only

2. Auxiliary winding option available (winding 711)



# 4 POLE Single Phase



**Reconnectable Double Delta 230V 60Hz/1800rpm  
1.0 Power Factor**

**2 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274F	N/A	N/A	N/A	N/A	103.1	103.1	92.5	92.5	80.0	80.0
UCI274G	N/A	N/A	N/A	N/A	115.7	115.7	109.0	109.0	93.9	93.9
UCI274H	N/A	N/A	N/A	N/A	135.0	135.0	125.0	125.0	106.3	106.3
HCI444C	N/A	N/A	N/A	N/A	135.0	135.0	125.0	125.0	110.0	110.0
S4L1S-C	N/A	N/A	N/A	N/A	135.0	135.0	125.0	125.0	110.0	110.0
UCDI274J	N/A	N/A	N/A	N/A	157.0	157.0	145.0	145.0	122.0	122.0
HCI444D	N/A	N/A	N/A	N/A	165.0	165.0	155.0	155.0	135.0	135.0
S4L1S-D	N/A	N/A	N/A	N/A	165.0	165.0	155.0	155.0	135.0	135.0
UCDI274K	N/A	N/A	N/A	N/A	166.0	166.0	151.0	151.0	131.0	131.0
HCI444E	N/A	N/A	N/A	N/A	195.0	195.0	180.0	180.0	155.0	155.0
S4L1S-E	N/A	N/A	N/A	N/A	195.0	195.0	180.0	180.0	155.0	155.0
HCI544C	N/A	N/A	N/A	N/A	200.0	200.0	183.0	183.0	160.0	160.0
HCI444F	N/A	N/A	N/A	N/A	220.0	220.0	200.0	200.0	180.0	180.0
HCI544D	N/A	N/A	N/A	N/A	220.0	220.0	198.0	198.0	174.0	174.0
HCI544E	N/A	N/A	N/A	N/A	261.0	261.0	238.0	238.0	210.0	210.0
HCI544F	N/A	N/A	N/A	N/A	281.0	281.0	263.0	263.0	231.0	231.0



# 4 POLE Single Phase



**Reconnectable Double Delta 240V 60Hz/1800rpm  
0.8 Power Factor**

**1 of 2**

Winding 311	Model	TEMPERATURE RISE									
		Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
		kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
	S0L1-D 1	5.4	4.3	5.3	4.2	5.0	4.0	4.6	3.7	3.7	3.0
	PI044D	5.4	4.3	5.3	4.2	5.0	4.0	4.5	3.6	4.0	3.2
	PI044E	7.3	5.8	7.1	5.7	6.6	5.3	6.0	4.8	5.3	4.2
	S0L1-H 1	7.3	5.8	7.1	5.7	6.6	5.3	6.1	4.9	5.0	4.0
	S0L1-L 1	9.1	7.3	8.9	7.1	8.3	6.6	7.6	6.1	6.2	5.0
	PI044F	9.1	7.3	8.9	7.1	8.3	6.6	7.5	6.0	6.6	5.3
	PI044G	10.9	8.7	10.7	8.6	9.9	7.9	9.0	7.2	7.9	6.3
	S0L1-P 1	10.9	8.7	10.7	8.6	9.9	7.9	9.1	7.3	7.5	6.0
	S0L2-F 1, 2	12.5	10.0	12.2	9.8	11.3	9.0	10.4	8.3	8.7	7.0
	PI044H	12.7	10.2	12.5	10.0	11.6	9.3	10.6	8.5	9.2	7.4
	S0L2-G 1, 2	14.3	11.4	14.0	11.2	13.0	10.4	11.9	9.5	10.0	8.0
	PI144D	14.5	11.6	14.2	11.4	13.2	10.6	12.0	9.6	10.6	8.5
	S0L2-M 1, 2	17.8	14.2	17.5	14.0	16.2	13.0	14.9	11.9	12.5	10.0
	PI144E	18.2	14.6	17.8	14.2	16.5	13.2	15.0	12.0	13.2	10.6
	PI144F	20.0	16.0	19.5	15.6	18.2	14.6	16.5	13.2	14.5	11.6
	S0L2-P 1, 2	21.4	17.1	21.0	16.8	19.4	15.5	17.9	14.3	15.0	12.0
	PI144G	21.8	17.4	21.3	17.0	19.8	15.8	18.2	14.6	15.8	12.6
	S1L2-J 1, 2	24.9	19.9	24.5	19.6	22.7	18.2	20.9	16.7	17.5	14.0
	PI144H	25.4	20.3	24.8	19.8	23.1	18.5	21.1	16.9	18.5	14.8
	S1L2-K 1, 2	28.5	22.8	28.0	22.4	25.9	20.7	23.8	19.0	20.0	16.0
	PI144J	29.7	23.8	29.0	23.2	26.4	21.1	24.1	19.3	21.1	16.9
	S1L2-N 1, 2	32.1	25.7	31.5	25.2	29.2	23.4	26.8	21.4	22.5	18.0
	PI144K	33.0	26.4	31.9	25.5	30.0	24.0	27.0	21.6	23.7	19.0
	S1L2-R 1, 2	35.6	28.5	35.0	28.0	32.4	25.9	29.8	23.8	25.0	20.0
	UCI224C	N/A	N/A	N/A	N/A	33.5	26.8	30.0	24.0	26.0	20.8
	UCI224D	N/A	N/A	N/A	N/A	40.0	32.0	35.0	28.0	30.5	24.4
	S1L2-Y 1, 2	44.6	35.7	43.7	35.0	40.5	32.4	37.3	29.8	31.2	25.0
	UCI224E	N/A	N/A	N/A	N/A	45.0	36.0	41.9	33.5	35.6	28.5
	UCI224F	N/A	N/A	N/A	N/A	56.0	44.8	50.0	40.0	43.8	35.0
	UCI224G	N/A	N/A	N/A	N/A	62.5	50.0	58.8	47.0	50.0	40.0
	UCI274C	N/A	N/A	N/A	N/A	67.5	54.0	58.5	46.8	50.6	40.5
	UCI274D	N/A	N/A	N/A	N/A	78.8	63.0	72.0	57.6	60.0	48.0



# 4 POLE Single Phase



**Reconnectable Double Delta 240V 60Hz/1800rpm  
0.8 Power Factor**

**2 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274E	N/A	N/A	N/A	N/A	96.0	76.8	84.0	67.2	72.0	57.6
UCI274F	N/A	N/A	N/A	N/A	108.8	87.0	97.5	78.0	84.0	67.2
UCI274G	N/A	N/A	N/A	N/A	123.4	98.72	115.7	92.6	100.3	80.2
HCI444C	N/A	N/A	N/A	N/A	140.0	112.0	130.0	104.0	115.0	92.0
S4L1S-C	N/A	N/A	N/A	N/A	140.0	112.0	130.0	104.0	115.0	92.0
UCI274H	N/A	N/A	N/A	N/A	142.5	114.0	131.3	105.0	112.5	90.0
UCDI274J	N/A	N/A	N/A	N/A	161.0	128.8	150.0	120.0	128.0	102.4
HCI444D	N/A	N/A	N/A	N/A	170.0	136.0	160.0	128.0	140.0	112.0
S4L1S-D	N/A	N/A	N/A	N/A	170.0	136.0	160.0	128.0	140.0	112.0
UCDI274K	N/A	N/A	N/A	N/A	175.0	140.0	160.0	128.0	140.0	112.0
HCI444E	N/A	N/A	N/A	N/A	200.0	160.0	185.0	148.0	160.0	128.0
S4L1S-E	N/A	N/A	N/A	N/A	200.0	160.0	185.0	148.0	160.0	128.0
HCI544C	N/A	N/A	N/A	N/A	210.0	168.0	190.0	152.0	168.0	134.4
HCI544D	N/A	N/A	N/A	N/A	230.0	184.0	208.0	166.4	180.0	144.0
HCI444F	N/A	N/A	N/A	N/A	230.0	184.0	210.0	168.0	185.0	148.0
S4L1S-F	N/A	N/A	N/A	N/A	230.0	184.0	210.0	168.0	185.0	148.0
HCI544E	N/A	N/A	N/A	N/A	273.0	218.4	250.0	200.0	220.0	176.0
HCI544F	N/A	N/A	N/A	N/A	295.0	236.0	275.0	220.0	243.0	194.4



# 4 POLE Single Phase



**Reconnectable Double Delta 240V 60Hz/1800rpm  
1.0 Power Factor**

**1 of 2**

Winding 311	Model	TEMPERATURE RISE									
		Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
		kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
	S0L1-D 1	6.2	6.2	6.0	6.0	5.6	5.6	5.1	5.1	4.3	4.3
	PI044D	6.5	6.5	6.4	6.4	6.0	6.0	5.4	5.4	4.8	4.8
	S0L1-H 1	8.2	8.2	8.1	8.1	7.5	7.5	6.9	6.9	5.8	5.8
	PI044E	8.8	8.8	8.5	8.5	7.9	7.9	7.2	7.2	6.4	6.4
	S0L1-L 1	10.3	10.3	10.1	10.1	9.3	9.3	8.6	8.6	7.2	7.2
	PI044F	10.9	10.9	10.7	10.7	10.0	10.0	9.0	9.0	7.9	7.9
	S0L1-P 1	12.3	12.3	12.1	12.1	11.2	11.2	10.3	10.3	8.7	8.7
	PI044G	13.1	13.1	12.8	12.8	11.9	11.9	10.8	10.8	9.5	9.5
	S0L2-F 1, 2	14.1	14.1	13.8	13.8	12.8	12.8	11.8	11.8	10.1	10.1
	PI044H	15.2	15.2	15.0	15.0	13.9	13.9	12.7	12.7	11.0	11.0
	PI144D	15.7	15.7	15.3	15.3	14.3	14.3	13.0	13.0	11.4	11.4
	S0L2-G 1, 3	16.1	16.1	15.8	15.8	14.6	14.6	13.5	13.5	11.6	11.6
	PI144E	19.7	19.7	19.2	19.2	17.8	17.8	16.2	16.2	14.3	14.3
	S0L2-M 1, 3	20.1	20.1	19.8	19.8	18.3	18.3	16.8	16.8	14.5	14.5
	PI144F	21.6	21.6	21.1	21.1	19.7	19.7	17.8	17.8	15.7	15.7
	PI14G	23.5	23.5	23.0	23.0	21.4	21.4	19.7	19.7	17.1	17.1
	S0L2-P 1, 3	24.2	24.2	23.7	23.7	22.0	22.0	20.2	20.2	17.4	17.4
	PI144H	27.4	27.4	26.8	26.8	24.9	24.9	26.8	26.8	20.0	20.0
	S1L2-J 1, 3	28.2	28.2	27.7	27.7	25.6	25.6	23.6	23.6	20.3	20.3
	PI144J	32.1	32.1	31.3	31.3	28.5	28.5	26.0	26.0	22.8	22.8
	S1L2-K 1, 3	32.2	32.2	31.6	31.6	29.3	29.3	26.9	26.9	23.2	23.2
	S1L2-N 1, 2	36.2	36.2	35.6	35.6	33.0	33.0	30.3	30.3	26.1	26.1
	PI144K	35.6	35.6	34.5	34.5	33.0	33.0	29.0	29.0	25.6	25.6
	S1L2-R 1, 2	40.3	40.3	39.5	39.5	36.6	36.6	33.7	33.7	29.0	29.0
	UCI224C	N/A	N/A	N/A	N/A	33.5	33.5	30.0	30.0	26.0	26.0
	UCI224D	N/A	N/A	N/A	N/A	40.0	40.0	35.0	35.0	30.5	30.5
	UCI224E	N/A	N/A	N/A	N/A	45.0	45.0	41.9	41.9	35.6	35.6
	S1L2-Y 1, 3	50.3	50.3	49.4	49.4	45.8	45.8	42.1	42.1	36.2	36.2
	UCI224F	N/A	N/A	N/A	N/A	56.0	56.0	50.0	50.0	43.8	43.8
	UCI224G	N/A	N/A	N/A	N/A	62.5	62.5	58.8	58.8	50.0	50.0
	UCI274C	N/A	N/A	N/A	N/A	67.5	67.5	58.5	58.5	50.6	50.6
	UCI274D	N/A	N/A	N/A	N/A	78.8	78.8	72.0	72.0	60.0	60.0



# 4 POLE Single Phase



**Reconnectable Double Delta 240V 60Hz/1800rpm  
1.0 Power Factor**

**2 of 2**

Winding 311	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274E	N/A	N/A	N/A	N/A	96.0	96.0	84.0	84.0	72.0	72.0
UCI274F	N/A	N/A	N/A	N/A	108.8	108.8	97.5	97.5	84.0	84.0
UCI274G	N/A	N/A	N/A	N/A	123.4	123.4	115.7	115.7	100.3	100.3
HCI444C	N/A	N/A	N/A	N/A	140.0	140.0	130.0	130.0	115.0	115.0
S4L1S-C	N/A	N/A	N/A	N/A	140.0	140.0	130.0	130.0	115.0	115.0
UCI274H	N/A	N/A	N/A	N/A	142.5	142.5	131.3	131.3	112.5	112.5
UCDI274J	N/A	N/A	N/A	N/A	161.0	161.0	150.0	150.0	128.0	128.0
HCI444D	N/A	N/A	N/A	N/A	170.0	170.0	160.0	160.0	140.0	140.0
S4L1S-D	N/A	N/A	N/A	N/A	170.0	170.0	160.0	160.0	140.0	140.0
UCDI274K	N/A	N/A	N/A	N/A	175.0	175.0	160.0	160.0	140.0	140.0
HCI444E	N/A	N/A	N/A	N/A	200.0	200.0	185.0	185.0	160.0	160.0
S4L1S-E	N/A	N/A	N/A	N/A	200.0	200.0	185.0	185.0	160.0	160.0
HCI544C	N/A	N/A	N/A	N/A	210.0	210.0	190.0	190.0	168.0	168.0
HCI544D	N/A	N/A	N/A	N/A	230.0	230.0	208.0	208.0	180.0	180.0
HCI444F	N/A	N/A	N/A	N/A	230.0	230.0	210.0	210.0	185.0	185.0
S4L1S-F	N/A	N/A	N/A	N/A	230.0	230.0	210.0	210.0	185.0	185.0
HCI544E	N/A	N/A	N/A	N/A	273.0	273.0	250.0	250.0	220.0	220.0
HCI544F	N/A	N/A	N/A	N/A	295.0	295.0	275.0	275.0	243.0	243.0



# 4 POLE Three Phase



Star 380V  
Parallel Star 190V  
Delta 220V

50Hz/1500rpm  
0.8 Power Factor

1 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S0L1-D 1	7.6	6.1	7.2	5.8	6.9	5.5	6.2	5.0	N/A	N/A
PI04D	8.3	6.6	8.1	6.5	7.5	6.0	6.8	5.4	6.0	4.8
S0L1-H 1	10.1	8.1	9.8	7.8	9.2	7.4	8.3	6.6	N/A	N/A
PI04E	11.0	8.8	10.8	8.6	10.0	8.0	9.1	7.3	8.0	6.4
S0L1-L 1	12.6	10.1	12.2	9.8	11.4	9.1	10.4	8.3	N/A	N/A
PI04F	13.8	11.0	13.5	10.8	12.5	10.0	11.4	9.1	10.0	8.0
S0L1-P 1	15.1	12.1	14.7	11.8	13.7	11.0	12.5	10.0	N/A	N/A
PI04G	16.5	13.2	16.2	13.0	15.0	12.0	13.7	11.0	12.0	9.6
S0L2-F 1,2	17.7	14.2	17.1	13.7	16.0	12.8	14.6	11.7	N/A	N/A
PI04H	19.3	15.4	18.9	15.1	17.5	14.0	16.0	12.8	14.0	11.2
S0L2-G 1,2	20.1	16.1	19.5	15.6	18.3	14.6	16.7	13.4	N/A	N/A
PI14D	22.0	17.6	21.5	17.2	20.0	16.0	18.2	14.6	16.0	12.8
S0L2-M 1,2	25.2	20.2	24.4	19.5	22.9	18.3	20.8	16.6	N/A	N/A
PI14E	27.5	22.0	26.9	21.5	25.0	20.0	22.8	18.2	20.0	16.0
PI14F	30.3	24.2	29.6	23.7	27.5	22.0	25.0	20.0	22.0	17.6
S0L2-P 1,2	30.2	24.2	29.3	23.4	27.5	22.0	25.0	20.0	N/A	N/A
PI14G	33.0	26.4	32.3	25.8	30.0	24.0	27.5	22.0	24.0	19.2
S1L2-J 1,2	35.3	28.2	34.3	27.4	32.0	25.6	29.2	23.4	N/A	N/A
PI14H	38.5	30.8	37.5	30.0	35.0	28.0	32.0	25.6	28.0	22.4
S1L2-K 1,2	40.3	32.2	39.0	31.2	36.6	29.3	33.3	26.6	N/A	N/A
PI14J	45.0	36.0	44.0	35.2	40.0	32.0	36.5	29.2	32.0	25.6
S1L2-N 1,2	45.3	36.2	44.0	35.2	41.2	33.0	37.5	30.0	N/A	N/A
UCI224C	46.8	37.4	45.0	36.0	42.5	34.0	37.5	30.0	33.0	26.4
PI14K	46.8	37.4	45.0	36.0	42.5	34.0	37.5	30.0	32.9	26.3
S1L2-R 1,2	50.4	40.3	48.8	39.0	45.8	36.6	41.7	33.4	N/A	N/A
UCI224D	55.0	44.0	53.0	42.4	50.0	40.0	45.0	36.0	40.0	32.0
S1L2-Y 1,2	63.0	50.4	61.0	48.8	57.2	45.8	52.1	41.7	N/A	N/A
UCI224E	63.0	50.4	61.0	48.8	60.0	48.0	53.0	42.4	47.0	37.6
UCI224F	80.0	64.0	77.0	61.6	72.5	58.0	65.0	52.0	56.0	44.8
UCI224G	90.8	72.6	87.5	70.0	85.0	68.0	75.0	60.0	68.0	54.4
UCI274C	110.0	88.0	106.0	84.8	100.0	80.0	84.0	67.2	75.0	60.0
UCI274D	125.0	100.0	121.0	96.8	114.0	91.2	100.0	80.0	90.0	72.0
UCI274E	150.0	120.0	145.0	116.0	140.0	112.0	125.0	100.0	112.5	90.0
UCI274F	175.0	140.0	170.0	136.0	160.0	128.0	145.0	116.0	126.0	100.8

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only





# 4 POLE Three Phase



Star 380V  
Parallel Star 190V  
Delta 220V

50Hz/1500rpm  
0.8 Power Factor

2 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274G	200.0	160.0	187.0	149.6	182.0	145.6	164.6	131.7	143.0	114.4
UCI274H	220.0	176.0	212.0	169.6	200.0	160.0	182.0	145.6	158.0	126.4
UCDI274J	260.0	208.0	250.0	200.0	230.0	184.0	210.0	168.0	180.0	144.0
UCDI274K	275.0	220.0	265.0	212.0	250.0	200.0	229.0	183.2	200.0	160.0
HCI444C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
S4L1S-C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
S4L1D-C 1	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
HCI444D	330.0	264.0	320.0	256.0	300.0	240.0	280.0	224.0	240.0	192.0
S4L1S-D	330.0	264.0	320.0	256.0	300.0	240.0	280.0	224.0	240.0	192.0
S4L1D-D 1	330.0	264.0	320.0	256.0	300.0	240.0	280.0	224.0	240.0	192.0
HCI444E	380.0	304.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
S4L1S-E	380.0	304.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
S4L1D-E 1	380.0	304.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
S4L1S-F	425.0	340.0	415.0	332.0	400.0	320.0	370.0	296.0	320.0	256.0
HCI444F	425.0	340.0	415.0	332.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1D-F 1	425.0	340.0	415.0	332.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1D-G	475.0	380.0	455.0	364.0	430.0	344.0	390.0	312.0	345.0	276.0
S5L1S-C	500.0	400.0	478.0	382.4	455.0	364.0	400.0	320.0	350.0	280.0
S5L1D-C 1	500.0	400.0	478.0	382.4	455.0	364.0	400.0	320.0	350.0	280.0
HCI544C	500.0	400.0	478.0	382.4	455.0	364.0	400.0	320.0	350.0	280.0
HCI544D	550.0	440.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
S5L1S-D	550.0	440.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
S5L1D-D 1	550.0	440.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
HCI544E	660.0	528.0	636.0	508.8	600.0	480.0	550.0	440.0	480.0	384.0
S5L1S-E	660.0	528.0	636.0	508.8	600.0	480.0	550.0	440.0	480.0	384.0
S5L1D-E 1	660.0	528.0	636.0	508.8	600.0	480.0	550.0	440.0	480.0	384.0
HCI544F	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1S-F	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1D-F 1	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1D-G 1	750.0	600.0	720.0	576.0	680.0	544.0	625.0	500.0	544.0	435.2
S5L1D-H 1	780.0	624.0	755.0	604.0	710.0	568.0	650.0	520.0	568.0	454.4
S6L1D-C 3	850.0	680.0	825.0	660.0	800.0	640.0	750.0	600.0	650.0	520.0
HCI634G 3	850.0	680.0	825.0	660.0	800.0	640.0	750.0	600.0	650.0	520.0
HCI634H 3	1000.0	800.0	960.0	768.0	910.0	728.0	830.0	664.0	740.0	592.0
S6L1D-D 3	1000.0	800.0	960.0	768.0	910.0	728.0	830.0	664.0	740.0	592.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6)



# 4 POLE Three Phase



Star 380V  
Parallel Star 190V  
Delta 220V

50Hz/1500rpm  
0.8 Power Factor

3 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S6L1D-E 3	1100.0	880.0	1060.0	848.0	1000.0	800.0	900.0	720.0	800.0	640.0
HCI634J 3	1100.0	880.0	1060.0	848.0	1000.0	800.0	900.0	720.0	800.0	640.0
S6L1D-F 3	1220.0	976.0	1180.0	944.0	1110.0	888.0	1000.0	800.0	885.0	708.0
HCI634K 3	1220.0	976.0	1180.0	944.0	1110.0	888.0	1000.0	800.0	885.0	708.0
S6L1D-G 3	1290.0	1032.0	1255.0	1004.0	1205.0	964.0	1085.0	868.0	965.0	772.0
PI734A 3	1310.0	1048.0	1275.0	1020.0	1225.0	980.0	1140.0	912.0	1055.0	844.0
S6L1D-H 3	1430.0	1144.0	1390.0	1112.0	1335.0	1068.0	1240.0	992.0	1140.0	912.0
PI734B 3	1455.0	1164.0	1415.0	1132.0	1360.0	1088.0	1265.0	1012.0	1170.0	936.0
S7L1D-C 3	1615.0	1292.0	1570.0	1256.0	1505.0	1204.0	1400.0	1120.0	1295.0	1036.0
PI734C 3	1615.0	1292.0	1570.0	1256.0	1505.0	1204.0	1400.0	1120.0	1295.0	1036.0
S7L1D-D 3	1715.0	1372.0	1675.0	1340.0	1615.0	1292.0	1500.0	1200.0	1380.0	1104.0
PI734D 3	1715.0	1372.0	1675.0	1340.0	1615.0	1292.0	1500.0	1200.0	1380.0	1104.0
S7L1D-E 3	1819.0	1455.2	1768.0	1414.4	1700.0	1360.0	1580.0	1264.0	1460.0	1168.0
S7L1D-F 3	1975.0	1580.0	1920.0	1536.0	1845.0	1476.0	1715.0	1372.0	1585.0	1268.0
PI734E 3	1975.0	1580.0	1920.0	1536.0	1845.0	1476.0	1715.0	1372.0	1585.0	1268.0
S7L1D-G 3	2165.0	1732.0	2105.0	1684.0	2020.0	1616.0	1880.0	1504.0	1735.0	1388.0
PI734F 3	2165.0	1732.0	2105.0	1684.0	2020.0	1616.0	1880.0	1504.0	1735.0	1388.0
PI734G 3	2290.0	1832.0	2225.0	1780.0	2135.0	1708.0	1985.0	1588.0	1835.0	1468.0
S7L1D-H 3	2290.0	1832.0	2225.0	1780.0	2135.0	1708.0	1985.0	1588.0	1835.0	1468.0
PI734H 3	2500.0	2000.0	2410.0	1928.0	2250.0	1800.0	2100.0	1680.0	1825.0	1460.0
P80-LVSI804R 3	2515.0	2012.0	2445.0	1956.0	2290.0	1832.0	2100.0	1680.0	1830.0	1464.0
S7L1D-J 3	2600.0	2080.0	2525.0	2020.0	2425.0	1940.0	2200.0	1760.0	1950.0	1560.0
P80-LVSI804S 3	2915.0	2332.0	2835.0	2268.0	2650.0	2120.0	2430.0	1944.0	2125.0	1700.0
P80-LVSI804T 3	3180.0	2544.0	3095.0	2476.0	2895.0	2316.0	2660.0	2128.0	2325.0	1860.0
P80-LVSI804W 3,4	3715.0	2972.0	3610.0	2888.0	3375.0	2700.0	3155.0	2524.0	2740.0	2192.0
P80-LVSI804X 3,4	4080.0	3264.0	3970.0	3176.0	3715.0	2972.0	3470.0	2776.0	3015.0	2412.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 400V  
 Parallel Star 200V  
 Delta 230V

50Hz/1500rpm  
 0.8 Power Factor

1 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
	Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA
PI04D	8.3	6.6	8.1	6.5	7.5	6.0	6.8	5.4	6.0	4.8
S0L1--D 1	8.3	6.6	8.0	6.4	7.5	6.0	6.8	5.4	N/A	N/A
PI04E	11.0	8.8	10.8	8.6	10.0	8.0	9.1	7.3	8.0	6.4
S0L1--H 1	11.0	8.8	10.7	8.6	10.0	8.0	9.1	7.3	N/A	N/A
PI04F	13.8	11.0	13.5	10.8	12.5	10.0	11.4	9.1	10.0	8.0
S0L1--L 1	13.8	11.0	13.3	10.6	12.5	10.0	11.4	9.1	N/A	N/A
PI04G	16.5	13.2	16.2	13.0	15.0	12.0	13.7	11.0	12.0	9.6
S0L1--P 1	16.5	13.2	16.0	12.8	15.0	12.0	13.7	11.0	N/A	N/A
PI04H	19.3	15.4	18.9	15.1	17.5	14.0	16.0	12.8	14.0	11.2
S0L2--F 1,2	19.3	15.4	18.7	15.0	17.5	14.0	15.9	12.7	N/A	N/A
PI14D	22.0	17.6	21.5	17.2	20.0	16.0	18.2	14.6	16.0	12.8
S0L2--G 1,2	22.0	17.6	21.3	17.0	20.0	16.0	18.2	14.6	N/A	N/A
PI14E	27.5	22.0	26.9	21.5	25.0	20.0	22.8	18.2	20.0	16.0
S0L2--M 1,2	27.5	22.0	26.7	21.4	25.0	20.0	22.8	18.2	N/A	N/A
PI14F	30.3	24.2	29.6	23.7	27.5	22.0	25.0	20.0	22.0	17.6
PI14G	33.0	26.4	32.3	25.8	30.0	24.0	27.5	22.0	24.0	19.2
S0L2--P 1,2	33.0	26.4	32.0	25.6	30.0	24.0	27.3	21.8	N/A	N/A
S1L2--J 1,2	38.5	30.8	37.5	30.0	35.0	28.0	31.9	25.5	N/A	N/A
PI14H	38.5	30.8	37.5	30.0	35.0	28.0	32.0	25.6	28.0	22.4
PI14J	45.0	36.0	44.0	35.2	40.0	32.0	36.5	29.2	32.0	25.6
S1L2--K	44.0	35.2	42.6	34.1	40.0	32.0	36.4	29.1	N/A	N/A
UCI224C	46.8	37.4	45.0	36.0	42.5	34.0	37.5	30.0	33.0	26.4
PI14K	46.8	37.4	45.0	36.0	42.5	34.0	37.5	30.0	32.9	26.3
S1L2--N 1, 2	49.5	39.6	48.0	38.4	45.0	36.0	41.0	32.8	N/A	N/A
UCI224D	55.0	44.0	53.0	42.4	50.0	40.0	45.0	36.0	40.0	32.0
S1L2--R 1, 2	55.0	44.0	53.3	42.6	50.0	40.0	45.5	36.4	N/A	N/A
UCI224E	63.0	50.4	61.0	48.8	60.0	48.0	53.0	42.4	47.0	37.6
S1L2--Y 1, 2	68.8	55.0	66.6	53.3	62.5	50.0	56.9	45.5	N/A	N/A
UCI224F	80.0	64.0	77.0	61.6	72.5	58.0	65.0	52.0	56.0	44.8
UCI224G	90.8	72.6	87.5	70.0	85.0	68.0	75.0	60.0	68.0	54.4
UCI274C	110.0	88.0	106.0	84.8	100.0	80.0	84.0	67.2	75.0	60.0
UCI274D	130.0	104.0	127.0	101.6	120.0	96.0	108.0	86.4	95.0	76.0
UCI274E	150.0	120.0	145.0	116.0	140.0	112.0	125.0	100.0	112.5	90.0
UCI274F	175.0	140.0	170.0	136.0	160.0	128.0	145.0	116.0	126.0	100.8
UCI274G	200.0	160.0	187.0	149.6	182.0	145.6	164.6	131.7	143.0	114.4
UCI274H	220.0	176.0	212.0	169.6	200.0	160.0	182.0	145.6	158.0	126.4

1. Available with single bearing only  
 2. Auxiliary winding option available (winding 711)  
 3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)



# 4 POLE Three Phase



Star 400V  
Parallel Star 200V  
Delta 230V

50Hz/1500rpm  
0.8 Power Factor

2 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCDI274J	260.0	208.0	250.0	200.0	230.0	184.0	210.0	168.0	180.0	144.0
UCDI274K	275.0	220.0	265.0	212.0	250.0	200.0	229.0	183.2	200.0	160.0
HCI444C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
S4L1S-C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
S4L1D-C 1	285.0	228.0	280.0	224.0	260.0	208.0	235.0	188.0	205.0	164.0
HCI444D	330.0	264.0	320.0	256.0	300.0	240.0	280.0	224.0	240.0	192.0
S4L1S-D	330.0	264.0	320.0	256.0	300.0	240.0	280.0	224.0	240.0	192.0
S4L1D-D 1	340.0	272.0	330.0	264.0	310.0	248.0	285.0	228.0	245.0	196.0
S4L1S-E	400.0	320.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
HCI444E	400.0	320.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
S4L1D-E 1	415.0	332.0	385.0	308.0	360.0	288.0	325.0	260.0	285.0	228.0
HCI444F	450.0	360.0	430.0	344.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1S-F	450.0	360.0	430.0	344.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1D-F 1	465.0	372.0	445.0	356.0	415.0	332.0	380.0	304.0	330.0	264.0
S4L1D-G 1	500.0	400.0	480.0	384.0	450.0	360.0	410.0	328.0	360.0	288.0
S5L1D-C 1	520.0	416.0	512.0	409.6	500.0	400.0	445.0	356.0	389.0	311.2
S5L1S-C	520.0	416.0	512.0	409.6	500.0	400.0	445.0	356.0	389.0	311.2
HCI544C	520.0	416.0	512.0	409.6	500.0	400.0	445.0	356.0	389.0	311.2
S5L1S-D 1	590.0	472.0	575.0	460.0	550.0	440.0	495.0	396.0	429.0	343.2
HCI544D	590.0	472.0	575.0	460.0	550.0	440.0	495.0	396.0	429.0	343.2
S5L1D-D 1	590.0	472.0	575.0	460.0	550.0	440.0	495.0	396.0	429.0	343.2
S5L1S-E	665.0	532.0	640.0	512.0	610.0	488.0	560.0	448.0	488.0	390.4
S5L1D-E 1	665.0	532.0	640.0	512.0	610.0	488.0	560.0	448.0	488.0	390.4
HCI544E	665.0	532.0	640.0	512.0	610.0	488.0	560.0	448.0	488.0	390.4
HCI544F	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1S-F	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1D-F 1	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1D-G 1	770.0	616.0	740.0	592.0	700.0	560.0	640.0	512.0	560.0	448.0
S5L1D-H 1	825.0	660.0	800.0	640.0	750.0	600.0	685.0	548.0	600.0	480.0
S6L1D-C 3	860.0	688.0	835.0	668.0	810.0	648.0	760.0	608.0	655.0	524.0
HCI634G	860.0	688.0	830.0	664.0	810.0	648.0	760.0	608.0	655.0	524.0
S6L1D-D 3	1010.0	808.0	980.0	784.0	940.0	752.0	860.0	688.0	765.0	612.0

1. Available with single bearing only

2. Auxiliary winding option available (winding 711)

3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)



# 4 POLE Three Phase



Star 400V  
 Parallel Star 200V  
 Delta 230V

50Hz/1500rpm  
 0.8 Power Factor

3 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI634H 3	1010.0	808.0	980.0	784.0	940.0	752.0	860.0	688.0	765.0	612.0
HCI634J 3	1110.0	888.0	1070.0	856.0	1030.0	824.0	927.0	741.6	825.0	660.0
S6L1D-E 3	1125.0	900.0	1100.0	880.0	1050.0	840.0	945.0	756.0	840.0	672.0
HCI634K 3	1230.0	984.0	1190.0	952.0	1135.0	908.0	1018.0	814.4	900.0	720.0
S6L1D-F 3	1230.0	984.0	1190.0	952.0	1150.0	920.0	1030.0	824.0	920.0	736.0
S6L1D-G 3	1345.0	1076.0	1315.0	1052.0	1260.0	1008.0	1135.0	908.0	1010.0	808.0
PI734A 3	1350.0	1080.0	1315.0	1052.0	1260.0	1008.0	1175.0	940.0	1085.0	868.0
S6L1D-H 3	1500.0	1200.0	1460.0	1168.0	1400.0	1120.0	1305.0	1044.0	1180.0	944.0
PI734B 3	1500.0	1200.0	1460.0	1168.0	1400.0	1120.0	1305.0	1044.0	1205.0	964.0
PI734C 3	1660.0	1328.0	1615.0	1292.0	1550.0	1240.0	1445.0	1156.0	1335.0	1068.0
S7L1D-C 3	1660.0	1328.0	1615.0	1292.0	1550.0	1240.0	1445.0	1156.0	1335.0	1068.0
PI734D 3	1770.0	1416.0	1720.0	1376.0	1650.0	1320.0	1540.0	1232.0	1420.0	1136.0
S7L1D-D 3	1770.0	1416.0	1720.0	1376.0	1650.0	1320.0	1540.0	1232.0	1420.0	1136.0
S7L1D-E 3	1873.0	1498.4	1820.0	1456.0	1750.0	1400.0	1625.0	1300.0	1505.0	1204.0
PI734E 3	2035.0	1628.0	1980.0	1584.0	1900.0	1520.0	1770.0	1416.0	1635.0	1308.0
S7L1D-F 3	2035.0	1628.0	1980.0	1584.0	1900.0	1520.0	1770.0	1416.0	1635.0	1308.0
PI734F 3	2250.0	1800.0	2170.0	1736.0	2080.0	1664.0	1935.0	1548.0	1790.0	1432.0
S7L1D-G 3	2250.0	1800.0	2170.0	1736.0	2080.0	1664.0	1935.0	1548.0	1790.0	1432.0
PI734G 3	2360.0	1888.0	2295.0	1836.0	2200.0	1760.0	2050.0	1640.0	1895.0	1516.0
S7L1D-H 3	2400.0	1920.0	2340.0	1872.0	2250.0	1800.0	2090.0	1672.0	1930.0	1544.0
PI734H 3	2600.0	2080.0	2500.0	2000.0	2325.0	1860.0	2150.0	1720.0	1900.0	1520.0
P80 LVSI804R 3	2650.0	2120.0	2575.0	2060.0	2410.0	1928.0	2210.0	1768.0	1930.0	1544.0
S7L1D-J 3	2750.0	2200.0	2600.0	2080.0	2500.0	2000.0	2250.0	1800.0	2000.0	1600.0
P80 LVSI804S 3	3070.0	2456.0	2985.0	2388.0	2790.0	2232.0	2560.0	2048.0	2240.0	1792.0
P80 LVSI804T 3	3350.0	2680.0	3260.0	2608.0	3050.0	2440.0	2800.0	2240.0	2450.0	1960.0
P80 LVSI804W 3,4	3910.0	3128.0	3800.0	3040.0	3555.0	2844.0	3322.0	2657.6	2887.0	2309.6
P80 LVSI804X 3,4	4080.0	3264.0	4180.0	3344.0	3911.0	3128.8	3655.0	2924.0	3177.0	2541.6

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 415V  
 Parallel Star 208V  
 Delta 240V

50Hz/1500rpm  
 0.8 Power Factor

1 of 3

Winding 311/312/12	Model	TEMPERATURE RISE									
		Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
		kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
	S0L1-D 1	8.3	6.6	8.0	6.4	7.5	6.0	6.8	5.4	N/A	N/A
	PI044D	8.3	6.6	8.1	6.5	7.5	6.0	6.8	5.4	6.0	4.8
	S0L1-H 1	11.0	8.8	10.7	8.6	10.0	8.0	9.1	7.3	N/A	N/A
	PI044E	11.0	8.8	10.8	8.6	10.0	8.0	9.1	7.3	8.0	6.4
	S0L1-L 1	13.8	11.0	13.3	10.6	12.5	10.0	11.4	9.1	N/A	N/A
	PI044F	13.8	11.0	13.5	10.8	12.5	10.0	11.4	9.1	10.0	8.0
	S0L1-P 1	16.5	13.2	16.0	12.8	15.0	12.0	13.7	11.0	N/A	N/A
	PI044G	16.5	13.2	16.2	13.0	15.0	12.0	13.7	11.0	12.0	9.6
	S0L2-F 1, 2	19.3	15.4	18.7	15.0	17.5	14.0	15.9	12.7	N/A	N/A
	PI044H	19.3	15.4	18.9	15.1	17.5	14.0	16.0	12.8	14.0	11.2
	S0L2-G 1, 2	22.0	17.6	21.3	17.0	20.0	16.0	18.2	14.6	N/A	N/A
	PI144D	22.0	17.6	21.5	17.2	20.0	16.0	18.2	14.6	16.0	12.8
	S0L2-M 1, 2	27.5	22.0	26.7	21.4	25.0	20.0	22.8	18.2	N/A	N/A
	PI144E	27.5	22.0	26.9	21.5	25.0	20.0	22.8	18.2	20.0	16.0
	PI144F	30.3	24.2	29.6	23.7	27.5	22.0	25.0	20.0	22.0	17.6
	S0L2-P 1, 2	33.0	26.4	32.0	25.6	30.0	24.0	27.3	21.8	N/A	N/A
	PI144G	33.0	26.4	32.3	25.8	30.0	24.0	27.5	22.0	24.0	19.2
	PI144H	38.5	30.8	37.5	30.0	35.0	28.0	32.0	25.6	28.0	22.4
	S1L2-J 1, 2	38.5	30.8	37.5	30.0	35.0	28.0	31.9	25.5	N/A	N/A
	S1L2-K 1, 2	44.0	35.2	42.6	34.1	40.0	32.0	36.4	29.1	N/A	N/A
	PI14J	45.0	36.0	44.0	35.2	40.0	32.0	36.5	29.2	32.0	25.6
	UCI224C	46.8	37.4	45.0	36.0	42.5	34.0	37.5	30.0	33.0	26.4
	PI14K	46.8	37.4	45.0	36.0	42.5	34.0	37.5	30.0	32.9	26.3
	S1L2-N 1, 2	49.5	39.6	48.0	38.4	45.0	36.0	41.0	32.8	N/A	N/A
	UCI224D	55.0	44.0	53.0	42.4	50.0	40.0	45.0	36.0	40.0	32.0
	S1L2-R 1, 2	55.0	44.0	53.3	42.6	50.0	40.0	45.5	36.4	N/A	N/A
	UCI224E	63.0	50.4	61.0	48.8	60.0	48.0	53.0	42.4	47.0	37.6
	S1L2-Y 1, 2	68.8	55.0	66.6	53.3	62.5	50.0	56.9	45.5	N/A	N/A
	UCI224F	80.0	64.0	77.0	61.6	72.5	58.0	65.0	52.0	56.0	44.8
	UCI224G	90.8	72.6	87.5	70.0	85.0	68.0	75.0	60.0	68.0	54.4
	UCI274C	110.0	88.0	106.0	84.8	100.0	80.0	84.0	67.2	80.0	64.0
	UCI274D	125.0	100.0	121.0	96.8	114.0	91.2	100.0	80.0	90.0	72.0
	UCI274E	150.0	120.0	145.0	116.0	140.0	112.0	125.0	100.0	112.5	90.0
	UCI274F	175.0	140.0	170.0	136.0	160.0	128.0	145.0	116.0	128.0	102.4
	UCI274G	200.0	160.0	187.0	149.6	182.0	145.6	164.6	131.7	144.0	115.2

1. Available with single bearing only

2. Auxiliary winding option available (winding 711)

3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)



# 4 POLE Three Phase



Star 415V  
 Parallel Star 208V  
 Delta 240V

**50Hz/1500rpm**  
**0.8 Power Factor**

**2 of 3**

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274H	220.0	176.0	212.0	169.6	200.0	160.0	182.0	145.6	160.0	128.0
UCDI274J	260.0	208.0	250.0	200.0	230.0	184.0	210.0	168.0	180.0	144.0
UCDI274K	275.0	220.0	265.0	212.0	250.0	200.0	229.0	183.2	200.0	160.0
HCI444C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
S4L1S-C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
S4L1D-C 1	285.0	228.0	280.0	224.0	260.0	208.0	235.0	188.0	205.0	164.0
HCI444D	330.0	264.0	320.0	256.0	300.0	240.0	280.0	224.0	240.0	192.0
S4L1S-D	330.0	264.0	330.0	264.0	300.0	240.0	280.0	224.0	240.0	192.0
S4L1D-D 1	340.0	272.0	330.0	264.0	310.0	248.0	285.0	228.0	245.0	196.0
HCI444E	380.0	304.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
S4L1S-E	380.0	304.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
S4L1D-E 1	400.0	320.0	385.0	308.0	360.0	288.0	325.0	260.0	285.0	228.0
HCI444F	440.0	352.0	430.0	344.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1S-F	440.0	352.0	430.0	344.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1D-F 1	455.0	364.0	445.0	356.0	415.0	332.0	380.0	304.0	330.0	264.0
S4L1D-G	500.0	400.0	480.0	384.0	450.0	360.0	410.0	328.0	360.0	288.0
HCI544C	500.0	400.0	478.0	382.4	455.0	364.0	400.0	320.0	350.0	280.0
S5L1S-C	500.0	400.0	478.0	382.4	455.0	364.0	400.0	320.0	350.0	280.0
S5L1D-C 1	500.0	400.0	478.0	382.4	455.0	364.0	400.0	320.0	350.0	280.0
HCI544D	550.0	440.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
S5L1S-D	550.0	440.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
S5L1D-D 1	550.0	440.0	515.0	440.0	500.0	400.0	450.0	360.0	390.0	312.0
HCI544E	660.0	528.0	636.0	508.8	600.0	480.0	550.0	440.0	480.0	384.0
S5L1S-E	660.0	528.0	636.0	508.8	600.0	480.0	550.0	440.0	480.0	384.0
S5L1D-E 1	660.0	528.0	636.0	528.0	600.0	480.0	550.0	440.0	480.0	384.0
HCI544F	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1S-F	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1D-F 1	738.0	590.4	710.0	572.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1D-G 1	770.0	616.0	740.0	592.0	700.0	560.0	640.0	512.0	560.0	448.0
S5L1D-H 1	825.0	660.0	800.0	640.0	750.0	600.0	685.0	548.0	600.0	480.0
HCI634G	850.0	680.0	825.0	660.0	800.0	640.0	750.0	600.0	650.0	520.0
S6L1D-C 3	850.0	680.0	835.0	668.0	810.0	648.0	760.0	608.0	655.0	524.0
HCI634H	1000.0	800.0	960.0	768.0	910.0	728.0	830.0	664.0	740.0	592.0
S6L1D-D 3	1010.0	808.0	980.0	784.0	940.0	752.0	860.0	688.0	765.0	612.0
HCI634J	1110.0	888.0	1070.0	856.0	1030.0	824.0	927.0	741.6	825.0	660.0
S6L1D-E 3	1125.0	900.0	1100.0	880.0	1050.0	840.0	945.0	756.0	840.0	672.0

1. Available with single bearing only  
 2. Auxiliary winding option available (winding 711)  
 3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)



# 4 POLE Three Phase



Star 415V  
 Parallel Star 208V  
 Delta 240V

50Hz/1500rpm  
 0.8 Power Factor

3 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI634K 3	1220.0	976.0	1180.0	944.0	1110.0	888.0	1000.0	800.0	885.0	708.0
S6L1D-F 3	1230.0	984.0	1190.0	952.0	1150.0	920.0	1030.0	824.0	920.0	736.0
S6L1D-G 3	1350.0	1080.0	1315.0	1052.0	1260.0	1008.0	1135.0	908.0	1010.0	808.0
PI734A 3	1350.0	1080.0	1315.0	1052.0	1260.0	1008.0	1175.0	940.0	1085.0	868.0
S6L1D-H 3	1500.0	1200.0	1460.0	1168.0	1400.0	1120.0	1305.0	1044.0	1205.0	964.0
PI734B 3	1500.0	1200.0	1460.0	1168.0	1400.0	1120.0	1305.0	1044.0	1205.0	964.0
S7L1D-C 3	1660.0	1328.0	1615.0	1292.0	1550.0	1240.0	1445.0	1156.0	1335.0	1068.0
PI734C 3	1660.0	1328.0	1615.0	1292.0	1550.0	1240.0	1445.0	1156.0	1335.0	1068.0
S7L1D-D 3	1770.0	1416.0	1720.0	1376.0	1650.0	1320.0	1540.0	1232.0	1420.0	1136.0
PI734D 3	1770.0	1416.0	1720.0	1376.0	1650.0	1320.0	1540.0	1232.0	1420.0	1136.0
S7L1D-E 3	1873.0	1498.4	1820.0	1456.0	1750.0	1400.0	1630.0	1304.0	1505.0	1204.0
S7L1D-F 3	2035.0	1628.0	1980.0	1584.0	1900.0	1520.0	1770.0	1416.0	1635.0	1308.0
PI734E 3	2035.0	1628.0	1980.0	1584.0	1900.0	1520.0	1770.0	1416.0	1635.0	1308.0
PI734F 3	2250.0	1800.0	2170.0	1736.0	2080.0	1664.0	1935.0	1548.0	1790.0	1432.0
S7L1D-G 3	2250.0	1800.0	2170.0	1736.0	2080.0	1664.0	1935.0	1548.0	1790.0	1432.0
PI734G 3	2360.0	1888.0	2295.0	1836.0	2200.0	1760.0	2050.0	1640.0	1895.0	1516.0
S7L1D-H 3	2400.0	1920.0	2340.0	1872.0	2250.0	1800.0	2090.0	1672.0	1930.0	1544.0
PI734H 3	2600.0	2080.0	2500.0	2000.0	2325.0	1860.0	2150.0	1720.0	1900.0	1520.0
P80 LVSI804R 3	2650.0	2120.0	2575.0	2060.0	2410.0	1928.0	2210.0	1768.0	1930.0	1544.0
S7L1D-J 3	2680.0	2144.0	2600.0	2080.0	2500.0	2000.0	2250.0	1800.0	2000.0	1600.0
P80 LVSI804S 3	3070.0	2456.0	2985.0	2388.0	2790.0	2232.0	2560.0	2048.0	2240.0	1792.0
P80 LVSI804T 3	3350.0	2680.0	3260.0	2608.0	3050.0	2440.0	2800.0	2240.0	2450.0	1960.0
P80 LVSI804W 3,4	3910.0	3128.0	3800.0	3040.0	3555.0	2844.0	3322.0	2657.6	2887.0	2309.6
P80 LVSI804X 3,4	4300.0	3440.0	4180.0	3344.0	3911.0	3128.8	3655.0	2924.0	3177.0	2541.6

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing





# 4 POLE Three Phase



Star 440V  
Parallel Star 220V  
Delta 254V

50Hz/1500rpm  
0.8 Power Factor

1 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	7.8	6.2	7.7	6.2	7.1	5.7	6.5	5.2	5.7	4.6
PI044E	10.5	8.4	10.3	8.2	9.5	7.6	8.6	6.9	7.6	6.1
PI044F	13.1	10.5	12.8	10.2	11.9	9.5	10.8	8.6	9.5	7.6
PI044G	15.7	12.6	15.4	12.3	14.3	11.4	13.0	10.4	11.4	9.1
PI044H	18.3	14.6	18.0	14.4	16.6	13.3	15.2	12.2	13.3	10.6
PI144D	20.9	16.7	20.4	16.3	19.0	15.2	17.3	13.8	15.2	12.2
PI144E	26.1	20.9	25.6	20.5	23.8	19.0	21.6	17.3	19.0	15.2
PI144F	28.7	23.0	28.1	22.5	26.1	20.9	23.8	19.0	20.9	16.7
PI144G	31.4	25.1	30.6	24.5	28.5	22.8	26.1	20.9	22.8	18.2
UCI224C	33.0	26.4	31.7	25.4	30.0	24.0	27.0	21.6	24.0	19.2
PI144H	36.6	29.3	35.6	28.5	33.3	26.6	30.4	24.3	26.6	21.3
UCI224D	41.2	33.0	39.1	31.3	37.5	30.0	33.6	26.9	30.5	24.4
PI144J	42.8	34.2	41.8	33.4	38.0	30.4	34.7	27.8	30.4	24.3
PI144K	44.5	35.6	42.8	34.2	40.4	32.3	35.6	28.5	31.3	25.0
UCI224E	47.3	37.8	45.8	36.6	45.0	36.0	40.3	32.2	35.7	28.6
UCI224F	60.5	48.4	58.0	46.4	55.0	44.0	48.7	39.0	42.0	33.6
UCI224G	80.1	64.1	76.9	61.5	75.0	60.0	67.4	53.9	59.3	47.4
HCI444C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
S4L1S-C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
S4L1D-C 1	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
HCI444D	320.0	256.0	310.0	248.0	290.0	232.0	270.0	216.0	230.0	184.0
S4L1S-D	320.0	256.0	310.0	248.0	290.0	232.0	270.0	216.0	230.0	184.0
S4L1D-D 1	320.0	256.0	310.0	248.0	290.0	232.0	270.0	216.0	230.0	184.0
HCI444E	380.0	304.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
S4L1S-E	380.0	304.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
S4L1D-E 1	380.0	304.0	370.0	296.0	350.0	280.0	320.0	256.0	275.0	220.0
HCI444F	440.0	352.0	430.0	344.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1S-F	440.0	352.0	430.0	344.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1D-F 1	440.0	352.0	430.0	344.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1D-G	475.0	380.0	455.0	364.0	430.0	344.0	390.0	312.0	345.0	276.0
HCI544C	495.0	396.0	478.0	382.4	450.0	360.0	400.0	320.0	350.0	280.0
S5L1S-C	495.0	396.0	478.0	382.4	450.0	360.0	400.0	320.0	350.0	280.0

1. Available with single bearing only

2. Auxiliary winding option available (winding 711)

3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)



# 4 POLE Three Phase



Star 440V  
 Parallel Star 220V  
 Delta 254V

50Hz/1500rpm  
 0.8 Power Factor

2 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S5L1D-C 1	495.0	396.0	478.0	382.4	450.0	360.0	400.0	320.0	350.0	280.0
HCI544D	530.0	424.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
S5L1S-D	530.0	424.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
S5L1D-D 1	530.0	424.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
HCI544E	660.0	528.0	636.0	508.8	600.0	480.0	550.0	440.0	480.0	384.0
S5L1S-E	660.0	528.0	636.0	508.8	600.0	480.0	550.0	440.0	480.0	384.0
S5L1D-E 1	660.0	528.0	636.0	508.8	600.0	480.0	550.0	440.0	480.0	384.0
HCI544F	715.0	572.0	690.0	552.0	650.0	520.0	600.0	480.0	520.0	416.0
S5L1S-F	715.0	572.0	690.0	552.0	650.0	520.0	600.0	480.0	520.0	416.0
S5L1D-F 1	715.0	572.0	690.0	552.0	650.0	520.0	600.0	480.0	520.0	416.0
S5L1D-G 1	750.0	600.0	720.0	576.0	680.0	544.0	625.0	500.0	544.0	435.2
S5L1D-H 1	780.0	624.0	755.0	604.0	710.0	568.0	650.0	520.0	568.0	454.4
HCI634G 3	850.0	680.0	820.0	656.0	800.0	640.0	750.0	600.0	650.0	520.0
S6L1D-C 3	850.0	680.0	825.0	660.0	800.0	640.0	750.0	600.0	650.0	520.0
HCI634H 3	960.0	768.0	920.0	736.0	875.0	700.0	800.0	640.0	738.0	590.4
S6L1D-D 3	960.0	768.0	920.0	736.0	875.0	700.0	800.0	640.0	700.0	560.0
S6L1D-E 3	1100.0	880.0	1060.0	848.0	1010.0	808.0	900.0	720.0	800.0	640.0
HCI634J 3	1100.0	880.0	1060.0	848.0	1010.0	808.0	900.0	720.0	800.0	640.0
HCI634K 3	1220.0	976.0	1180.0	944.0	1110.0	888.0	1000.0	800.0	885.0	708.0
S6L1D-F 3	1220.0	976.0	1180.0	944.0	1110.0	888.0	1000.0	800.0	885.0	708.0
S6L1D-G 3	1320.0	1056.0	1290.0	1032.0	1235.0	988.0	1100.0	888.0	990.0	792.0
PI734A 3	1325.0	1060.0	1290.0	1032.0	1235.0	988.0	1150.0	920.0	1065.0	852.0
S6L1D-H 3	1435.0	1148.0	1400.0	1120.0	1340.0	1072.0	1250.0	1000.0	1140.0	912.0
PI734B 3	1470.0	1176.0	1430.0	1144.0	1375.0	1100.0	1280.0	1024.0	1180.0	944.0
S7L1D-C 3	1630.0	1304.0	1590.0	1272.0	1520.0	1216.0	1415.0	1132.0	1310.0	1048.0
PI734C 3	1630.0	1304.0	1590.0	1272.0	1520.0	1216.0	1415.0	1132.0	1310.0	1048.0
S7L1D-D 3	1735.0	1388.0	1685.0	1348.0	1620.0	1296.0	1505.0	1204.0	1400.0	1120.0
PI734D 3	1735.0	1388.0	1685.0	1348.0	1620.0	1296.0	1505.0	1204.0	1400.0	1120.0
S7L1D-E 3	1840.0	1472.0	1789.0	1431.2	1720.0	1376.0	1600.0	1280.0	1480.0	1184.0
S7L1D-F 3	1995.0	1596.0	1940.0	1552.0	1865.0	1492.0	1735.0	1388.0	1615.0	1292.0
PI734E 3	1995.0	1596.0	1940.0	1552.0	1865.0	1492.0	1735.0	1388.0	1615.0	1292.0
S7L1D-G 3	2185.0	1748.0	2125.0	1700.0	2040.0	1632.0	1900.0	1520.0	1755.0	1404.0

1. Available with single bearing only  
 2. Auxiliary winding option available (winding 711)  
 3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)



# 4 POLE Three Phase



Star 440V  
 Parallel Star 220V  
 Delta 254V

50Hz/1500rpm  
 0.8 Power Factor

3 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI734F 3	2185.0	1748.0	2125.0	1700.0	2040.0	1632.0	1900.0	1520.0	1755.0	1404.0
S7L1D-H 3	2310.0	1848.0	2250.0	1800.0	2160.0	1728.0	2005.0	1604.0	1855.0	1484.0
PI734G 3	2310.0	1848.0	2250.0	1800.0	2160.0	1728.0	2005.0	1604.0	1855.0	1484.0
S7L1D-J 3	2490.0	1992.0	2420.0	1936.0	2265.0	1812.0	2075.0	1660.0	1880.0	1504.0
P80 LVSI804R 3	2490.0	1992.0	2420.0	1936.0	2265.0	1812.0	2075.0	1660.0	1815.0	1452.0
PI734H 3	2600.0	2080.0	2500.0	2000.0	2325.0	1860.0	2150.0	1720.0	1900.0	1520.0
P80 LVSI804S 3	2885.0	2308.0	2805.0	2244.0	2620.0	2096.0	2405.0	1924.0	2105.0	1684.0
P80 LVSI804T 3	3150.0	2520.0	3065.0	2452.0	2865.0	2292.0	2630.0	2104.0	2300.0	1840.0
P80 LVSI804W 3,4	3675.0	2940.0	3570.0	2856.0	3340.0	2672.0	3122.0	2497.6	2715.0	2172.0
P80 LVSI804X 3,4	4040.0	3232.0	3970.0	3176.0	3675.0	2940.0	3435.0	2748.0	2980.0	2384.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 660V - 690V  
 Parallel Star 330V - 345V  
 Delta 380V - 400V

50Hz/1500rpm  
 0.8 Power Factor

1 of 2

Winding 25/26/65	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI224C	41.0	32.8	39.5	31.6	37.5	30.0	34.5	27.6	30.0	24.0
UCI224D	55.0	44.0	53.0	42.4	50.0	40.0	45.0	36.0	40.0	32.0
UCI224F	71.5	57.2	69.0	55.2	65.0	52.0	60.0	48.0	52.0	41.6
UCI224G	85.0	68.0	82.0	65.6	80.0	64.0	73.5	58.8	64.0	51.2
UCI274C	110.0	88.0	106.0	84.8	100.0	80.0	84.0	67.2	75.0	60.0
UCI274D	125.0	100.0	121.0	96.8	114.0	91.2	100.0	80.0	90.0	72.0
UCI274E	150.0	120.0	145.0	116.0	140.0	112.0	125.0	100.0	112.5	90.0
UCI274F	175.0	140.0	170.0	136.0	160.0	128.0	145.0	116.0	126.0	100.8
UCI274G	189.0	151.2	182.0	145.6	175.0	140.0	160.0	128.0	138.8	111.0
UCI274H	220.0	176.0	212.0	169.6	200.0	160.0	182.0	145.6	158.0	126.4
HCI444C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
S4L1S-C	275.0	220.0	270.0	216.0	250.0	200.0	230.0	184.0	200.0	160.0
HCI444D	330.0	264.0	320.0	256.0	300.0	240.0	280.0	224.0	240.0	192.0
S4L1S-D	330.0	264.0	320.0	256.0	300.0	240.0	280.0	224.0	240.0	192.0
HCI444E	370.0	296.0	355.0	284.0	340.0	272.0	310.0	248.0	265.0	212.0
S4L1S-E	370.0	296.0	355.0	284.0	340.0	272.0	310.0	248.0	265.0	212.0
HCI444F	440.0	352.0	430.0	344.0	400.0	320.0	370.0	296.0	320.0	256.0
S4L1S-F	440.0	352.0	430.0	344.0	400.0	320.0	370.0	296.0	320.0	256.0
HCI544C	468.0	374.4	450.0	360.0	425.0	340.0	375.0	300.0	325.0	260.0
S5L1S-C	468.0	374.4	450.0	360.0	425.0	340.0	375.0	300.0	325.0	260.0
HCI544D	530.0	424.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
S5L1S-D	530.0	424.0	515.0	412.0	500.0	400.0	450.0	360.0	390.0	312.0
HCI544E	610.0	488.0	590.0	472.0	560.0	448.0	510.0	408.0	445.0	356.0
S5L1S-E	610.0	488.0	590.0	472.0	560.0	448.0	510.0	408.0	445.0	356.0
HCI544F	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S5L1S-F	738.0	590.4	710.0	568.0	670.0	536.0	620.0	496.0	540.0	432.0
S6L1D-C 3,5	850.0	680.0	820.0	656.0	800.0	640.0	750.0	600.0	650.0	520.0
HCI634G 3	850.0	680.0	820.0	656.0	800.0	640.0	750.0	600.0	650.0	520.0
S6L1D-D 3,5	990.0	792.0	950.0	760.0	900.0	720.0	820.0	656.0	730.0	584.0
HCI634H 3	990.0	792.0	950.0	760.0	900.0	720.0	820.0	656.0	730.0	584.0
S6L1D-E 3,5	1100.0	880.0	1060.0	848.0	1000.0	800.0	900.0	720.0	800.0	640.0
HCI634J 3	1100.0	880.0	1060.0	848.0	1000.0	800.0	900.0	720.0	800.0	640.0

3. Star connection only

4. Only available in 2 bearing

5. 660V ratings may differ - refer technical data sheet



# 4 POLE Three Phase



**Star** 660V - 690V  
**Parallel Star** 330V - 345V  
**Delta** 380V - 400V

**50Hz/1500rpm**  
**0.8 Power Factor**

**2 of 2**

Winding 25/26/65	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>S6L1D-F</b> 3,5	1150.0	920.0	1115.0	892.0	<b>1050.0</b>	<b>840.0</b>	945.0	756.0	820.0	656.0
<b>HCI634K</b> 3	1150.0	920.0	1115.0	892.0	<b>1050.0</b>	<b>840.0</b>	945.0	756.0	820.0	656.0
<b>S6L1D-G</b> 3,5	1350.0	1080.0	1315.0	1052.0	<b>1260.0</b>	<b>1008.0</b>	1175.0	940.0	1037.0	829.6
<b>PI734A</b> 3	1350.0	1080.0	1315.0	1052.0	<b>1260.0</b>	<b>1008.0</b>	1175.0	940.0	1085.0	868.0
<b>S6L1D-H</b> 3,5	1500.0	1200.0	1460.0	1168.0	<b>1388.0</b>	<b>1110.4</b>	1250.0	1000.0	1120.0	896.0
<b>PI734B</b> 3	1500.0	1200.0	1460.0	1168.0	<b>1400.0</b>	<b>1120.0</b>	1305.0	1044.0	1205.0	964.0
<b>PI734C</b> 3	1620.0	1296.0	1575.0	1260.0	<b>1510.0</b>	<b>1208.0</b>	1405.0	1124.0	1300.0	1040.0
<b>S7L1D-C</b> 3	1620.0	1296.0	1575.0	1260.0	<b>1510.0</b>	<b>1208.0</b>	1405.0	1124.0	1300.0	1040.0
<b>PI734D</b> 3	1770.0	1416.0	1720.0	1376.0	<b>1650.0</b>	<b>1320.0</b>	1535.0	1228.0	1420.0	1136.0
<b>S7L1D-D</b> 3	1770.0	1416.0	1720.0	1376.0	<b>1650.0</b>	<b>1320.0</b>	1535.0	1228.0	1420.0	1136.0
<b>S7L1D-E</b> 3	1840.0	1472.0	1785.0	1428.0	<b>1715.0</b>	<b>1372.0</b>	1600.0	1280.0	1475.0	1180.0
<b>PI734E</b> 3	1895.0	1516.0	1845.0	1476.0	<b>1770.0</b>	<b>1416.0</b>	1645.0	1316.0	1520.0	1216.0
<b>S7L1D-F</b> 3	1990.0	1592.0	1940.0	1552.0	<b>1860.0</b>	<b>1488.0</b>	1730.0	1384.0	1600.0	1280.0
<b>PI734F</b> 3	2230.0	1784.0	2170.0	1736.0	<b>2080.0</b>	<b>1664.0</b>	1935.0	1548.0	1790.0	1432.0
<b>S7L1D-G</b> 3	2230.0	1784.0	2170.0	1736.0	<b>2080.0</b>	<b>1664.0</b>	1935.0	1548.0	1790.0	1432.0
<b>PI734G</b> 3	2295.0	1836.0	2200.0	1760.0	<b>2150.0</b>	<b>1720.0</b>	2000.0	1600.0	1835.0	1468.0
<b>S7L1D-H</b> 3	2345.0	1876.0	2280.0	1824.0	<b>2200.0</b>	<b>1760.0</b>	2050.0	1640.0	1885.0	1508.0
<b>P80 LVSI804T</b> 3	3110.0	2488.0	3025.0	2420.0	<b>2830.0</b>	<b>2264.0</b>	2560.0	2048.0	2170.0	1736.0
<b>P80 LVSI804W</b> 3,4	3650.0	2920.0	3550.0	2840.0	<b>3320.0</b>	<b>2656.0</b>	3020.0	2416.0	2560.0	2048.0
<b>P80 LVSI804Y</b> 3,4	4180.0	3344.0	4065.0	3252.0	<b>3800.0</b>	<b>3040.0</b>	3535.0	2828.0	3080.0	2464.0

3. Star connection only

4. Only available in 2 bearing

5. 660V ratings may differ - refer technical data sheet



# 4 POLE Three Phase



Star 380V  
Parallel Star 190V  
Delta 220V

60Hz/1800rpm  
0.8 Power Factor

1 of 3

Winding 13/14	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	10.2	8.2	9.9	7.9	9.4	7.5	8.5	6.8	7.5	6.0
S0L1-D 1	10.2	8.2	9.9	7.9	9.4	7.5	8.5	6.8	7.5	6.0
PI044E	13.6	10.9	13.1	10.5	12.5	10.0	11.3	9.0	10.0	8.0
S0L1-H 1	13.6	10.9	13.1	10.5	12.5	10.0	11.3	9.0	10.0	8.0
PI044F	16.4	13.1	15.8	12.6	15.0	12.0	13.5	10.8	12.0	9.6
S0L1-L 1	16.4	13.1	15.8	12.6	15.0	12.0	13.5	10.8	12.0	9.6
PI044G	20.5	16.4	19.7	15.8	18.8	15.0	16.9	13.5	15.0	12.0
S0L1-P 1	20.5	16.4	19.7	15.8	18.8	15.0	16.9	13.5	15.0	12.0
PI044H	22.9	18.3	22.1	17.7	21.0	16.8	18.9	15.1	16.8	13.4
S0L2-F 1	22.9	18.3	22.1	17.7	21.0	16.8	18.9	15.1	16.8	13.4
PI144D	27.3	21.8	26.3	21.0	25.0	20.0	22.5	18.0	20.0	16.0
S0L2-G 1	27.3	21.8	26.3	21.0	25.0	20.0	22.5	18.0	20.0	16.0
PI144E	32.7	26.2	31.5	25.2	30.0	24.0	27.0	21.6	24.0	19.2
S0L2-M 1	32.7	26.2	31.5	25.2	30.0	24.0	27.0	21.6	24.0	19.2
PI144F	36.0	28.8	34.7	27.8	33.0	26.4	29.7	23.8	26.4	21.1
PI144G	40.9	32.7	39.4	31.5	37.5	30.0	33.8	27.0	30.0	24.0
S0L2-P 1	40.9	32.7	39.4	31.5	37.5	30.0	33.8	27.0	30.0	24.0
PI144H	47.7	38.2	46.0	36.8	43.8	35.0	39.4	31.5	35.0	28.0
S1L2-J 1	47.7	38.2	46.0	36.8	43.8	35.0	39.4	31.5	35.0	28.0
PI144J	51.8	41.4	49.9	39.9	47.5	38.0	42.8	34.2	38.0	30.4
S1L2-K 1	51.8	41.4	49.9	39.9	47.5	38.0	42.8	34.2	38.0	30.4
PI144K	60.0	48.0	57.8	46.2	55.0	44.0	49.5	39.6	44.0	35.2
S1L2-N 1	60.0	48.0	57.8	46.2	55.0	44.0	49.5	39.6	44.0	35.2
UCI224C	60.0	48.0	58.1	46.5	55.0	44.0	48.0	38.4	42.0	33.6
UCI224D	66.3	53.0	65.0	52.0	62.5	50.0	56.0	44.8	48.5	38.8
S1L2-R 1	66.3	53.0	65.0	52.0	62.5	50.0	56.0	44.8	48.5	38.8
UCI224E	75.0	60.0	73.8	59.0	70.0	56.0	65.0	52.0	55.0	44.0
S1L2-Y 1	75.0	60.0	73.8	59.0	70.0	56.0	65.0	52.0	55.0	44.0
UCI224F	92.0	73.6	89.4	71.5	85.0	68.0	75.0	60.0	65.0	52.0
UCI224G	106.3	85.0	102.5	82.0	100.0	80.0	93.8	75.0	81.3	65.0
UCI274C	132.0	105.6	127.0	101.6	120.0	96.0	110.0	88.0	95.0	76.0
UCI274D	142.5	114.0	137.5	110.0	131.3	105.0	120.0	96.0	100.0	80.0

1. Available with single bearing only
2. Auxiliary winding option available
3. Star connection only
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 380V  
Parallel Star 190V  
Delta 220V

60Hz/1800rpm  
0.8 Power Factor

2 of 3

Winding 13/14	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274E	175.0	140.0	170.0	136.0	160.0	128.0	140.0	112.0	120.0	96.0
UCI274F	190.0	152.0	186.0	148.8	180.0	144.0	160.0	128.0	137.5	110.0
UCI274G	212.5	170.0	207.5	166.0	200.0	160.0	187.5	150.0	162.5	130.0
UCI274H	256.3	205.0	250.0	200.0	237.5	190.0	218.8	175.0	187.5	150.0
UCDI274J	325.0	260.0	319.0	255.2	300.0	240.0	275.0	220.0	240.0	192.0
HCI444C	330.0	264.0	320.0	256.0	300.0	240.0	275.0	220.0	240.0	192.0
S4L1S-C	330.0	264.0	320.0	256.0	300.0	240.0	275.0	220.0	240.0	192.0
HCI444D	385.0	308.0	375.0	300.0	350.0	280.0	315.0	252.0	270.0	216.0
S4L1S-D	385.0	308.0	375.0	300.0	350.0	280.0	315.0	252.0	270.0	216.0
HCI544C	540.0	432.0	520.0	416.0	500.0	400.0	460.0	368.0	400.0	320.0
S5L1S-C	540.0	432.0	520.0	416.0	500.0	400.0	460.0	368.0	400.0	320.0
HCI444F	550.0	440.0	535.0	428.0	500.0	400.0	465.0	372.0	400.0	320.0
S4L1S-F	550.0	440.0	535.0	428.0	500.0	400.0	465.0	372.0	400.0	320.0
S5L1S-D	673.0	538.4	655.0	524.0	625.0	500.0	563.0	450.4	495.0	396.0
HCI544D	673.0	538.4	655.0	524.0	625.0	500.0	563.0	450.4	495.0	396.0
HCI544E	730.0	584.0	710.0	568.0	675.0	540.0	620.0	496.0	535.0	428.0
S5L1S-E	730.0	584.0	710.0	568.0	675.0	540.0	620.0	496.0	535.0	428.0
S5L1S-F	906.0	724.8	875.0	700.0	825.0	660.0	750.0	600.0	660.0	528.0
HCI544F	906.0	724.8	875.0	700.0	825.0	660.0	750.0	600.0	660.0	528.0
S6L1D-C	950.0	760.0	913.0	730.4	875.0	700.0	813.0	650.4	710.0	568.0
HCI634G 3	950.0	760.0	913.0	730.4	875.0	700.0	813.0	650.4	710.0	568.0
HCI634H 3	1080.0	864.0	1050.0	840.0	1000.0	800.0	910.0	728.0	790.0	632.0
S6L1D-D	1080.0	864.0	1050.0	840.0	1000.0	800.0	910.0	728.0	790.0	632.0
S6L1D-E	1325.0	1060.0	1275.0	1020.0	1225.0	980.0	1125.0	900.0	981.0	784.8
HCI634J 3	1350.0	1080.0	1300.0	1040.0	1250.0	1000.0	1150.0	920.0	1000.0	800.0
HCI634K 3	1500.0	1200.0	1455.0	1164.0	1375.0	1100.0	1260.0	1008.0	1090.0	872.0
S6L1D-F	1500.0	1200.0	1455.0	1164.0	1375.0	1100.0	1260.0	1008.0	1090.0	872.0
PI734A 3	1505.0	1204.0	1460.0	1168.0	1405.0	1124.0	1310.0	1048.0	1210.0	968.0
S6L1D-G	1505.0	1204.0	1460.0	1168.0	1405.0	1124.0	1310.0	1048.0	1200.0	960.0
PI734B 3	1670.0	1336.0	1625.0	1300.0	1560.0	1248.0	1455.0	1164.0	1345.0	1076.0
S6L1D-H	1670.0	1336.0	1625.0	1300.0	1560.0	1248.0	1455.0	1164.0	1312.0	1049.6
PI734C 3	1895.0	1516.0	1845.0	1476.0	1770.0	1416.0	1650.0	1320.0	1525.0	1220.0

1. Available with single bearing only
2. Auxiliary winding option available
3. Star connection only
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 380V  
Parallel Star 190V  
Delta 220V

60Hz/1800rpm  
0.8 Power Factor

3 of 3

Winding 13/14	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>S7L1D-C</b> 3	1900.0	1520.0	1856.0	1484.8	<b>1781.0</b>	<b>1424.8</b>	1656.0	1324.8	1531.0	1224.8
<b>PI734D</b> 3	2050.0	1640.0	1995.0	1596.0	<b>1915.0</b>	<b>1532.0</b>	1785.0	1428.0	1650.0	1320.0
<b>S7L1D-D</b> 3	2050.0	1640.0	2000.0	1600.0	<b>1919.0</b>	<b>1535.2</b>	1787.0	1429.6	1650.0	1320.0
<b>S7L1D-E</b> 3	2150.0	1720.0	2094.0	1675.2	<b>2013.0</b>	<b>1610.4</b>	1875.0	1500.0	1731.0	1384.8
<b>S7L1D-F</b> 3	2338.0	1870.4	2269.0	1815.2	<b>2187.0</b>	<b>1749.6</b>	2031.0	1624.8	1881.0	1504.8
<b>PI734F</b> 3	2680.0	2144.0	2605.0	2084.0	<b>2505.0</b>	<b>2004.0</b>	2330.0	1864.0	2155.0	1724.0
<b>S7L1D-G</b> 3	2681.0	2144.8	2606.0	2084.8	<b>2506.0</b>	<b>2004.8</b>	2331.0	1864.8	2156.0	1724.8
<b>S7L1D-H</b> 3	2788.0	2230.4	2713.0	2170.4	<b>2613.0</b>	<b>2090.4</b>	2431.0	1944.8	2250.0	1800.0
<b>P80 LVSI804R</b> 3	3105.0	2484.0	3015.0	2412.0	<b>2825.0</b>	<b>2260.0</b>	2590.0	2072.0	2260.0	1808.0
<b>S7L1D-J</b> 3	3106.0	2484.8	3019.0	2415.2	<b>2850.0</b>	<b>2280.0</b>	2619.0	2095.2	2281.0	1824.8
<b>P80 LVSI804S</b> 3	3570.0	2856.0	3470.0	2776.0	<b>3250.0</b>	<b>2600.0</b>	2975.0	2380.0	2630.0	2104.0
<b>P80 LVSI804T</b> 3	3740.0	2992.0	3630.0	2904.0	<b>3400.0</b>	<b>2720.0</b>	3130.0	2504.0	2750.0	2200.0
<b>P80 LVSI804W</b> 3,4	4120.0	3296.0	4000.0	3200.0	<b>3750.0</b>	<b>3000.0</b>	3450.0	2760.0	3030.0	2424.0

1. Available with single bearing only
2. Auxiliary winding option available
3. Star connection only
4. Only available in 2 bearing





# 4 POLE Three Phase



Star 380V  
 Parallel Star 190V  
 Delta 220V

**60Hz/1800rpm**  
**0.8 Power Factor**

1 of 3

\* Winding 13/14 is the recommended option for 380V (60Hz)

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S0L1-D 1	7.9	6.3	7.6	6.1	7.1	5.7	6.5	5.2	5.8	4.6
PI044D	8.5	6.8	8.3	6.6	7.7	6.2	7.0	5.6	6.2	5.0
PI044E	11.3	9.0	11.1	8.9	10.3	8.2	9.3	7.4	8.2	6.6
S0L1-H 1	10.5	8.4	10.1	8.1	10.3	8.2	8.6	6.9	7.6	6.1
S0L1-L 1	13.1	10.5	12.6	10.1	11.9	9.5	10.9	8.7	9.5	7.6
PI044F	14.1	11.3	13.8	11.0	12.8	10.2	11.7	9.4	10.3	8.2
S0L1-P 1	15.6	12.5	15.3	12.2	14.3	11.4	13.0	10.4	11.4	9.1
PI044G	16.9	13.5	16.6	13.3	15.4	12.3	14.0	11.2	12.3	9.8
S0L2-F 1, 2	18.3	14.6	17.8	14.2	16.6	13.3	15.1	12.1	13.3	10.6
PI044H	19.7	15.8	19.4	15.5	17.9	14.3	16.4	13.1	14.4	11.5
S0L2-G 1, 2	20.9	16.7	20.3	16.2	19.0	15.2	17.3	13.8	15.3	12.2
PI144D	22.6	18.1	22.0	17.6	20.5	16.4	18.7	15.0	16.4	13.1
S0L2-M 1, 2	26.1	20.9	25.4	20.3	23.8	19.0	21.6	17.3	19.0	15.2
PI144E	28.2	22.6	27.6	22.1	25.6	20.5	23.3	18.6	20.5	16.4
PI144F	31.0	24.8	30.3	24.2	28.2	22.6	25.6	20.5	22.6	18.1
S0L2-P 1, 2	31.4	25.1	30.4	24.3	28.5	22.8	26.0	20.8	22.8	18.2
PI144G	33.8	27.0	33.1	26.5	30.8	24.6	28.2	22.6	24.6	19.7
S1L24J 1, 2	36.6	29.3	35.6	28.5	33.3	26.6	30.3	24.2	26.6	21.3
PI144H	39.5	31.6	38.4	30.7	35.9	28.7	32.8	26.2	28.7	23.0
S1L24K 1, 2	41.8	33.4	40.5	32.4	38.0	30.4	34.6	27.7	30.4	24.3
PI144J	46.1	36.9	45.1	36.1	41.0	32.8	37.4	29.9	32.8	26.2
S1L24N 1, 2	47.0	37.6	45.6	36.5	42.8	34.2	38.9	31.1	34.3	27.4
PI144K	49.2	39.4	47.6	38.1	45.1	36.1	39.4	31.5	34.5	27.6
UCI224C	50.0	40.0	48.5	38.8	45.5	36.4	41.0	32.8	35.0	28.0
S1L24R 1, 2	52.3	41.8	50.6	40.5	47.5	38.0	43.3	34.6	38.0	30.4
UCI224D	59.4	47.5	57.0	45.6	54.8	43.8	48.0	38.4	41.5	33.2
S1L24Y 1, 2	65.4	52.3	63.4	50.7	59.4	47.5	54.0	43.2	47.5	38.0
UCI224E	66.0	52.8	63.8	51.0	61.5	49.2	57.0	45.6	48.3	38.6
UCI224F	83.8	67.0	80.6	64.5	76.3	61.0	68.3	54.6	59.4	47.5
UCI224G	92.2	73.8	89.4	71.5	85.4	68.3	79.4	63.5	68.3	54.6
UCI274C	108.8	87.0	106.3	85.0	102.5	82.0	88.8	71.0	76.9	61.5
UCI274D	130.0	104.0	125.0	100.0	120.0	96.0	110.0	88.0	90.0	72.0

1. Available with single bearing only  
 2. Auxiliary winding option available (winding 711)  
 3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)



# 4 POLE Three Phase



**Star** 380V  
**Parallel Star** 190V  
**Delta** 220V  
**60Hz/1800rpm**  
**0.8 Power Factor**

**2 of 3**

\* Winding 13/14 is the recommended option for 380V (60Hz)

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274E	160.0	128.0	155.0	124.0	140.0	112.0	127.5	102.0	110.0	88.0
UCI274F	175.0	140.0	171.3	137.0	165.0	132.0	147.5	118.0	127.5	102.0
UCI274G	193.8	155.0	187.5	150.0	181.3	145.0	168.8	135.0	147.4	117.9
UCI274H	233.8	187.0	227.5	182.0	212.5	170.0	200.0	160.0	168.8	135.0
UCDI274J	269.0	215.2	263.0	210.4	250.0	200.0	225.0	180.0	194.0	155.2
UCDI274K	276.0	220.8	269.0	215.2	258.0	206.4	236.0	188.8	206.0	164.8
HCI444C	285.0	228.0	275.0	220.0	260.0	208.0	240.0	192.0	210.0	168.0
S4L1S-C	285.0	228.0	275.0	220.0	260.0	208.0	240.0	192.0	210.0	168.0
S4L1D-C 1	285.0	228.0	277.5	222.0	262.5	210.0	240.0	192.0	210.0	168.0
HCI444D	340.0	272.0	330.0	264.0	310.0	248.0	290.0	232.0	250.0	200.0
S4L1S-D	340.0	272.0	330.0	264.0	310.0	248.0	290.0	232.0	250.0	200.0
S4L1D-D 1	342.5	274.0	333.8	267.0	313.8	251.0	290.0	232.0	251.3	201.0
HCI444E	395.0	316.0	380.0	304.0	365.0	292.0	330.0	264.0	290.0	232.0
S4L1S-E	395.0	316.0	380.0	304.0	365.0	292.0	330.0	264.0	290.0	232.0
S4L1D-E 1	397.5	318.0	383.8	307.0	365.0	292.0	333.8	267.0	290.0	232.0
HCI444F	455.0	364.0	445.0	356.0	415.0	332.0	385.0	308.0	335.0	268.0
S4L1S-F	455.0	364.0	445.0	356.0	415.0	332.0	385.0	308.0	335.0	268.0
S4L1D-F 1	456.3	365.0	445.0	356.0	416.3	333.0	385.0	308.0	335.0	268.0
S4L1D-G 1	516.3	413.0	488.8	391.0	456.3	365.0	416.3	333.0	365.0	292.0
HCI544C	519.0	415.2	500.0	400.0	480.0	384.0	438.0	350.4	380.0	304.0
HCI544D	550.0	440.0	535.0	428.0	525.0	420.0	470.0	376.0	410.0	328.0
HCI544E	673.0	538.4	656.0	524.8	623.0	498.4	570.0	456.0	500.0	400.0
HCI544F	738.0	590.4	713.0	570.4	673.0	538.4	625.0	500.0	550.0	440.0
S6L1D-C 3	867.5	694.0	833.8	667.0	798.8	639.0	745.0	596.0	648.8	519.0
HCI634G 3	863.0	690.4	831.0	664.8	800.0	640.0	725.0	580.0	650.0	520.0
S6L1D-D 3	1027.5	822.0	993.8	795.0	936.3	749.0	836.3	669.0	721.3	577.0
HCI634H 3	1025.0	820.0	994.0	795.2	938.0	750.4	863.0	690.4	719.0	575.2
S6L1D-E 3	1141.3	913.0	1101.3	881.0	1050.0	840.0	971.3	777.0	845.0	676.0
HCI634J 3	1138.0	910.4	1100.0	880.0	1050.0	840.0	969.0	775.2	844.0	675.2
S6L1D-F 3	1275.0	1020.0	1231.0	984.8	1163.0	930.4	1081.0	864.8	938.0	750.4
HCI634K 3	1278.8	1023.0	1233.8	987.0	1165.0	932.0	1085.0	868.0	941.3	753.0
S6L1D-G 3	1291.3	1033.0	1242.5	994.0	1187.5	950.0	1096.3	877.0	950.0	760.0

1. Available with single bearing only  
 2. Auxiliary winding option available (winding 711)  
 3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)



# 4 POLE Three Phase



**Star** 380V  
**Parallel Star** 190V  
**Delta** 220V

**60Hz/1800rpm**  
**0.8 Power Factor**

**3 of 3**

\* Winding 13/14 is the recommended option for 380V (60Hz)

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI734A 3	1290.0	1032.0	1255.0	1004.0	1205.0	964.0	1120.0	896.0	1040.0	832.0
PI734B 3	1435.0	1148.0	1395.0	1116.0	1340.0	1072.0	1245.0	996.0	1155.0	924.0
S6L1D-H 3	1450.0	1160.0	1410.0	1128.0	1352.5	1082.0	1292.5	1034.0	1165.0	932.0
S7L1D-C 3	1603.0	1282.4	1564.0	1251.2	1499.0	1199.2	1395.0	1116.0	1286.0	1028.8
PI734C 3	1605.0	1284.0	1565.0	1252.0	1500.0	1200.0	1400.0	1120.0	1290.0	1032.0
PI734D 3	1710.0	1368.0	1660.0	1328.0	1595.0	1276.0	1485.0	1188.0	1375.0	1100.0
S7L1D-D 3	1712.0	1369.6	1663.0	1330.4	1598.0	1278.4	1484.0	1187.2	1375.0	1100.0
S7L1D-E 3	1792.0	1433.6	1742.0	1393.6	1678.0	1342.4	1559.0	1247.2	1440.0	1152.0
S7L1D-F 3	1955.0	1564.0	1900.0	1520.0	1821.0	1456.8	1697.0	1357.6	1583.0	1266.4
PI734E 3	1950.0	1560.0	1895.0	1516.0	1825.0	1460.0	1695.0	1356.0	1570.0	1256.0
S7L1D-G 3	2206.0	1764.8	2142.0	1713.6	2058.0	1646.4	1920.0	1536.0	1777.0	1421.6
PI734F 3	2205.0	1764.0	2145.0	1716.0	2060.0	1648.0	1915.0	1532.0	1770.0	1416.0
S7L1D-H 3	2335.0	1868.0	2266.0	1812.8	2177.0	1741.6	2028.0	1622.4	1875.0	1500.0
PI734G 3	2330.0	1864.0	2265.0	1812.0	2180.0	1744.0	2025.0	1620.0	1875.0	1500.0
S7L1D-J 3	2533.0	2026.4	2474.0	1979.2	2375.0	1900.0	2177.0	1741.6	1900.0	1520.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)



# 4 POLE Three Phase



Star 416V  
Parallel Star 208V  
Delta 240V

60Hz/1800rpm  
0.8 Power Factor

1 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S0L1-D 1	8.7	7.0	8.5	6.8	7.9	6.3	7.2	5.8	6.3	5.0
PI044D	9.1	7.3	8.9	7.1	8.3	6.6	7.5	6.0	6.6	5.3
S0L1-H 1	11.6	9.3	11.3	9.0	10.6	8.5	9.6	7.7	8.4	6.7
PI044E	12.1	9.7	11.9	9.5	11.0	8.8	10.0	8.0	8.8	7.0
S0L1-L 1	14.5	11.6	14.1	11.3	13.2	10.6	12.0	9.6	10.6	8.5
PI044F	15.1	12.1	14.9	11.9	13.8	11.0	12.5	10.0	11.0	8.8
S0L1-P 1	17.4	13.9	16.9	13.5	15.8	12.6	14.4	11.5	12.7	10.2
PI044G	18.2	14.6	17.8	14.2	16.5	13.2	15.1	12.1	13.2	10.6
S0L2-F 1, 2	20.3	16.2	19.8	15.8	18.5	14.8	16.8	13.4	14.8	11.8
PI044H	21.2	17.0	20.8	16.6	19.3	15.4	17.6	14.1	15.4	12.3
S0L2-G 1, 2	23.2	18.6	22.6	18.1	21.1	16.9	19.2	15.4	16.9	13.5
PI144D	24.2	19.4	23.7	19.0	22.0	17.6	20.0	16.0	17.6	14.1
S0L2-M 1,2	29.0	23.2	28.2	22.6	26.4	21.1	24.0	19.2	21.1	16.9
PI144E	30.3	24.2	29.6	23.7	27.5	22.0	25.0	20.0	22.0	17.6
PI144F	33.3	26.6	32.6	26.1	30.3	24.2	27.5	22.0	24.2	19.4
S0L2-P 1, 2	34.8	27.8	33.9	27.1	31.7	25.4	28.8	23.0	25.3	20.2
PI144G	36.3	29.0	35.5	28.4	33.0	26.4	30.3	24.2	26.4	21.1
S1L2-J 1, 2	40.7	32.6	39.5	31.6	37.0	29.6	33.6	26.9	29.6	23.7
PI144H	42.4	33.9	41.3	33.0	38.5	30.8	35.2	28.2	30.8	24.6
S1L2-K 1, 2	46.5	37.2	45.2	36.2	42.2	33.8	38.4	30.7	33.8	27.0
PI144J	49.5	39.6	48.4	38.7	44.0	35.2	40.2	32.2	35.2	28.2
S1L2-N 1,2	52.3	41.8	50.8	40.6	47.5	38.0	43.2	34.6	38.0	30.4
PI144K	55.0	44.0	53.1	42.5	50.0	40.0	45.0	36.0	39.5	31.6
UCI224C	55.0	44.0	53.1	42.5	50.0	40.0	45.0	36.0	38.8	31.0
S1L2-R 1, 2	58.1	46.5	56.5	45.2	52.8	42.2	48.0	38.4	42.2	33.8
UCI224D	65.0	52.0	62.5	50.0	60.0	48.0	52.5	42.0	45.5	36.4
S1L2-Y 1, 2	72.6	58.1	70.6	56.5	66.0	52.8	60.1	48.1	52.8	42.2
UCI224E	72.5	58.0	70.0	56.0	67.5	54.0	62.5	50.0	53.1	42.5
UCI224F	91.9	73.5	88.8	71.0	83.8	67.0	75.0	60.0	65.3	52.2
UCI224G	101.3	81.0	98.1	78.5	93.8	75.0	87.5	70.0	75.0	60.0
UCI274C	120.0	96.0	116.3	93.0	112.5	90.0	97.5	78.0	84.4	67.5
UCI274D	142.5	114.0	137.5	110.0	131.3	105.0	120.0	96.0	100.0	80.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 416V  
Parallel Star 208V  
Delta 240V

60Hz/1800rpm  
0.8 Power Factor

2 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274E	175.0	140.0	170.0	136.0	160.0	128.0	140.0	112.0	120.0	96.0
UCI274F	192.5	154.0	187.5	150.0	181.3	145.0	162.5	130.0	140.0	112.0
UCI274G	218.5	174.8	213.0	170.4	205.0	164.0	192.8	154.2	167.0	133.6
UCI274H	256.3	205.0	250.0	200.0	237.5	190.0	218.8	175.0	187.5	150.0
UCDI274J	294.0	235.2	288.0	230.4	269.0	215.2	250.0	200.0	213.0	170.4
HCI444C	310.0	248.0	300.0	240.0	288.0	230.4	260.0	208.0	230.0	184.0
S4L1S-C	310.0	248.0	300.0	240.0	288.0	230.4	260.0	208.0	230.0	184.0
S4L1D-C 1	310.0	248.0	300.0	240.0	288.0	230.4	260.0	208.0	230.0	184.0
UCDI27K	312.0	249.6	304.0	243.2	291.0	232.8	267.0	213.6	233.0	186.4
HCI444D	375.0	300.0	365.0	292.0	344.0	275.2	315.0	252.0	275.0	220.0
S4L1S-D	375.0	300.0	365.0	292.0	344.0	275.2	315.0	252.0	275.0	220.0
S4L1D-D 1	375.0	300.0	365.0	292.0	344.0	275.2	315.0	252.0	275.0	220.0
HCI444E	435.0	348.0	420.0	336.0	400.0	320.0	365.0	292.0	315.0	252.0
S4L1S-E	435.0	348.0	420.0	336.0	400.0	320.0	365.0	292.0	315.0	252.0
S4L1D-E 1	435.0	348.0	420.0	336.0	400.0	320.0	365.0	292.0	315.0	252.0
HCI444F	500.0	400.0	485.0	388.0	455.0	364.0	420.0	336.0	365.0	292.0
S4L1S-F	500.0	400.0	485.0	388.0	455.0	364.0	420.0	336.0	365.0	292.0
S4L1D-F 1	500.0	400.0	485.0	388.0	455.0	364.0	420.0	336.0	365.0	292.0
S4L1D-G 1	565.0	452.0	535.0	428.0	500.0	400.0	455.0	364.0	400.0	320.0
HCI544C	569.0	455.2	550.0	440.0	525.0	420.0	481.0	384.8	420.0	336.0
S5L1S-C	569.0	455.2	550.0	440.0	525.0	420.0	481.0	384.8	420.0	336.0
S5L1D-C 1	569.0	455.2	550.0	440.0	525.0	420.0	481.0	384.8	420.0	336.0
HCI544D	606.0	484.8	588.0	470.4	575.0	460.0	519.0	415.2	450.0	360.0
S5L1S-D	606.0	484.8	588.0	470.4	575.0	460.0	519.0	415.2	450.0	360.0
S5L1D-D 1	606.0	484.8	588.0	470.4	575.0	460.0	519.0	415.2	450.0	360.0
HCI544E	738.0	590.4	719.0	575.2	681.0	544.8	625.0	500.0	550.0	440.0
S5L1S-E	738.0	590.4	719.0	575.2	681.0	544.8	625.0	500.0	550.0	440.0
S5L1D-E 1	738.0	590.4	719.0	575.2	681.0	544.8	625.0	500.0	550.0	440.0
HCI544F	806.0	644.8	781.0	624.8	738.0	590.4	688.0	550.4	605.0	484.0
S5L1S-F	806.0	644.8	781.0	624.8	738.0	590.4	688.0	550.4	605.0	484.0
S5L1D-F 1	806.0	644.8	781.0	624.8	738.0	590.4	688.0	550.4	605.0	484.0
S5L1D-G 1	825.0	660.0	794.0	635.2	750.0	600.0	694.0	555.2	600.0	480.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 416V  
Parallel Star 208V  
Delta 240V

60Hz/1800rpm  
0.8 Power Factor

3 of 3

Winding 311/312/12	Model	TEMPERATURE RISE									
		Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
		kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S5L1D-H	1	881.0	704.8	850.0	680.0	800.0	640.0	737.0	589.6	638.0	510.4
S6L1D-C	3	950.0	760.0	913.0	730.4	875.0	700.0	815.0	652.0	710.0	568.0
HCI634G	3	950.0	760.0	913.0	730.4	875.0	700.0	813.0	650.4	710.0	568.0
HCI634H	3	1125.0	900.0	1088.0	870.4	1025.0	820.0	913.0	730.4	790.0	632.0
S6L1D-D	3	1125.0	900.0	1088.0	870.4	1025.0	820.0	915.0	732.0	790.0	632.0
S6L1D-E	3	1250.0	1000.0	1206.0	964.8	1150.0	920.0	1063.0	850.4	925.0	740.0
HCI634J	3	1250.0	1000.0	1206.0	964.8	1150.0	920.0	1063.0	850.4	925.0	740.0
S6L1D-F	3	1400.0	1120.0	1350.0	1080.0	1275.0	1020.0	1188.0	950.4	1030.0	824.0
HCI634K	3	1400.0	1120.0	1350.0	1080.0	1275.0	1020.0	1188.0	950.4	1030.0	824.0
S6L1D-G	3	1413.0	1130.4	1356.0	1084.8	1300.0	1040.0	1200.0	960.0	1038.0	830.4
PI734A	3	1465.0	1172.0	1425.0	1140.0	1375.0	1100.0	1275.0	1020.0	1180.0	944.0
S6L1D-H	3	1588.0	1270.4	1544.0	1235.2	1481.0	1184.8	1415.0	1132.0	1275.0	1020.0
PI734B	3	1630.0	1304.0	1590.0	1272.0	1525.0	1220.0	1415.0	1132.0	1310.0	1048.0
PI734C	3	1820.0	1456.0	1770.0	1416.0	1705.0	1364.0	1590.0	1272.0	1465.0	1172.0
S7L1D-C	3	1820.0	1456.0	1775.0	1420.0	1706.0	1364.8	1594.0	1275.2	1469.0	1175.2
PI734D	3	1940.0	1552.0	1890.0	1512.0	1815.0	1452.0	1690.0	1352.0	1565.0	1252.0
S7L1D-D	3	1944.0	1555.2	1900.0	1520.0	1819.0	1455.2	1700.0	1360.0	1569.0	1255.2
S7L1D-E	3	1969.0	1575.2	1912.0	1529.6	1837.0	1469.6	1712.0	1369.6	1581.0	1264.8
PI734E	3	2215.0	1772.0	2155.0	1724.0	2070.0	1656.0	1935.0	1548.0	1780.0	1424.0
S7L1D-F	3	2219.0	1775.2	2156.0	1724.8	2070.0	1656.0	1937.0	1549.6	1781.0	1424.8
PI734F	3	2505.0	2004.0	2435.0	1948.0	2345.0	1876.0	2190.0	1752.0	2015.0	1612.0
S7L1D-G	3	2506.0	2004.8	2437.0	1949.6	2350.0	1880.0	2194.0	1755.2	2019.0	1615.2
PI734G	3	2590.0	2072.0	2515.0	2012.0	2420.0	1936.0	2255.0	1804.0	2080.0	1664.0
S7L1D-H	3	2594.0	2075.2	2519.0	2015.2	2425.0	1940.0	2256.0	1804.8	2081.0	1664.8
PI734H	3	2740.0	2192.0	2640.0	2112.0	2500.0	2000.0	2320.0	1856.0	2050.0	1640.0
S7L1D-J	3	2787.0	2229.6	2712.0	2169.6	2600.0	2080.0	2381.0	1904.8	2081.0	1664.8
P80 LVSI804R	3	2860.0	2288.0	2780.0	2224.0	2600.0	2080.0	2385.0	1908.0	2080.0	1664.0
P80 LVSI804S	3	3195.0	2556.0	3105.0	2484.0	2900.0	2320.0	2665.0	2132.0	2325.0	1860.0
P80 LVSI804T	3	3490.0	2792.0	3390.0	2712.0	3170.0	2536.0	2910.0	2328.0	2600.0	2080.0
P80 LVSI804W	3,4	3940.0	3152.0	3841.0	3072.8	3590.0	2872.0	3350.0	2680.0	2915.0	2332.0
P80 LVSI804X	3,4	4300.0	3440.0	4130.0	3304.0	3870.0	3096.0	3615.0	2892.0	3140.0	2512.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 440V  
 Parallel Star 220V  
 Delta 254V

60Hz/1800rpm  
 0.8 Power Factor

1 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S0L1--D 1	9.2	7.4	9.0	7.2	8.4	6.7	7.6	6.1	6.7	5.4
PI044D	9.7	7.8	9.5	7.6	8.8	7.0	8.0	6.4	7.1	5.7
S0L1--H 1	12.3	9.8	12.0	9.6	11.2	9.0	10.2	8.2	9.0	7.2
PI044E	12.9	10.3	12.7	10.2	11.8	9.4	10.7	8.6	9.4	7.5
S0L1--L 1	15.4	12.3	15.0	12.0	14.0	11.2	12.7	10.2	11.2	9.0
PI044F	16.2	13.0	15.9	12.7	14.7	11.8	13.4	10.7	11.8	9.4
S0L1--P 1,2	18.5	14.8	18.0	14.4	16.8	13.4	15.3	12.2	13.4	10.7
PI044G	19.4	15.5	19.0	15.2	17.6	14.1	16.1	12.9	14.1	11.3
S0L2--F 1.2	21.5	17.2	21.0	16.8	19.6	15.7	17.8	14.2	15.7	12.6
PI044H	22.6	18.1	22.2	17.8	20.6	16.5	18.8	15.0	16.5	13.2
S0L2--G 1.2	24.6	19.7	24.0	19.2	22.4	17.9	20.4	16.3	17.9	14.3
PI144D	25.9	20.7	25.3	20.2	23.5	18.8	21.4	17.1	18.8	15.0
S0L2--M 1.2	30.8	24.6	29.9	23.9	28.0	22.4	25.5	20.4	22.4	17.9
PI144E	32.3	25.8	31.6	25.3	30.0	24.0	26.7	21.4	23.5	18.8
PI144F	35.5	28.4	34.8	27.8	32.3	25.8	29.4	23.5	25.9	20.7
S0L2--P 1.2	36.9	29.5	35.9	28.7	33.6	26.9	30.6	24.5	26.9	21.5
PI144G	38.8	31.0	37.9	30.3	35.3	28.2	32.3	25.8	28.2	22.6
S1L2--J 1.2	43.1	34.5	41.9	33.5	39.2	31.4	35.7	28.6	31.3	25.0
PI144H	45.2	36.2	44.1	35.3	41.1	32.9	37.6	30.1	32.9	26.3
S1L2--K 1.2	49.3	39.4	47.9	38.3	44.8	35.8	40.7	32.6	35.8	28.6
PI144J	52.9	42.3	51.7	41.4	47.0	37.6	42.9	34.3	37.6	30.1
S1L2--N 1.2	55.4	44.3	53.9	43.1	50.4	40.3	45.8	36.6	40.3	32.2
PI144K	56.3	45.0	55.0	44.0	52.5	42.0	46.3	37.0	40.6	32.5
UCI224C	56.3	45.0	55.0	44.0	52.5	42.0	46.3	37.0	40.0	32.0
S1L2--R 1.2	61.0	48.8	59.3	47.4	55.4	44.3	50.5	40.4	44.4	35.5
UCI224D	66.3	53.0	65.0	52.0	62.5	50.0	55.0	44.0	47.5	38.0
UCI224E	75.0	60.0	73.8	59.0	70.0	56.0	65.0	52.0	55.0	44.0
S1L2--Y 1.2	76.2	61.0	74.2	59.4	69.3	55.4	63.1	50.5	55.4	44.3
UCI224F	95.0	76.0	92.5	74.0	87.5	70.0	78.1	62.5	68.0	54.4
UCI224G	106.3	85.0	102.5	82.0	97.5	78.0	90.0	72.0	77.5	62.0
UCI274C	127.5	102.0	125.0	100.0	117.5	94.0	106.3	85.0	92.5	74.0
UCI274D	150.0	120.0	145.0	116.0	137.5	110.0	125.0	100.0	108.8	87.0

1. Available with single bearing only  
 2. Auxiliary winding option available (winding 711)  
 3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)  
 4. Only available in 2 bearing



# 4 POLE Three Phase



Star 440V  
 Parallel Star 220V  
 Delta 254V

60Hz/1800rpm  
 0.8 Power Factor

2 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274E	181.3	145.0	175.0	140.0	167.5	134.0	143.8	115.0	122.5	98.0
UCI274F	206.3	165.0	200.0	160.0	190.0	152.0	172.5	138.0	150.0	120.0
UCI274G	234.0	187.2	228.8	183.0	218.5	174.8	199.0	159.2	173.6	138.9
UCI274H	265.0	212.0	258.8	207.0	245.0	196.0	225.0	180.0	195.0	156.0
UCDI274J	306.0	244.8	300.0	240.0	281.0	224.8	264.0	211.2	219.0	175.2
UCDI274K	320.0	256.0	312.5	250.0	299.0	239.2	275.0	220.0	240.0	192.0
S4L1S-C	330.0	264.0	320.0	256.0	300.0	240.0	275.0	220.0	240.0	192.0
HCI444C	330.0	264.0	320.0	256.0	300.0	240.0	275.0	220.0	240.0	192.0
S4L1D-C 1	345.0	276.0	330.0	264.0	310.0	248.0	280.0	224.0	245.0	196.0
HCI444D	395.0	316.0	385.0	308.0	360.0	288.0	335.0	268.0	290.0	232.0
S4L1S-D	395.0	316.0	385.0	308.0	360.0	288.0	335.0	268.0	290.0	232.0
S4L1D-D 1	410.0	328.0	400.0	320.0	370.0	296.0	340.0	272.0	295.0	236.0
S4L1S-E	455.0	364.0	445.0	356.0	420.0	336.0	385.0	308.0	335.0	268.0
HCI444E	455.0	364.0	445.0	356.0	420.0	336.0	385.0	308.0	335.0	268.0
S4L1D-E 1	470.0	376.0	460.0	368.0	435.0	348.0	395.0	316.0	345.0	276.0
S4L1S-F	530.0	424.0	515.0	412.0	480.0	384.0	445.0	356.0	385.0	308.0
HCI444F	530.0	424.0	515.0	412.0	480.0	384.0	445.0	356.0	385.0	308.0
S4L1D-F 1	550.0	440.0	535.0	428.0	500.0	400.0	460.0	368.0	400.0	320.0
S4L1D-G 1	600.0	480.0	575.0	460.0	535.0	428.0	485.0	388.0	425.0	340.0
S5L1S-C	600.0	480.0	581.0	464.8	550.0	440.0	500.0	400.0	440.0	352.0
S5L1D-C 1	600.0	480.0	581.0	464.8	550.0	440.0	500.0	400.0	440.0	352.0
HCI544C	600.0	480.0	581.0	464.8	550.0	440.0	500.0	400.0	440.0	352.0
S5L1S-D 1	644.0	515.2	625.0	500.0	594.0	475.2	538.0	430.4	470.0	376.0
HCI544D	644.0	515.2	625.0	500.0	594.0	475.2	538.0	430.4	470.0	376.0
S5L1D-D 1	644.0	515.2	625.0	500.0	594.0	475.2	538.0	430.4	470.0	376.0
S5L1S-E	769.0	615.2	750.0	600.0	713.0	570.4	650.0	520.0	570.0	456.0
S5L1D-E 1	769.0	615.2	750.0	600.0	713.0	570.4	650.0	520.0	570.0	456.0
HCI544E	769.0	615.2	750.0	600.0	713.0	570.4	650.0	520.0	570.0	456.0
S5L1S-F	844.0	675.2	819.0	655.2	775.0	620.0	719.0	575.2	632.0	505.6
S5L1D-F 1	844.0	675.2	819.0	655.2	775.0	620.0	719.0	575.2	632.0	505.6
HCI544F	844.0	675.2	819.0	655.2	775.0	620.0	719.0	575.2	632.0	505.6
S5L1D-G 1	869.0	695.2	837.0	669.6	794.0	635.2	725.0	580.0	631.0	504.8
S5L1D-H 1	931.0	744.8	894.0	715.2	844.0	675.2	775.0	620.0	675.0	540.0
S6L1D-C 3	1000.0	800.0	969.0	775.2	925.0	740.0	845.0	676.0	735.0	588.0
HCI634G 3	1000.0	800.0	969.0	775.2	925.0	740.0	844.0	675.2	735.0	588.0

1. Available with single bearing only  
 2. Auxiliary winding option available (winding 711)  
 3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)  
 4. Only available in 2 bearing





# 4 POLE Three Phase



Star 440V  
Parallel Star 220V  
Delta 254V

60Hz/1800rpm  
0.8 Power Factor

3 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI634H 3	1163.0	930.4	1125.0	900.0	1063.0	850.4	963.0	770.4	850.0	680.0
S6L1D-D 3	1163.0	930.4	1125.0	900.0	1063.0	850.4	965.0	772.0	850.0	680.0
S6L1D-E 3	1300.0	1040.0	1250.0	1000.0	1200.0	960.0	1100.0	880.0	950.0	760.0
HCI634J 3	1300.0	1040.0	1250.0	1000.0	1200.0	960.0	1100.0	880.0	950.0	760.0
S6L1D-F 3	1463.0	1170.4	1406.0	1124.8	1338.0	1070.4	1238.0	990.4	1075.0	860.0
HCI634K 3	1463.0	1170.4	1413.0	1130.4	1338.0	1070.4	1238.0	990.4	1075.0	860.0
S6L1D-G 3	1563.0	1250.4	1500.0	1200.0	1431.0	1144.8	1313.0	1050.4	1144.0	915.2
PI734A 3	1605.0	1284.0	1560.0	1248.0	1500.0	1200.0	1395.0	1116.0	1290.0	1032.0
S6L1D-H 3	1681.0	1344.8	1637.0	1309.6	1569.0	1255.2	1500.0	1200.0	1356.0	1084.8
PI734B 3	1740.0	1392.0	1690.0	1352.0	1625.0	1300.0	1510.0	1208.0	1400.0	1120.0
PI734C 3	1945.0	1556.0	1890.0	1512.0	1815.0	1452.0	1690.0	1352.0	1565.0	1252.0
S7L1D-C 3	1945.0	1556.0	1894.0	1515.2	1819.0	1455.2	1694.0	1355.2	1569.0	1255.2
PI734D 3	2070.0	1656.0	2015.0	1612.0	1935.0	1548.0	1800.0	1440.0	1665.0	1332.0
S7L1D-D 3	2075.0	1660.0	2019.0	1615.2	1937.0	1549.6	1800.0	1440.0	1675.0	1340.0
S7L1D-E 3	2081.0	1664.8	2025.0	1620.0	1944.0	1555.2	1812.0	1449.6	1675.0	1340.0
PI734E 3	2365.0	1892.0	2300.0	1840.0	2210.0	1768.0	2055.0	1644.0	1900.0	1520.0
S7L1D-F 3	2369.0	1895.2	2300.0	1840.0	2212.0	1769.6	2056.0	1644.8	1900.0	1520.0
S7L1D-G 3	2675.0	2140.0	2600.0	2080.0	2500.0	2000.0	2325.0	1860.0	2150.0	1720.0
PI734F 3	2675.0	2140.0	2600.0	2080.0	2500.0	2000.0	2325.0	1860.0	2150.0	1720.0
PI734G 3	2715.0	2172.0	2635.0	2108.0	2535.0	2028.0	2360.0	1888.0	2180.0	1744.0
S7L1D-H 3	2719.0	2175.2	2637.0	2109.6	2537.0	2029.6	2362.0	1889.6	2181.0	1744.8
PI734H 3	2855.0	2284.0	2750.0	2200.0	2570.0	2056.0	2385.0	1908.0	2110.0	1688.0
S7L1D-J 3	2938.0	2350.4	2868.0	2294.4	2750.0	2200.0	2519.0	2015.2	2200.0	1760.0
P80 LVSI804R 3	3025.0	2424.0	2940.0	2352.0	2750.0	2200.0	2520.0	2016.0	2200.0	1760.0
P80 LVSI804S 3	3380.0	2704.0	3285.0	2628.0	3070.0	2456.0	2820.0	2256.0	2455.0	1964.0
P80 LVSI804T 3	3690.0	2952.0	3590.0	2872.0	3355.0	2684.0	3080.0	2464.0	2750.0	2200.0
P80 LVSI804W 3,4	4170.0	3336.0	4060.0	3248.0	3800.0	3040.0	3550.0	2840.0	3085.0	2468.0
P80 LVSI804X 3,4	4490.0	3592.0	4370.0	3496.0	4090.0	3272.0	3820.0	3056.0	3300.0	2640.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 460V  
Parallel Star 230V  
Delta 266V

60Hz/1800rpm  
0.8 Power Factor

1 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	10.0	8.0	9.8	7.8	9.1	7.3	8.2	6.6	7.3	5.8
PI044E	13.3	10.6	13.1	10.5	12.1	9.7	11.0	8.8	9.7	7.8
PI044F	16.7	13.4	16.4	13.1	15.2	12.2	13.8	11.0	12.1	9.7
PI044G	20.0	16.0	19.6	15.7	18.2	14.6	16.6	13.3	14.6	11.7
PI044H	23.3	18.6	22.9	18.3	21.2	17.0	19.4	15.5	17.0	13.6
PI144D	26.7	21.4	26.1	20.9	24.3	19.4	22.1	17.7	19.4	15.5
PI144E	33.3	26.6	32.6	26.1	30.3	24.2	27.6	22.1	24.3	19.4
PI144F	36.7	29.4	35.9	28.7	33.3	26.6	30.3	24.2	26.7	21.4
PI144G	40.0	32.0	39.1	31.3	36.4	29.1	33.3	26.6	29.1	23.3
PI144H	46.7	37.4	45.5	36.4	42.4	33.9	38.8	31.0	34.0	27.2
PI144J	54.6	43.7	53.4	42.7	48.5	38.8	44.3	35.4	38.8	31.0
PI144K	56.3	45.0	55.0	44.0	52.5	42.0	46.3	37.0	40.6	32.5
UCI22C	56.3	45.0	55.0	44.0	52.5	42.0	46.3	37.0	40.0	32.0
UCI22D	66.3	53.0	65.0	52.0	62.5	50.0	56.0	44.8	48.5	38.8
UCI22E	75.0	60.0	73.8	59.0	72.5	58.0	65.0	52.0	57.5	46.0
UCI22F	95.0	76.0	92.5	74.0	87.5	70.0	78.1	62.5	68.0	54.4
UCI22G	106.3	85.0	102.5	82.0	100.0	80.0	93.8	75.0	81.3	65.0
UCI27C	127.5	102.0	125.0	100.0	117.5	94.0	106.3	85.0	92.5	74.0
UCI27D	150.0	120.0	145.0	116.0	137.5	110.0	125.0	100.0	108.8	87.0
UCI27E	181.3	145.0	175.0	140.0	167.5	134.0	143.8	115.0	122.5	98.0
UCI27F	206.3	165.0	200.0	160.0	190.0	152.0	172.5	138.0	150.0	120.0
UCI27G	234.0	187.2	228.8	183.0	218.5	174.8	199.0	159.2	173.6	138.9
UCI27H	265.0	212.0	258.8	207.0	245.0	196.0	225.0	180.0	195.0	156.0
UCDI27J	319.0	255.2	313.0	250.4	294.0	235.2	275.0	220.0	231.0	184.8
UCDI27K	343.8	275.0	331.3	265.0	312.5	250.0	286.5	229.2	250.0	200.0
HCI444C	345.0	276.0	335.0	268.0	315.0	252.0	290.0	232.0	250.0	200.0
S4L1S-C	345.0	276.0	335.0	268.0	315.0	252.0	290.0	232.0	250.0	200.0
S4L1D-C 1	345.0	276.0	335.0	268.0	315.0	252.0	290.0	232.0	250.0	200.0
HCI444D	415.0	332.0	400.0	320.0	375.0	300.0	345.0	276.0	300.0	240.0
S4L1S-D	415.0	332.0	400.0	320.0	375.0	300.0	345.0	276.0	300.0	240.0
S4L1D-D 1	415.0	332.0	400.0	320.0	375.0	300.0	345.0	276.0	300.0	240.0
HCI444E	475.0	380.0	460.0	368.0	440.0	352.0	400.0	320.0	350.0	280.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 460V  
 Parallel Star 230V  
 Delta 266V

60Hz/1800rpm  
 0.8 Power Factor

2 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S4L1S-E	475.0	380.0	460.0	368.0	440.0	352.0	400.0	320.0	350.0	280.0
S4L1D-E 1	475.0	380.0	460.0	368.0	440.0	352.0	400.0	320.0	350.0	280.0
HCI444F	550.0	440.0	535.0	428.0	500.0	400.0	465.0	372.0	400.0	320.0
S4L1S-F	550.0	440.0	535.0	428.0	500.0	400.0	465.0	372.0	400.0	320.0
S4L1D-F 1	550.0	440.0	535.0	428.0	500.0	400.0	465.0	372.0	400.0	320.0
S4L1D-G	600.0	480.0	575.0	460.0	540.0	432.0	490.0	392.0	430.0	344.0
HCI544C	631.0	504.8	613.0	490.4	581.0	464.8	531.0	424.8	465.0	372.0
S5L1S-C	631.0	504.8	613.0	490.4	581.0	464.8	531.0	424.8	465.0	372.0
S5L1D-C 1	631.0	504.8	613.0	490.4	581.0	464.8	531.0	424.8	465.0	372.0
HCI544D	673.0	538.4	655.0	524.0	625.0	500.0	563.0	450.4	495.0	396.0
S5L1S-D 1	673.0	538.4	655.0	524.0	625.0	500.0	563.0	450.4	495.0	396.0
S5L1S-D 1	673.0	538.4	655.0	524.0	625.0	500.0	563.0	450.4	495.0	396.0
HCI544E	798.0	638.4	780.0	624.0	731.0	584.8	663.0	530.4	580.0	464.0
S5L1S-E	798.0	638.4	780.0	624.0	731.0	584.8	663.0	530.4	580.0	464.0
S5L1D-E 1	798.0	638.4	780.0	624.0	731.0	584.8	663.0	530.4	580.0	464.0
HCI544F	878.0	702.4	848.0	678.4	800.0	640.0	731.0	584.8	642.0	513.6
S5L1S-F	878.0	702.4	848.0	678.4	800.0	640.0	731.0	584.8	642.0	513.6
S5L1D-F 1	878.0	702.4	848.0	678.4	800.0	640.0	731.0	584.8	642.0	513.6
S5L1D-G 1	912.0	729.6	881.0	704.8	831.0	664.8	762.0	609.6	663.0	530.4
S5L1D-H 1	975.0	780.0	944.0	755.2	887.0	709.6	819.0	655.2	712.0	569.6
S6L1D-C 3	1044.0	835.2	1006.0	804.8	963.0	770.4	890.0	712.0	765.0	612.0
HCI634G 3	1044.0	835.2	1008.0	806.4	963.0	770.4	888.0	710.4	765.0	612.0
HCI634H 3	1175.0	940.0	1138.0	910.4	1075.0	860.0	1000.0	800.0	875.0	700.0
S6L1D-D 3	1175.0	940.0	1138.0	910.4	1075.0	860.0	1000.0	800.0	875.0	700.0
S6L1D-E 3	1350.0	1080.0	1300.0	1040.0	1250.0	1000.0	1150.0	920.0	1000.0	800.0
HCI634J 3	1350.0	1080.0	1300.0	1040.0	1250.0	1000.0	1150.0	920.0	1000.0	800.0
S6L1D-F 3	1519.0	1215.2	1450.0	1160.0	1388.0	1110.4	1275.0	1020.0	1100.0	880.0
HCI634K 3	1519.0	1215.2	1469.0	1175.2	1388.0	1110.4	1275.0	1020.0	1100.0	880.0
S6L1D-G 3	1563.0	1250.4	1500.0	1200.0	1438.0	1150.4	1319.0	1055.2	1150.0	920.0
PI734A 3	1615.0	1292.0	1570.0	1256.0	1510.0	1208.0	1405.0	1124.0	1300.0	1040.0
S6L1D-H 3	1756.0	1404.8	1706.0	1364.8	1638.0	1310.4	1540.0	1232.0	1412.0	1129.6
PI734B 3	1775.0	1420.0	1725.0	1380.0	1655.0	1324.0	1540.0	1232.0	1425.0	1140.0

1. Available with single bearing only  
 2. Auxiliary winding option available (winding 711)  
 3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)  
 4. Only available in 2 bearing



# 4 POLE Three Phase



Star 460V  
Parallel Star 230V  
Delta 266V

60Hz/1800rpm  
0.8 Power Factor

3 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI734C 3	1985.0	1588.0	1930.0	1544.0	1855.0	1484.0	1725.0	1380.0	1595.0	1276.0
S7L1D-C 3	1985.0	1588.0	1931.0	1544.8	1856.0	1484.8	1725.0	1380.0	1600.0	1280.0
PI734D 3	2115.0	1692.0	2055.0	1644.0	1975.0	1580.0	1840.0	1472.0	1700.0	1360.0
S7L1D-D 3	2125.0	1700.0	2063.0	1650.4	1975.0	1580.0	1844.0	1475.2	1700.0	1360.0
S7L1D-E 3	2175.0	1740.0	2112.0	1689.6	2031.0	1624.8	1888.0	1510.4	1750.0	1400.0
PI734E 3	2415.0	1932.0	2345.0	1876.0	2255.0	1804.0	2100.0	1680.0	1940.0	1552.0
S7L1D-F 3	2419.0	1935.2	2350.0	1880.0	2256.0	1804.8	2100.0	1680.0	1944.0	1555.2
PI734F 3	2730.0	2184.0	2650.0	2120.0	2550.0	2040.0	2370.0	1896.0	2195.0	1756.0
S7L1D-G 3	2731.0	2184.8	2650.0	2120.0	2550.0	2040.0	2375.0	1900.0	2200.0	1760.0
S7L1D-H 3	2812.0	2249.6	2725.0	2180.0	2625.0	2100.0	2450.0	1960.0	2256.0	1804.8
PI734G 3	2810.0	2248.0	2725.0	2180.0	2625.0	2100.0	2445.0	1956.0	2255.0	1804.0
PI734H 3	2935.0	2348.0	2850.0	2280.0	2640.0	2112.0	2450.0	1960.0	2170.0	1736.0
S7L1D-J 3	3063.0	2450.4	3000.0	2400.0	2875.0	2300.0	2631.0	2104.8	2300.0	1840.0
P80 LVSI804R 3	3163.0	2530.0	3066.0	2452.8	2875.0	2300.0	2635.0	2108.0	2300.0	1840.0
P80 LVSI804S 3	3531.0	2824.0	3436.0	2748.8	3210.0	2568.0	2948.0	2358.4	2569.0	2055.2
P80 LVSI804T 3	3857.0	3085.0	3753.0	3002.4	3508.0	2806.4	3220.0	2576.0	2875.0	2300.0
P80 LVSI804W 3,4	4360.0	3488.0	4245.0	3396.0	3969.0	3175.2	3710.0	2968.0	3224.0	2579.2
P80 LVSI804X 3,4	4696.0	3756.0	4571.0	3656.8	4278.0	3422.4	3998.0	3198.4	3474.0	2779.2

3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)

4. Only available in 2 bearing



# 4 POLE Three Phase



Star 480V  
Parallel Star 240V  
Delta 277V

60Hz/1800rpm  
0.8 Power Factor

1 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S0L1-D 1	10.0	8.0	9.6	7.7	9.0	7.2	8.2	6.6	7.2	5.8
PI044D	10.3	8.2	10.1	8.1	9.4	7.5	8.5	6.8	7.5	6.0
PI044E	13.2	10.6	12.8	10.2	13.0	10.4	10.9	8.7	9.6	7.7
S0L1-H 1	13.8	11.0	13.5	10.8	12.5	10.0	11.4	9.1	10.0	8.0
S0L1-L 1	16.5	13.2	16.0	12.8	15.0	12.0	13.7	11.0	12.0	9.6
PI044F	17.2	13.8	16.9	13.5	15.6	12.5	14.3	11.4	12.5	10.0
S0L2-P 1	19.8	15.8	19.2	15.4	18.0	14.4	16.4	13.1	14.4	11.5
PI044G	20.6	16.5	20.3	16.2	18.8	15.0	17.1	13.7	15.0	12.0
S0L2-F 1.2	23.1	18.5	22.4	17.9	21.0	16.8	19.1	15.3	16.8	13.4
PI044H	24.1	19.3	23.6	18.9	21.9	17.5	20.0	16.0	17.5	14.0
S0L2-G 1.2	26.4	21.1	25.6	20.5	24.0	19.2	21.8	17.4	19.2	15.4
PI044D	27.5	22.0	26.9	21.5	25.0	20.0	22.8	18.2	20.0	16.0
S0L2-M 1.2	33.0	26.4	32.0	25.6	30.0	24.0	27.3	21.8	24.0	19.2
PI144E	34.4	27.5	33.6	26.9	31.3	25.0	28.4	22.7	25.0	20.0
PI144F	37.8	30.2	37.0	29.6	34.4	27.5	31.3	25.0	27.5	22.0
S0L2-P 1.2	39.6	31.7	38.4	30.7	36.0	28.8	32.8	26.2	28.8	23.0
PI144G	41.3	33.0	40.3	32.2	37.5	30.0	34.4	27.5	30.0	24.0
S1L2-J 1.2	46.2	37.0	45.0	36.0	42.0	33.6	38.2	30.6	33.6	26.9
PI144H	48.1	38.5	46.9	37.5	43.8	35.0	40.0	32.0	35.0	28.0
S1L2-K 1.2	52.8	42.2	51.2	41.0	48.0	38.4	43.7	35.0	38.4	30.7
PI144J	56.3	45.0	55.0	44.0	50.0	40.0	45.6	36.5	40.0	32.0
S1L2-N 1.2	59.4	47.5	57.6	46.1	54.0	43.2	49.1	39.3	43.2	34.6
PI144K	60.0	48.0	58.1	46.5	55.0	44.0	48.0	38.4	42.1	33.7
UCI224C	60.0	48.0	58.1	46.5	55.0	44.0	48.0	38.4	42.0	33.6
S1L2-R 1.2	66.0	52.8	64.0	51.2	60.0	48.0	54.6	43.7	48.0	38.4
UCI224D	71.3	57.0	68.8	55.0	65.0	52.0	58.0	46.4	50.0	40.0
S1L2-Y 1.2	80.0	64.0	78.8	63.0	75.0	60.0	68.0	54.4	60.0	48.0
UCI224E	82.5	66.0	80.0	64.0	75.0	60.0	68.2	54.6	60.0	48.0
UCI224F	102.5	82.0	100.0	80.0	93.8	75.0	82.5	66.0	71.8	57.4
UCI224G	113.8	91.0	110.0	88.0	103.8	83.0	95.0	76.0	82.5	66.0
UCI274C	137.5	110.0	132.5	106.0	125.0	100.0	112.5	90.0	97.5	78.0
UCI274D	158.8	127.0	156.3	125.0	146.3	117.0	131.3	105.0	110.0	88.0

1. Available with single bearing only  
2. Auxiliary winding option available (winding 711)



# 4 POLE Three Phase



Star 480V  
Parallel Star 240V  
Delta 277V

60Hz/1800rpm  
0.8 Power Factor

2 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274E	193.8	155.0	187.5	150.0	178.8	143.0	160.0	128.0	138.0	110.4
UCI274F	218.8	175.0	212.5	170.0	206.3	165.0	187.5	150.0	160.0	128.0
UCI274G	253.3	202.6	250.0	200.0	231.4	185.1	212.2	169.8	180.0	144.0
UCI274H	280.0	224.0	275.0	220.0	255.0	204.0	235.0	188.0	204.0	163.2
UCDI274J	325.0	260.0	319.0	255.2	300.0	240.0	275.0	220.0	235.0	188.0
UCDI274K	343.8	275.0	331.3	265.0	312.5	250.0	288.0	230.4	250.0	200.0
HCI444C	345.0	276.0	335.0	268.0	315.0	252.0	290.0	232.0	250.0	200.0
S4L1S-C	345.0	276.0	335.0	268.0	315.0	252.0	290.0	232.0	250.0	200.0
S4L1D-C 1	355.0	284.0	350.0	280.0	325.0	260.0	295.0	236.0	260.0	208.0
HCI444D	415.0	332.0	400.0	320.0	375.0	300.0	345.0	276.0	300.0	240.0
S4L1S-D	415.0	332.0	400.0	320.0	375.0	300.0	345.0	276.0	300.0	240.0
S4L1D-D 1	430.0	344.0	415.0	332.0	390.0	312.0	355.0	284.0	310.0	248.0
HCI444E	475.0	380.0	460.0	368.0	440.0	352.0	400.0	320.0	350.0	280.0
S4L1S-E	475.0	380.0	460.0	368.0	440.0	352.0	400.0	320.0	350.0	280.0
S4L1D-E 1	490.0	392.0	475.0	380.0	455.0	364.0	410.0	328.0	360.0	288.0
HCI444F	550.0	440.0	535.0	428.0	500.0	400.0	465.0	372.0	400.0	320.0
S4L1S-F	550.0	440.0	535.0	428.0	500.0	400.0	465.0	372.0	400.0	320.0
S4L1D-F 1	575.0	460.0	555.0	444.0	520.0	416.0	480.0	384.0	415.0	332.0
S4L1D-G 1	625.0	500.0	600.0	480.0	562.5	450.0	510.0	408.0	445.0	356.0
HCI544C	645.0	516.0	625.0	500.0	594.0	475.2	538.0	430.4	470.0	376.0
S5L1S-C	645.0	516.0	625.0	500.0	594.0	475.2	538.0	430.4	470.0	376.0
S5L1D-C 1	644.0	515.2	625.0	500.0	594.0	475.2	538.0	430.4	470.0	376.0
HCI544D	694.0	555.2	675.0	540.0	644.0	515.2	588.0	470.4	515.0	412.0
S5L1S-D	694.0	555.2	675.0	540.0	644.0	515.2	588.0	470.4	515.0	412.0
S5L1D-D 1	694.0	555.2	675.0	540.0	644.0	515.2	588.0	470.4	515.0	412.0
HCI544E	819.0	655.2	800.0	640.0	750.0	600.0	675.0	540.0	594.0	475.2
S5L1S-E	819.0	655.2	800.0	640.0	750.0	600.0	675.0	540.0	594.0	475.2
S5L1D-E 1	819.0	655.2	800.0	640.0	750.0	600.0	675.0	540.0	594.0	475.2
HCI544F	906.0	724.8	875.0	700.0	825.0	660.0	750.0	600.0	660.0	528.0
S5L1S-F	906.0	724.8	875.0	700.0	825.0	660.0	750.0	600.0	660.0	528.0
S5L1D-F 1	906.0	724.8	875.0	700.0	825.0	660.0	750.0	600.0	660.0	528.0
S5L1D-G 1	944.0	755.2	913.0	730.4	875.0	700.0	794.0	635.2	700.0	560.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 480V  
Parallel Star 240V  
Delta 277V

60Hz/1800rpm  
0.8 Power Factor

3 of 3

Winding 311/312/12	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S5L1D-H 1	1013.0	810.4	981.0	784.8	937.0	749.6	844.0	675.2	750.0	600.0
S6L1D-C 3	1088.0	870.4	1044.0	835.2	1000.0	800.0	915.0	732.0	790.0	632.0
HCI634G 3	1088.0	870.4	1046.0	836.8	1000.0	800.0	913.0	730.4	790.0	632.0
HCI634H 3	1219.0	975.2	1188.0	950.4	1125.0	900.0	1025.0	820.0	900.0	720.0
S6L1D-D 3	1219.0	975.2	1188.0	950.4	1125.0	900.0	1025.0	820.0	900.0	720.0
S6L1D-E 3	1400.0	1120.0	1350.0	1080.0	1300.0	1040.0	1188.0	950.4	1035.0	828.0
HCI634J 3	1400.0	1120.0	1350.0	1080.0	1300.0	1040.0	1188.0	950.4	1035.0	828.0
S6L1D-F 3	1575.0	1260.0	1500.0	1200.0	1438.0	1150.4	1313.0	1050.4	1125.0	900.0
HCI634K 3	1575.0	1260.0	1525.0	1220.0	1438.0	1150.4	1313.0	1050.4	1125.0	900.0
S6L1D-G 3	1625.0	1300.0	1569.0	1255.2	1500.0	1200.0	1375.0	1100.0	1200.0	960.0
PI734A 3	1630.0	1304.0	1585.0	1268.0	1525.0	1220.0	1415.0	1132.0	1310.0	1048.0
PI734B 3	1810.0	1448.0	1760.0	1408.0	1690.0	1352.0	1575.0	1260.0	1455.0	1164.0
S6L1D-H 3	1812.0	1449.6	1762.0	1409.6	1694.0	1355.2	1575.0	1260.0	1455.0	1164.0
PI734C 3	2025.0	1620.0	1970.0	1576.0	1890.0	1512.0	1760.0	1408.0	1625.0	1300.0
S7L1D-C 3	2025.0	1620.0	1975.0	1580.0	1894.0	1515.2	1762.0	1409.6	1625.0	1300.0
PI734D 3	2160.0	1728.0	2100.0	1680.0	2015.0	1612.0	1875.0	1500.0	1735.0	1388.0
S7L1D-D 3	2162.0	1729.6	2100.0	1680.0	2019.0	1615.2	1875.0	1500.0	1737.0	1389.6
S7L1D-E 3	2263.0	1810.4	2200.0	1760.0	2119.0	1695.2	1969.0	1575.2	1819.0	1455.2
PI734E 3	2465.0	1972.0	2395.0	1916.0	2300.0	1840.0	2140.0	1712.0	2000.0	1600.0
S7L1D-F 3	2469.0	1975.2	2400.0	1920.0	2300.0	1840.0	2144.0	1715.2	2000.0	1600.0
PI734F 3	2785.0	2228.0	2705.0	2164.0	2600.0	2080.0	2420.0	1936.0	2240.0	1792.0
S7L1D-G 3	2787.0	2229.6	2706.0	2164.8	2600.0	2080.0	2425.0	1940.0	2244.0	1795.2
PI734G 3	2945.0	2356.0	2860.0	2288.0	2750.0	2200.0	2560.0	2048.0	2365.0	1892.0
S7L1D-H 3	2950.0	2360.0	2862.0	2289.6	2750.0	2200.0	2562.0	2049.6	2369.0	1895.2
PI734H 3	3120.0	2496.0	3000.0	2400.0	2800.0	2240.0	2600.0	2080.0	2300.0	1840.0
S7L1D-J 3	3200.0	2560.0	3125.0	2500.0	3000.0	2400.0	2750.0	2200.0	2400.0	1920.0
P80 LVSI804R 3	3300.0	2640.0	3200.0	2560.0	3000.0	2400.0	2750.0	2200.0	2400.0	1920.0
P80 LVSI804S 3	3685.0	2948.0	3585.0	2868.0	3350.0	2680.0	3075.0	2460.0	2680.0	2144.0
P80 LVSI804T 3	4025.0	3220.0	3915.0	3132.0	3660.0	2928.0	3360.0	2688.0	3000.0	2400.0
P80 LVSI804W 3,4	4550.0	3640.0	4430.0	3544.0	4142.0	3313.6	3871.0	3096.8	3364.0	2691.2
P80 LVSI804X 3,4	4900.0	3920.0	4770.0	3816.0	4464.0	3571.2	4172.0	3337.6	3625.0	2900.0

1. Available with single bearing only
2. Auxiliary winding option available (winding 711)
3. Star connection only (reconnectable winding 311 available on request for HCI6 & S6L1D)
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 600V  
Parallel Star 300V  
Delta 346V

60Hz/1800rpm  
0.8 Power Factor

1 of 3

Winding 07/17	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
PI044D	10.2	8.2	9.9	7.9	9.4	7.5	8.5	6.8	7.5	6.0
S0L1-D 1	10.2	8.2	9.9	7.9	9.4	7.5	8.5	6.8	7.5	6.0
PI044E	13.6	10.9	13.1	10.5	12.5	10.0	11.3	9.0	10.0	8.0
S0L1-H 1	13.6	10.9	13.1	10.5	12.5	10.0	11.3	9.0	10.0	8.0
S0L1-L 1	16.4	13.1	15.8	12.6	15.0	12.0	13.5	10.8	12.0	9.6
PI044F	17.0	13.6	16.4	13.1	15.6	12.5	14.0	11.2	12.5	10.0
PI044G	20.5	16.4	19.7	15.8	18.8	15.0	16.9	13.5	15.0	12.0
S0L1-P 1	20.5	16.4	19.7	15.8	18.8	15.0	16.9	13.5	15.0	12.0
S0L2-F 1	22.9	18.3	22.1	17.7	21.0	16.8	18.9	15.1	16.8	13.4
PI044H	23.9	19.1	23.0	18.4	21.9	17.5	19.7	15.8	17.5	14.0
PI144D	27.3	21.8	26.3	21.0	25.0	20.0	22.5	18.0	20.0	16.0
S0L2-G 1	27.3	21.8	26.3	21.0	25.0	20.0	22.5	18.0	20.0	16.0
S0L2-M 1	32.7	26.2	31.5	25.2	30.0	24.0	27.0	21.6	24.0	19.2
PI144E	34.1	27.3	32.9	26.3	31.3	25.0	28.2	22.6	25.0	20.0
PI144F	37.5	30.0	36.1	28.9	34.4	27.5	31.0	24.8	27.5	22.0
S0L2-P 1	39.7	31.8	38.2	30.6	36.4	29.1	32.8	26.2	29.1	23.3
PI144G	40.9	32.7	39.4	31.5	37.5	30.0	33.8	27.0	30.0	24.0
PI144H	47.7	38.2	46.0	36.8	43.8	35.0	39.4	31.5	35.0	28.0
S1L2-J 1	47.7	38.2	46.0	36.8	43.8	35.0	39.4	31.5	35.0	28.0
S1L2-K 1	51.8	41.4	49.9	39.9	47.5	38.0	42.8	34.2	38.0	30.4
PI144J	54.5	43.6	52.5	42.0	50.0	40.0	45.0	36.0	40.0	32.0
PI144K	60.0	48.0	57.8	46.2	55.0	44.0	49.5	39.6	44.0	35.2
S1L2-N 1	60.0	48.0	57.8	46.2	55.0	44.0	49.5	39.6	44.0	35.2
UCI22C	60.0	48.0	58.1	46.5	55.0	44.0	48.0	38.4	42.0	33.6
S1L2-R 1	69.2	55.4	66.7	53.4	63.1	50.5	56.3	45.0	48.5	38.8
UCI224D	71.3	57.0	68.8	55.0	65.0	52.0	58.0	46.4	50.0	40.0
UCI224E	80.0	64.0	78.8	63.0	75.0	60.0	68.0	54.4	60.0	48.0
S1L2-Y 1	80.0	64.0	78.8	63.0	75.0	60.0	68.0	54.4	60.0	48.0
UCI224F	102.5	82.0	98.8	79.0	94.0	75.2	82.5	66.0	71.8	57.4
UCI224G	113.8	91.0	110.0	88.0	103.8	83.0	95.0	76.0	82.5	66.0
UCI274C	132.0	105.6	127.0	101.6	120.0	96.0	110.0	88.0	95.0	76.0
UCI274D	158.8	127.0	155.0	124.0	146.3	117.0	131.3	105.0	110.0	88.0
UCI274E	193.8	155.0	187.5	150.0	178.8	143.0	160.0	128.0	138.0	110.4
UCI274F	218.8	175.0	212.5	170.0	206.3	165.0	187.5	150.0	160.0	128.0

1. Available with single bearing only
2. Auxiliary winding option available
3. Star connection only
4. Only available in 2 bearing





# 4 POLE Three Phase



Star 600V  
Parallel Star 300V  
Delta 346V

60Hz/1800rpm  
0.8 Power Factor

2 of 3

Winding 07/17	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274G	246.3	197.0	240.0	192.0	225.0	180.0	206.3	165.0	175.0	140.0
UCI274H	280.0	224.0	275.0	220.0	255.0	204.0	235.0	188.0	204.0	163.2
UCDI274J	334.0	267.2	328.0	262.4	305.0	244.0	281.0	224.8	244.0	195.2
HCI444C	345.0	276.0	335.0	268.0	315.0	252.0	290.0	232.0	250.0	200.0
S4L1S-C	345.0	276.0	335.0	268.0	315.0	252.0	290.0	232.0	250.0	200.0
HCI444D	415.0	332.0	400.0	320.0	375.0	300.0	345.0	276.0	300.0	240.0
S4L1S-D	415.0	332.0	400.0	320.0	375.0	300.0	345.0	276.0	300.0	240.0
HC144E	475.0	380.0	460.0	368.0	440.0	352.0	400.0	320.0	350.0	280.0
S4L1S-E	475.0	380.0	460.0	368.0	440.0	352.0	400.0	320.0	350.0	280.0
HCI444F	550.0	440.0	535.0	428.0	500.0	400.0	465.0	372.0	400.0	320.0
S4L1S-F	550.0	440.0	535.0	428.0	500.0	400.0	465.0	372.0	400.0	320.0
HCI544C	615.0	492.0	595.0	476.0	563.0	450.4	515.0	412.0	448.0	358.4
S5L1S-C	615.0	492.0	595.0	476.0	563.0	450.4	515.0	412.0	448.0	358.4
HCI544D	694.0	555.2	675.0	540.0	644.0	515.2	588.0	470.4	515.0	412.0
S5L1S-D	694.0	555.2	675.0	540.0	644.0	515.2	588.0	470.4	515.0	412.0
HCI544E	790.0	632.0	770.0	616.0	725.0	580.0	658.0	526.4	570.0	456.0
S5L1S-E	790.0	632.0	770.0	616.0	725.0	580.0	658.0	526.4	570.0	456.0
HCI544F	906.0	724.8	875.0	700.0	825.0	660.0	750.0	600.0	660.0	528.0
S5L1S-F	906.0	724.8	875.0	700.0	825.0	660.0	750.0	600.0	660.0	528.0
S6L1D-C 3	1088.0	870.4	1046.0	836.8	1000.0	800.0	913.0	730.4	790.0	632.0
HCI634G 3	1088.0	870.4	1046.0	836.8	1000.0	800.0	913.0	730.4	790.0	632.0
HCI634H 3	1163.0	930.4	1125.0	900.0	1063.0	850.4	963.0	770.4	850.0	680.0
S6L1D-D 3	1163.0	930.4	1125.0	900.0	1063.0	850.4	963.0	770.4	850.0	680.0
HCI634J 3	1400.0	1120.0	1350.0	1080.0	1300.0	1040.0	1188.0	950.4	1035.0	828.0
S6L1D-E 3	1400.0	1120.0	1350.0	1080.0	1300.0	1040.0	1188.0	950.4	1035.0	828.0
HCI634K 3	1575.0	1260.0	1525.0	1220.0	1438.0	1150.4	1313.0	1050.4	1125.0	900.0
S6L1D-F 3	1575.0	1260.0	1525.0	1220.0	1438.0	1150.4	1313.0	1050.4	1125.0	900.0
S6L1D-G 3	1630.0	1304.0	1585.0	1268.0	1525.0	1220.0	1415.0	1132.0	1300.0	1040.0
PI734A 3	1630.0	1304.0	1585.0	1268.0	1525.0	1220.0	1415.0	1132.0	1310.0	1048.0
S6L1D-H 3	1810.0	1448.0	1760.0	1408.0	1690.0	1352.0	1575.0	1260.0	1450.0	1160.0
PI734B 3	1810.0	1448.0	1760.0	1408.0	1690.0	1352.0	1575.0	1260.0	1455.0	1164.0
PI734C 3	2025.0	1620.0	1970.0	1576.0	1890.0	1512.0	1760.0	1408.0	1625.0	1300.0

1. Available with single bearing only
2. Auxiliary winding option available
3. Star connection only
4. Only available in 2 bearing



# 4 POLE Three Phase



Star 600V  
Parallel Star 300V  
Delta 346V

60Hz/1800rpm  
0.8 Power Factor

3 of 3

Winding 07/17	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S7L1D-C 3	2025.0	1620.0	1975.0	1580.0	1894.0	1515.2	1762.0	1409.6	1625.0	1300.0
PI734D 3	2160.0	1728.0	2100.0	1680.0	2015.0	1612.0	1875.0	1500.0	1735.0	1388.0
S7L1D-D 3	2162.0	1729.6	2100.0	1680.0	2019.0	1615.2	1875.0	1500.0	1737.0	1389.6
S7L1D-E 3	2263.0	1810.4	2200.0	1760.0	2119.0	1695.2	1969.0	1575.2	1819.0	1455.2
PI734E 3	2465.0	1972.0	2395.0	1916.0	2300.0	1840.0	2140.0	1712.0	1980.0	1584.0
S7L1D-F 3	2469.0	1975.2	2400.0	1920.0	2300.0	1840.0	2144.0	1715.2	1981.0	1584.8
PI734F 3	2785.0	2228.0	2705.0	2164.0	2600.0	2080.0	2420.0	1936.0	2240.0	1792.0
S7L1D-G 3	2787.0	2229.6	2706.0	2164.8	2600.0	2080.0	2425.0	1940.0	2244.0	1795.2
PI734G 3	2945.0	2356.0	2860.0	2288.0	2750.0	2200.0	2560.0	2048.0	2365.0	1892.0
S7L1D-H 3	2950.0	2360.0	2862.0	2289.6	2750.0	2200.0	2562.0	2049.6	2369.0	1895.2
P80 LVSI804S 3	3420.0	2736.0	3325.0	2660.0	3110.0	2488.0	2820.0	2256.0	2370.0	1896.0
P80 LVSI804W 3,4	4550.0	3640.0	4430.0	3544.0	4142.0	3313.6	3871.0	3096.8	3364.0	2691.2
P80 LVSI804X 3,4	4900.0	3920.0	4770.0	3816.0	4464.0	3571.2	4172.0	3337.6	3625.0	2900.0

1. Available with single bearing only
2. Auxiliary winding option available
3. Star connection only
4. Only available in 2 bearing



# 4 POLE Three Phase



**Star** 660V - 690V  
**Parallel Star** 330V - 345V  
**Delta** 380V - 400V

**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 27/28	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
UCI274E	172.0	137.6	167.0	133.6	160.0	128.0	147.0	117.6	128.0	102.4
UCI274H	263.0	210.4	259.0	207.2	240.0	192.0	220.0	176.0	192.0	153.6
HCI444C	345.0	276.0	335.0	268.0	315.0	252.0	290.0	232.0	250.0	200.0
S4L1S-C	345.0	276.0	335.0	268.0	315.0	252.0	290.0	232.0	250.0	200.0
HCI444D	375.0	300.0	365.0	292.0	340.0	272.0	315.0	252.0	275.0	220.0
S4L1S-D	375.0	300.0	365.0	292.0	340.0	272.0	315.0	252.0	275.0	220.0
HC144E	420.0	336.0	410.0	328.0	385.0	308.0	355.0	284.0	310.0	248.0
S4L1S-E	420.0	336.0	410.0	328.0	385.0	308.0	355.0	284.0	310.0	248.0
HCI444F	520.0	416.0	500.0	400.0	475.0	380.0	435.0	348.0	380.0	304.0
S4L1S-F	520.0	416.0	500.0	400.0	475.0	380.0	435.0	348.0	380.0	304.0
HCI544C	600.0	480.0	580.0	464.0	550.0	440.0	500.0	400.0	440.0	352.0
S5L1S-C	600.0	480.0	580.0	464.0	550.0	440.0	500.0	400.0	440.0	352.0
HCI544D	655.0	524.0	633.0	506.4	600.0	480.0	545.0	436.0	480.0	384.0
S5L1S-D	655.0	524.0	633.0	506.4	600.0	480.0	545.0	436.0	480.0	384.0
HCI544E	790.0	632.0	765.0	612.0	725.0	580.0	659.0	527.2	580.0	464.0
S5L1S-E	790.0	632.0	765.0	612.0	725.0	580.0	659.0	527.2	580.0	464.0
HCI544F	818.0	654.4	790.0	632.0	750.0	600.0	682.0	545.6	600.0	480.0
S5L1S-F	818.0	654.4	790.0	632.0	750.0	600.0	682.0	545.6	600.0	480.0
HCI634G 3	1035.0	828.0	995.0	796.0	950.0	760.0	870.0	696.0	760.0	608.0
S6L1D-C 3	1035.0	828.0	995.0	796.0	950.0	760.0	870.0	696.0	760.0	608.0
PI734A 3	1500.0	1200.0	1440.0	1152.0	1405.0	1124.0	1305.0	1044.0	1195.0	956.0
S6L1D-F 3	1500.0	1200.0	1440.0	1152.0	1405.0	1124.0	1305.0	1044.0	1160.0	928.0
HCI634K 3	1588.0	1270.4	1538.0	1230.4	1450.0	1160.0	1330.0	1064.0	1160.0	928.0
S6L1D-G 3	1588.0	1270.4	1538.0	1230.4	1450.0	1160.0	1330.0	1064.0	1195.0	956.0
PI734B 3	1665.0	1332.0	1600.0	1280.0	1560.0	1248.0	1450.0	1160.0	1330.0	1064.0
S6L1D-H 3	1665.0	1332.0	1600.0	1280.0	1560.0	1248.0	1450.0	1160.0	1330.0	1064.0
PI734C 3	1960.0	1568.0	1880.0	1504.0	1840.0	1472.0	1710.0	1368.0	1570.0	1256.0
PI734D 3	2065.0	1652.0	1985.0	1588.0	1940.0	1552.0	1800.0	1440.0	1655.0	1324.0
PI734E 3	2185.0	1748.0	2100.0	1680.0	2050.0	1640.0	1910.0	1528.0	1750.0	1400.0
PI734F 3	2520.0	2016.0	2415.0	1932.0	2360.0	1888.0	2200.0	1760.0	2015.0	1612.0



# 6 POLE Three Phase



**Star** 380V - 440V **50Hz/1000rpm**  
**Delta** 220V - 254V **0.8 Power Factor**

Winding 312	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI636G 3	300.0	240.0	291.0	232.8	280.0	224.0	260.0	208.0	225.0	180.0
HCI636H 3	407.0	325.6	395.0	316.0	380.0	304.0	350.0	280.0	300.0	240.0
HCI636J 3	482.0	385.6	468.0	374.4	450.0	360.0	420.0	336.0	360.0	288.0
HCI636K 3	610.0	488.0	593.0	474.4	570.0	456.0	525.0	420.0	450.0	360.0
PI736B 3	750.0	600.0	730.0	584.0	700.0	560.0	650.0	520.0	565.0	452.0
PI736D 3	985.0	788.0	960.0	768.0	920.0	736.0	850.0	680.0	740.0	592.0
PI736F 3	1390.0	1112.0	1355.0	1084.0	1300.0	1040.0	1200.0	960.0	1040.0	832.0

**Star** 380V **60Hz/1200rpm**  
**Delta** 220V **0.8 Power Factor**

Winding 312	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI636G 3	321.0	256.8	312.0	249.6	300.0	240.0	275.0	220.0	235.0	188.0
HCI636H 3	428.0	342.4	416.0	332.8	400.0	320.0	370.0	296.0	310.0	248.0
HCI636J 3	513.0	410.4	499.0	399.2	480.0	384.0	450.0	360.0	390.0	312.0
HCI636K 3	652.0	521.6	634.0	507.2	610.0	488.0	565.0	452.0	480.0	384.0
PI736B 3	790.0	632.0	765.0	612.0	750.0	600.0	690.0	552.0	600.0	480.0
PI736D 3	1025.0	820.0	990.0	792.0	960.0	768.0	885.0	708.0	765.0	612.0
PI736F 3	1465.0	1172.0	1425.0	1140.0	1370.0	1096.0	1255.0	1004.0	1090.0	872.0



# 6 POLE Three Phase



**Star** 416V **60Hz/1200rpm**  
**Delta** 240V **0.8 Power Factor**

Winding 312	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI636G 3	354.0	283.2	344.0	275.2	331.0	264.8	306.0	244.8	260.0	208.0
HCI636H 3	482.0	385.6	468.0	374.4	450.0	360.0	413.0	330.4	350.0	280.0
HCI636J 3	568.0	454.4	552.0	441.6	531.0	424.8	500.0	400.0	430.0	344.0
HCI636K 3	722.0	577.6	702.0	561.6	675.0	540.0	625.0	500.0	535.0	428.0
PI736B 3	870.0	696.0	845.0	676.0	815.0	652.0	750.0	600.0	650.0	520.0
PI736D 3	1125.0	900.0	1095.0	876.0	1050.0	840.0	970.0	776.0	840.0	672.0
PI736F 3	1605.0	1284.0	1560.0	1248.0	1500.0	1200.0	1375.0	1100.0	1195.0	956.0

**Star** 440V **60Hz/1200rpm**  
**Delta** 254V **0.8 Power Factor**

Winding 312	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI636G 3	375.0	300.0	364.0	291.2	350.0	280.0	325.0	260.0	280.0	224.0
HCI636H 3	508.0	406.4	494.0	395.2	475.0	380.0	438.0	350.4	375.0	300.0
HCI636J 3	602.0	481.6	586.0	468.8	563.0	450.4	525.0	420.0	450.0	360.0
HCI636K 3	763.0	610.4	742.0	593.6	713.0	570.4	656.0	524.8	560.0	448.0
PI736B 3	940.0	752.0	910.0	728.0	875.0	700.0	815.0	652.0	705.0	564.0
PI736D 3	1230.0	984.0	1200.0	960.0	1150.0	920.0	1065.0	852.0	920.0	736.0
PI736F 3	1740.0	1392.0	1690.0	1352.0	1625.0	1300.0	1500.0	1200.0	1300.0	1040.0



# 6 POLE Three Phase



**Star** 480V **60Hz/1200rpm**  
**Delta** 277V **0.8 Power Factor**

Winding 312	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI636G 3	375.0	300.0	364.0	291.2	350.0	280.0	325.0	260.0	280.0	224.0
HCI636H 3	508.0	406.4	494.0	395.2	475.0	380.0	438.0	350.4	375.0	300.0
HCI636J 3	602.0	481.6	586.0	468.8	563.0	450.4	525.0	420.0	450.0	360.0
HCI636K 3	763.0	610.4	742.0	593.6	713.0	570.4	656.0	524.8	560.0	448.0
PI736B 3	940.0	752.0	910.0	728.0	875.0	700.0	815.0	652.0	705.0	564.0
PI736D 3	1230.0	984.0	1200.0	960.0	1150.0	920.0	1065.0	852.0	920.0	736.0
PI736F 3	1815.0	1452.0	1760.0	1408.0	1625.0	1300.0	1565.0	1252.0	1355.0	1084.0

**Star** 600V **60Hz/1200rpm**  
**Delta** 346V **0.8 Power Factor**

Winding 07	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
HCI636G 3	375.0	300.0	364.0	291.2	350.0	280.0	325.0	260.0	280.0	224.0
HCI636H 3	508.0	406.4	494.0	395.2	475.0	380.0	438.0	350.4	380.0	304.0
HCI636J 3	602.0	481.6	586.0	468.8	563.0	450.4	525.0	420.0	450.0	360.0
HCI636K 3	763.0	610.4	742.0	593.6	713.0	570.4	656.0	524.8	570.0	456.0
PI736B 3	940.0	752.0	910.0	728.0	875.0	700.0	815.0	652.0	705.0	564.0
PI736D 3	1230.0	984.0	1200.0	960.0	1150.0	920.0	1065.0	852.0	920.0	736.0
PI736F 3	1740.0	1392.0	1690.0	1352.0	1625.0	1300.0	1500.0	1200.0	1300.0	1040.0



# 4 POLE Medium Voltage Three Phase



**Star**      3300V      **50Hz/1500rpm**  
**0.8 Power Factor**

Winding 51	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>S9M1D-B</b>	2618.0	2094.4	2547.0	2037.6	<b>2380.0</b>	<b>1904.0</b>	2190.0	1752.0	1904.0	1523.2
<b>S9M1D-C</b>	2915.0	2332.0	2836.0	2268.8	<b>2650.0</b>	<b>2120.0</b>	2438.0	1950.4	2120.0	1696.0
<b>S9M1D-D</b>	3190.0	2552.0	3103.0	2482.4	<b>2900.0</b>	<b>2320.0</b>	2668.0	2134.4	2320.0	1856.0
<b>S9M1D-E</b>	3476.0	2780.8	3381.0	2704.8	<b>3160.0</b>	<b>2528.0</b>	2907.0	2325.6	2528.0	2022.4
<b>S9M1D-F</b>	4092.0	3273.6	3980.0	3184.0	<b>3720.0</b>	<b>2976.0</b>	3422.0	2737.6	2976.0	2380.8
<b>S9M1D-G</b>	4681.0	3744.8	4553.0	3642.4	<b>4255.0</b>	<b>3404.0</b>	3915.0	3132.0	3404.0	2723.2
<b>S9M1D-H</b>	5060.0	4048.0	4922.0	3937.6	<b>4600.0</b>	<b>3680.0</b>	4232.0	3385.6	3680.0	2944.0

**Star**      3300V      **50Hz/1500rpm**  
**0.8 Power Factor**

Winding 51	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>P80-MVSI804R</b>	2915.0	2332.0	2835.0	2268.0	<b>2650.0</b>	<b>2120.0</b>	2400.0	1920.0	2100.0	1680.0
<b>P80-MVSI804S</b>	3300.0	2640.0	3100.0	2480.0	<b>2900.0</b>	<b>2320.0</b>	2660.0	2128.0	2330.0	1864.0
<b>P80-MVSI804T</b>	3630.0	2904.0	3370.0	2696.0	<b>3160.0</b>	<b>2528.0</b>	2940.0	2352.0	2590.0	2072.0
<b>P80-MVSI804W</b>	4098.0	3278.4	3960.0	3168.0	<b>3718.0</b>	<b>2974.4</b>	3475.0	2780.0	3114.0	2491.2
<b>P80-MVSI804X</b>	4637.0	3709.6	4520.0	3616.0	<b>4253.0</b>	<b>3402.4</b>	3975.0	3180.0	3562.0	2849.6

\* Winding pitch is 5/6th for S9 and 2/3rd for P80



# 4 POLE High Voltage Three Phase



Star

5500V

**50Hz/1500rpm**  
**0.8 Power Factor**

Winding 63	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S9H1D-B	2475.0	1980.0	2408.0	1926.4	2250.0	1800.0	2070.0	1656.0	1800.0	1440.0
S9H1D-C	2772.0	2217.6	2696.0	2156.8	2520.0	2016.0	2318.0	1854.4	2016.0	1612.8
S9H1D-D	3163.0	2530.4	3076.0	2460.8	2875.0	2300.0	2645.0	2116.0	2300.0	1840.0
S9H1D-E	3751.0	3000.8	3649.0	2919.2	3410.0	2728.0	3137.0	2509.6	2728.0	2182.4
S9H1D-F	4263.0	3410.4	4146.0	3316.8	3875.0	3100.0	3565.0	2852.0	3100.0	2480.0
S9H1D-G	4604.0	3683.2	4478.0	3582.4	4185.0	3348.0	3850.0	3080.0	3348.0	2678.4
S9H1D-H	4972.0	3977.6	4836.0	3868.8	4520.0	3616.0	4158.0	3326.4	3616.0	2892.8

Star

6000V

**50Hz/1500rpm**  
**0.8 Power Factor**

Winding 71	TEMPERATURE RISE									
	Standby 138/27 (F)		Standby 125/40 (F)		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-HVSI804R	2500.0	2000.0	2400.0	1920.0	N/A	N/A	2250.0	1800.0	1950.0	1560.0
P80-HVSI804S	2795.0	2236.0	2695.0	2156.0	N/A	N/A	2520.0	2016.0	2200.0	1760.0
P80-HVSI804T	3190.0	2552.0	3075.0	2460.0	N/A	N/A	2875.0	2300.0	2480.0	1984.0
P80-HVSI804W	3780.0	3024.0	3640.0	2912.0	N/A	N/A	3410.0	2728.0	2970.0	2376.0
P80-HVSI804X	4260.0	3408.0	4140.0	3312.0	N/A	N/A	3875.0	3100.0	3370.0	2696.0





# 4 POLE High Voltage Three Phase



Star

6300V

**50Hz/1500rpm**  
**0.8 Power Factor**

Winding 61	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S9H1D-B	2365.0	1892.0	2301.0	1840.8	2150.0	1720.0	1978.0	1582.4	1720.0	1376.0
S9H1D-C	2646.0	2116.8	2573.0	2058.4	2405.0	1924.0	2213.0	1770.4	1924.0	1539.2
S9H1D-D	3020.0	2416.0	2937.0	2349.6	2745.0	2196.0	2525.0	2020.0	2196.0	1756.8
S9H1D-E	3581.0	2864.8	3483.0	2786.4	3255.0	2604.0	2995.0	2396.0	2604.0	2083.2
S9H1D-F	4070.0	3256.0	3959.0	3167.2	3700.0	2960.0	3404.0	2723.2	2960.0	2368.0
S9H1D-G	4450.0	3560.0	4328.0	3462.4	4045.0	3236.0	3721.0	2976.8	3236.0	2588.8
S9H1D-H	4895.0	3916.0	4762.0	3809.6	4450.0	3560.0	4094.0	3275.2	3560.0	2848.0

Star

6300V

**50Hz/1500rpm**  
**0.8 Power Factor**

Winding 61	TEMPERATURE RISE									
	Standby 138/27 (F)		Standby 125/40 (F)		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-HVSI804R	2386.0	1908.8	2291.0	1832.8	N/A	N/A	2148.0	1718.4	1861.0	1488.8
P80-HVSI804S	2668.0	2134.4	2573.0	2058.4	N/A	N/A	2405.0	1924.0	2100.0	1680.0
P80-HVSI804T	3045.0	2436.0	2935.0	2348.0	N/A	N/A	2744.0	2195.2	2368.0	1894.4
P80-HVSI804W	3608.0	2886.4	3475.0	2780.0	N/A	N/A	3255.0	2604.0	2835.0	2268.0
P80-HVSI804X	4108.0	3286.4	3952.0	3161.6	N/A	N/A	3699.0	2959.2	3226.0	2580.8



# 4 POLE High Voltage Three Phase



**Star 6600V - 6900V**     **50Hz/1500rpm**  
**0.8 Power Factor**

Winding 61	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>S9H1D-B</b>	2475.0	1980.0	2408.0	1926.4	<b>2250.0</b>	<b>1800.0</b>	2070.0	1656.0	1800.0	1440.0
<b>S9H1D-C</b>	2772.0	2217.6	2696.0	2156.8	<b>2520.0</b>	<b>2016.0</b>	2318.0	1854.4	2016.0	1612.8
<b>S9H1D-D</b>	3163.0	2530.4	3076.0	2460.8	<b>2875.0</b>	<b>2300.0</b>	2645.0	2116.0	2300.0	1840.0
<b>S9H1D-E</b>	3751.0	3000.8	3649.0	2919.2	<b>3410.0</b>	<b>2728.0</b>	3137.0	2509.6	2728.0	2182.4
<b>S9H1D-F</b>	4263.0	3410.4	4146.0	3316.8	<b>3875.0</b>	<b>3100.0</b>	3565.0	2852.0	3100.0	2480.0
<b>S9H1D-G</b>	4686.0	3748.8	4558.0	3646.4	<b>4260.0</b>	<b>3408.0</b>	3919.0	3135.2	3408.0	2726.4
<b>S9H1D-H</b>	5154.0	4123.2	5013.0	4010.4	<b>4685.0</b>	<b>3748.0</b>	4310.0	3448.0	3748.0	2998.4

**Star 6600V - 6900V**     **50Hz/1500rpm**  
**0.8 Power Factor**

Winding 61	TEMPERATURE RISE									
	Standby 138/27 (F)		Standby 125/40 (F)		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>P80-HVSI804R</b>	2500.0	2000.0	2400.0	1920.0	N/A	N/A	<b>2250.0</b>	<b>1800.0</b>	1950.0	1560.0
<b>P80-HVSI804S</b>	2795.0	2236.0	2695.0	2156.0	N/A	N/A	<b>2520.0</b>	<b>2016.0</b>	2200.0	1760.0
<b>P80-HVSI804T</b>	3190.0	2552.0	3075.0	2460.0	N/A	N/A	<b>2875.0</b>	<b>2300.0</b>	2480.0	1984.0
<b>P80-HVSI804W</b>	3780.0	3024.0	3640.0	2912.0	N/A	N/A	<b>3410.0</b>	<b>2728.0</b>	2970.0	2376.0
<b>P80-HVSI804X</b>	4300.0	3440.0	4140.0	3312.0	N/A	N/A	<b>3875.0</b>	<b>3100.0</b>	3380.0	2704.0



# 4 POLE High Voltage Three Phase



Star

10000V

**50Hz/1500rpm**  
**0.8 Power Factor**

Winding 81	TEMPERATURE RISE									
	Standby 138/27		Standby 125/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-HVSI804R	2520.0	2116.0	2430.0	1944.0	N/A	N/A	2270.0	1816.0	2000.0	1600.0
P80-HVSI804S	2790.0	2232.0	2690.0	2152.0	N/A	N/A	2515.0	2012.0	2200.0	1760.0
P80-HVSI804T	3150.0	2520.0	3035.0	2428.0	N/A	N/A	2840.0	2272.0	2500.0	2000.0
P80-HVSI804W	3600.0	2880.0	3470.0	2776.0	N/A	N/A	3259.0	2607.2	2830.0	2264.0
P80-HVSI804X	4100.0	3280.0	3960.0	3168.0	N/A	N/A	3724.0	2979.2	3240.0	2592.0

Star 10500V - 11000V

**50Hz/1500rpm**  
**0.8 Power Factor**

Winding 83	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S7H1D-C	1185.0	948.0	1155.0	924.0	1080.0	864.0	1000.0	800.0	930.0	744.0
S7H1D-D	1340.0	1072.0	1300.0	1040.0	1220.0	976.0	1125.0	900.0	1050.0	840.0
S7H1D-E	1485.0	1188.0	1440.0	1152.0	1350.0	1080.0	1250.0	1000.0	1160.0	928.0
S7H1D-F	1785.0	1428.0	1735.0	1388.0	1625.0	1300.0	1500.0	1200.0	1400.0	1120.0
S9H1D-B	2530.0	2024.0	2461.0	1968.8	2300.0	1840.0	2116.0	1692.8	1840.0	1472.0
S9H1D-C	2767.0	2213.6	2691.0	2152.8	2515.0	2012.0	2314.0	1851.2	2012.0	1609.6
S9H1D-D	3124.0	2499.2	3039.0	2431.2	2840.0	2272.0	2613.0	2090.4	2272.0	1817.6
S9H1D-E	3586.0	2868.8	3488.0	2790.4	3260.0	2608.0	2999.0	2399.2	2608.0	2086.4
S9H1D-F	4098.0	3278.4	3986.0	3188.8	3725.0	2980.0	3427.0	2741.6	2980.0	2384.0
S9H1D-G	4466.0	3572.8	4344.0	3475.2	4060.0	3248.0	3735.0	2988.0	3248.0	2598.4
S9H1D-H	4950.0	3960.0	4815.0	3852.0	4500.0	3600.0	4140.0	3312.0	3600.0	2880.0

Note: Winding pitch is 5/6th for S9 and 2/3rd for P80



# 4 POLE High Voltage Three Phase



**Star** 10500V **50Hz/1500rpm**  
**0.8 Power Factor**

Winding 83	TEMPERATURE RISE									
	Standby 138/27 (F)		Standby 125/40 (F)		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-HVSI804R	2405.0	1924.0	2320.0	1856.0	N/A	N/A	2168.0	1734.4	1909.0	1527.2
P80-HVSI804S	2663.0	2130.0	2568.0	2054.4	N/A	N/A	2401.0	1920.8	2100.0	1680.0
P80-HVSI804T	3007.0	2406.0	2897.0	2317.6	N/A	N/A	2711.0	2168.8	2386.0	1908.8
P80-HVSI804W	3426.0	2749.0	3312.0	2649.6	N/A	N/A	3111.0	2488.8	2701.0	2160.8
P80-HVSI804X	3914.0	3131.0	3780.0	3024.0	N/A	N/A	3555.0	2844.0	3093.0	2474.4

**Star** 11000V **50Hz/1500rpm**  
**0.8 Power Factor**

Winding 83	TEMPERATURE RISE									
	Standby 138/27 (F)		Standby 125/40 (F)		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-HVSI804R	2520.0	2016.0	2430.0	1944.0	N/A	N/A	2270.0	1816.0	2000.0	1600.0
P80-HVSI804S	2790.0	2232.0	2690.0	2152.0	N/A	N/A	2515.0	2012.0	2200.0	1760.0
P80-HVSI804T	3150.0	2520.0	3035.0	2428.0	N/A	N/A	2840.0	2272.0	2500.0	2000.0
P80-HVSI804W	3600.0	2880.0	3470.0	2776.0	N/A	N/A	3259.0	2607.2	2830.0	2264.0
P80-HVSI804X	4100.0	3280.0	3960.0	3168.0	N/A	N/A	3724.0	2979.2	3240.0	2592.0



# 4 POLE Medium Voltage Three Phase



Star

4160V

**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 51	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S9M1D-B	3113.0	2490.4	3028.0	2422.4	2830.0	2264.0	2604.0	2083.2	2264.0	1811.2
S9M1D-C	3465.0	2772.0	3371.0	2696.8	3150.0	2520.0	2898.0	2318.4	2520.0	2016.0
S9M1D-D	3883.0	3106.4	3777.0	3021.6	3530.0	2824.0	3248.0	2598.4	2824.0	2259.2
S9M1D-E	4290.0	3432.0	4173.0	3338.4	3900.0	3120.0	3588.0	2870.4	3120.0	2496.0
S9M1D-F	4945.0	3956.0	4810.0	3848.0	4495.0	3596.0	4135.0	3308.0	3596.0	2876.8
S9M1D-G	5709.0	4567.2	5553.0	4442.4	5190.0	4152.0	4775.0	3820.0	4152.0	3321.6
S9M1D-H	6160.0	4928.0	5992.0	4793.6	5600.0	4480.0	5152.0	4121.6	4480.0	3584.0

Star

4160V

**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 51	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-MVSI804R	3465.0	2772.0	3370.0	2696.0	3150.0	2520.0	2880.0	2304.0	2520.0	2016.0
P80-MVSI804S	3880.0	3104.0	3775.0	3020.0	3530.0	2824.0	3250.0	2600.0	2820.0	2256.0
P80-MVSI804T	4290.0	3432.0	4160.0	3328.0	3900.0	3120.0	3630.0	2904.0	3180.0	2544.0
P80-MVSI804W	4940.0	3952.0	4780.0	3824.0	4494.0	3595.2	4200.0	3360.0	3650.0	2920.0
P80-MVSI804X	5700.0	4560.0	5520.0	4416.0	5190.0	4152.0	4850.0	3880.0	4215.0	3372.0



# 4 POLE High Voltage Three Phase



Star

6600V

**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 63	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S9H1D-B	3163.0	2530.4	3076.0	2460.8	<b>2875.0</b>	<b>2300.0</b>	2645.0	2116.0	2300.0	1840.0
S9H1D-C	3454.0	2763.2	3360.0	2688.0	<b>3140.0</b>	<b>2512.0</b>	2889.0	2311.2	2512.0	2009.6
S9H1D-D	3883.0	3106.4	3777.0	3021.6	<b>3530.0</b>	<b>2824.0</b>	3248.0	2598.4	2824.0	2259.2
S9H1D-E	4620.0	3696.0	4494.0	3595.2	<b>4200.0</b>	<b>3360.0</b>	3864.0	3091.2	3360.0	2688.0
S9H1D-F	5225.0	4180.0	5083.0	4066.4	<b>4750.0</b>	<b>3800.0</b>	4370.0	3496.0	3800.0	3040.0
S9H1D-G	5643.0	4514.4	5489.0	4391.2	<b>5130.0</b>	<b>4104.0</b>	4720.0	3776.0	4104.0	3283.2
S9H1D-H	6094.0	4875.2	5928.0	4742.4	<b>5540.0</b>	<b>4432.0</b>	5097.0	4077.6	4432.0	3545.6

Star

7200V

**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 71	TEMPERATURE RISE									
	Standby 138/27		Standby 125/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-HVSI804R	3190.0	2552.0	3075.0	2460.0	N/A	N/A	<b>2875.0</b>	<b>2300.0</b>	2510.0	2008.0
P80-HVSI804S	3480.0	2784.0	3360.0	2688.0	N/A	N/A	<b>3140.0</b>	<b>2512.0</b>	2750.0	2200.0
P80-HVSI804T	3910.0	3128.0	3775.0	3020.0	N/A	N/A	<b>3530.0</b>	<b>2824.0</b>	3080.0	2464.0
P80-HVSI804W	4650.0	3720.0	4490.0	3592.0	N/A	N/A	<b>4200.0</b>	<b>3360.0</b>	3660.0	2928.0
P80-HVSI804X	5230.0	4184.0	5080.0	4064.0	N/A	N/A	<b>4750.0</b>	<b>3800.0</b>	4130.0	3304.0



# 4 POLE High Voltage Three Phase



**Star** 11400V **60Hz/1800rpm**  
**0.8 Power Factor**

Winding 81	TEMPERATURE RISE									
	Standby 138/27		Standby 125/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-HVSI804R	2870.0	2296.0	2770.0	2216.0	N/A	N/A	2588.0	2070.4	2280.0	1824.0
P80-HVSI804S	3180.0	2544.0	3065.0	2452.0	N/A	N/A	2868.0	2294.4	2505.0	2004.0
P80-HVSI804T	3590.0	2872.0	3460.0	2768.0	N/A	N/A	3238.0	2590.4	2850.0	2280.0
P80-HVSI804W	4100.0	3280.0	3950.0	3160.0	N/A	N/A	3715.0	2972.0	3226.0	2580.8
P80-HVSI804X	4670.0	3736.0	4510.0	3608.0	N/A	N/A	4245.0	3396.0	3694.0	2955.2

**Star** 12470V **60Hz/1800rpm**  
**0.8 Power Factor**

Winding 91	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
S9H1D-B	2640.0	2112.0	2568.0	2054.4	2400.0	1920.0	2208.0	1766.4	1920.0	1536.0
S9H1D-C	2981.0	2384.8	2900.0	2320.0	2710.0	2168.0	2493.0	1994.4	2168.0	1734.4
S9H1D-D	3278.0	2622.4	3189.0	2551.2	2980.0	2384.0	2742.0	2193.6	2384.0	1907.2
S9H1D-E	3702.0	2961.6	3601.0	2880.8	3365.0	2692.0	3096.0	2476.8	2692.0	2153.6
S9H1D-F	4191.0	3352.8	4077.0	3261.6	3810.0	3048.0	3505.0	2804.0	3048.0	2438.4
S9H1D-G	4571.0	3656.8	4446.0	3556.8	4155.0	3324.0	3823.0	3058.4	3324.0	2659.2
S9H1D-H	4967.0	3973.6	4831.0	3864.8	4515.0	3612.0	4154.0	3323.2	3612.0	2889.6

Note: Winding pitch is 5/6th for S9 and 2/3rd for P80



# 4 POLE High Voltage Three Phase



Star

12470V

**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 87	TEMPERATURE RISE									
	Standby 138/27		Standby 125/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-HVSI804R	2940.0	2352.0	2840.0	2272.0	N/A	N/A	2650.0	2120.0	2312.0	1849.6
P80-HVSI804S	3220.0	2576.0	3090.0	2472.0	N/A	N/A	2900.0	2320.0	2535.0	2028.0

Star

12470V

**60Hz/1800rpm**  
**0.8 Power Factor**

Winding 91	TEMPERATURE RISE									
	Standby 138/27		Standby 125/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
P80-HVSI804R	2655.0	2124.0	2570.0	2056.0	N/A	N/A	2400.0	1920.0	2080.0	1664.0
P80-HVSI804S	3010.0	2408.0	2900.0	2320.0	N/A	N/A	2710.0	2168.0	2355.0	1884.0
P80-HVSI804T	3305.0	2644.0	3185.0	2548.0	N/A	N/A	2980.0	2384.0	2590.0	2072.0
P80-HVSI804W	3710.0	2968.0	3580.0	2864.0	N/A	N/A	3365.0	2692.0	2930.0	2344.0
P80-HVSI804X	4200.0	3360.0	4050.0	3240.0	N/A	N/A	3810.0	3048.0	3300.0	2640.0





# 4 POLE High Voltage Three Phase



**Star**      13200V      **60Hz/1800rpm**  
**0.8 Power Factor**

Winding 91	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>S9H1D-B</b>	2789.0	2231.2	2712.0	2169.6	<b>2535.0</b>	<b>2028.0</b>	2332.0	1865.6	2028.0	1622.4
<b>S9H1D-C</b>	3157.0	2525.6	3070.9	2456.7	<b>2870.0</b>	<b>2296.0</b>	2640.0	2112.0	2296.0	1836.8
<b>S9H1D-D</b>	3471.0	2776.8	3376.0	2700.8	<b>3155.0</b>	<b>2524.0</b>	2903.0	2322.4	2524.0	2019.2
<b>S9H1D-E</b>	3916.0	3132.8	3809.0	3047.2	<b>3560.0</b>	<b>2848.0</b>	3275.0	2620.0	2848.0	2278.4
<b>S9H1D-F</b>	4433.0	3546.4	4312.0	3449.6	<b>4030.0</b>	<b>3224.0</b>	3708.0	2966.4	3224.0	2579.2
<b>S9H1D-G</b>	4840.0	3872.0	4708.0	3766.4	<b>4400.0</b>	<b>3520.0</b>	4048.0	3238.4	3520.0	2816.0
<b>S9H1D-H</b>	5258.0	4206.4	5115.0	4092.0	<b>4780.0</b>	<b>3824.0</b>	4398.0	3518.4	3824.0	3059.2

**Star**      13200V      **60Hz/1800rpm**  
**0.8 Power Factor**

Winding 91	TEMPERATURE RISE									
	Standby 138/27		Standby 125/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>P80-HVSI804R</b>	2810.0	2248.0	2720.0	2176.0	N/A	N/A	<b>2535.0</b>	<b>2028.0</b>	2200.0	1760.0
<b>P80-HVSI804S</b>	3185.0	2548.0	3070.0	2456.0	N/A	N/A	<b>2870.0</b>	<b>2296.0</b>	2490.0	1992.0
<b>P80-HVSI804T</b>	3500.0	2800.0	3375.0	2700.0	N/A	N/A	<b>3155.0</b>	<b>2524.0</b>	2740.0	2192.0
<b>P80-HVSI804W</b>	3930.0	3144.0	3790.0	3032.0	N/A	N/A	<b>3560.0</b>	<b>2848.0</b>	3100.0	2480.0
<b>P80-HVSI804X</b>	4450.0	3560.0	4295.0	3436.0	N/A	N/A	<b>4030.0</b>	<b>3224.0</b>	3500.0	2800.0

Note: Winding pitch is 5/6th for S9 and 2/3rd for P80



# 4 POLE High Voltage Three Phase



**Star**      13800V      **60Hz/1800rpm**  
**0.8 Power Factor**

Winding 91	TEMPERATURE RISE									
	Standby 163/27		Standby 150/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>S9H1D-B</b>	2915.0	2332.0	2836.0	2268.8	<b>2650.0</b>	<b>2120.0</b>	2438.0	1950.4	2120.0	1696.0
<b>S9H1D-C</b>	3300.0	2640.0	3210.0	2568.0	<b>3000.0</b>	<b>2400.0</b>	2760.0	2208.0	2400.0	1920.0
<b>S9H1D-D</b>	3630.0	2904.0	3531.0	2824.8	<b>3300.0</b>	<b>2640.0</b>	3036.0	2428.8	2640.0	2112.0
<b>S9H1D-E</b>	4098.0	3278.4	3986.0	3188.8	<b>3725.0</b>	<b>2980.0</b>	3427.0	2741.6	2980.0	2384.0
<b>S9H1D-F</b>	4637.0	3709.6	4510.0	3608.0	<b>4215.0</b>	<b>3372.0</b>	3878.0	3102.4	3372.0	2697.6
<b>S9H1D-G</b>	5060.0	4048.0	4922.0	3938.0	<b>4600.0</b>	<b>3680.0</b>	4232.0	3385.6	3680.0	2944.0
<b>S9H1D-H</b>	5500.0	4400.0	5350.0	4280.0	<b>5000.0</b>	<b>4000.0</b>	4600.0	3680.0	4000.0	3200.0

**Star**      13800V      **60Hz/1800rpm**  
**0.8 Power Factor**

Winding 91	TEMPERATURE RISE									
	Standby 138/27		Standby 125/40		Continuous 125/40 (H)		Continuous 105/40 (F)		Continuous 80/40 (B)	
Model	kVA	kW	kVA	kW	kVA	kW	kVA	kW	kVA	kW
<b>P80-HVSI804R</b>	2940.0	2352.0	2840.0	2272.0	N/A	N/A	<b>2650.0</b>	<b>2120.0</b>	2312.0	1849.6
<b>P80-HVSI804S</b>	3330.0	2664.0	3200.0	2560.0	N/A	N/A	<b>3000.0</b>	<b>2400.0</b>	2625.0	2100.0
<b>P80-HVSI804T</b>	3660.0	2928.0	3530.0	2824.0	N/A	N/A	<b>3300.0</b>	<b>2640.0</b>	2880.0	2304.0
<b>P80-HVSI804W</b>	4110.0	3288.0	3960.0	3168.0	N/A	N/A	<b>3724.0</b>	<b>2979.2</b>	3240.0	2592.0
<b>P80-HVSI804X</b>	4650.0	3720.0	4490.0	3592.0	N/A	N/A	<b>4214.0</b>	<b>3371.2</b>	3660.0	2928.0



# Notes



A large area of the page is filled with horizontal dotted lines, providing a space for handwritten notes.



# Notes



A large area of the page is filled with horizontal dotted lines, providing a space for handwritten notes.

# Application Engineering

Application Engineering generally owns the technical relationship with our customers and therefore is the first point of contact. The team's aim is to 'Delight our Customers' by providing a world class customer service by striving to understand customer needs and best matched products to suit each individual customer application.

Application teams are based in the US, Europe, India and China, sharing a common email enquiry database. Due to this, there are always Application Engineers available to support customer requirements and deliver the best technical product selection that NEWAGE | STAMFORD | AvK branded products can offer.

Key deliverables include:

- Provide technical data and support for Cummins Generator Technologies products
  - Technical data, drawings, application guidance notes
  - Size alternators for different load applications -motors, lighting, non-linear (UPS, VSD, SCR)
  - Advise and discuss all aspects of alternator application, control and installation

- Discuss needs, resolve issues and review specification
  - Provide qualified technical recommendations to ensure fit for purpose products
  - Assist with design and development of complete generating set systems
- Provide bespoke application engineering training to suit customer requirements
  - Application sizing
  - Alternator selection considerations
  - Changing market requirements such as grid codes or marine standards
- Provide Voice of Customer and application field knowledge into new product introduction or product improvement programs.

Application Engineering support customers as they venture into new market segments and integrate product designs to ensure superior fit to market. The team work closely with the Application Validation Team to validate and fully understand the operating boundaries of our products to ensure the right machines meet the harsh, increasingly challenging environments in which our customers operate in.



For Applications Support contact:  
[applications@cummins.com](mailto:applications@cummins.com)

**NEWAGE® | STAMFORD® | AvK®**

Powering the world with confidence since 1904



For Applications Support:  
[applications@cummins.com](mailto:applications@cummins.com)

For Customer Service:  
EMEA: [emea.service@cummins.com](mailto:emea.service@cummins.com)  
Americas: [cgta.service@cummins.com](mailto:cgta.service@cummins.com)  
China: [cgt.china.service@cummins.com](mailto:cgt.china.service@cummins.com)  
APAC: [apac.service@cummins.com](mailto:apac.service@cummins.com)  
India: [cgtil.csnotify@cummins.com](mailto:cgtil.csnotify@cummins.com)

For general enquiries:  
[newagestamfordavk@cummins.com](mailto:newagestamfordavk@cummins.com)  
[www.stamford-avk.com](http://www.stamford-avk.com)

**Disclaimer**

The ratings provided are for information only, the accuracy cannot be guaranteed as Cummins Generator Technologies has an ongoing process of development and reserves the right to change the contents of ratings book without notice and shall not be held responsible for any subsequent claims in relation to the content



**There for you™**

Copyright 2020, Cummins Generator Technologies Ltd. All rights reserved.  
Cummins and the Cummins logo are registered trade marks of Cummins Inc.  
NEWAGE, STAMFORD and AvK are registered trade marks of Cummins Generator Technologies Ltd.